

zowe

Welcome to Zowe CLI!

Zowe CLI is a command line interface (CLI) that provides a simple and streamlined way to interact with IBM z/OS.

For additional Zowe CLI documentation, visit <https://docs.zowe.org>

For Zowe CLI support, visit <https://www.zowe.org>

Global Options

- `--response-format-json` | `--rfj` (*boolean*)
 - Produce JSON formatted data from a command
- `--help` | `-h` (*boolean*)
 - Display help text
- `--help-examples` (*boolean*)
 - Not available for top tier Zowe group
- `--help-web` | `--hw` (*boolean*)
 - Display HTML help in browser

Table of Contents

- [auth](#)
 - [login | li](#)
 - [apiml](#)
 - [logout | lo](#)
 - [apiml](#)
- [cics](#)
 - [add-to-list | atl](#)
 - [csdGroup | csdg](#)
 - [define | def](#)
 - [program | prog](#)
 - [transaction | tran](#)
 - [urimap-client | uc](#)
 - [urimap-pipeline | up](#)
 - [urimap-server | us](#)
 - [webservice | web](#)
 - [delete | del](#)
 - [program | prog](#)
 - [transaction | tran](#)
 - [urimap](#)
 - [webservice | web](#)
 - [disable](#)
 - [urimap](#)
 - [discard | dis](#)
 - [program | prog](#)
 - [transaction | tran](#)
 - [urimap](#)
 - [enable | en](#)
 - [urimap](#)
 - [get](#)
 - [resource | res](#)
 - [install | ins](#)
 - [program | prog](#)
 - [transaction | tran](#)
 - [urimap](#)
 - [refresh | ref](#)
 - [program | prog](#)
 - [remove-from-list | rfl](#)
 - [csdGroup | csdg](#)

- config
 - auto-init
 - convert-profiles | convert
 - edit
 - import
 - init
 - list | ls
 - profiles
 - schema
 - secure
 - set
 - update-schemas | us
- daemon
 - disable
 - enable
 - restart
- db2
 - call
 - procedure | proc | sp
 - execute
 - sql
 - export
 - table
- ims
 - query | qry
 - program | pgm
 - region | reg
 - transaction | tran
 - start | sta
 - program | pgm
 - region | reg
 - transaction | tran
 - stop | sto
 - program | pgm
 - region | reg
 - transaction | tran
 - update | upd
 - program | pgm
 - transaction | tran
- mq

- run
 - mqsc
- plugins
 - install
 - list
 - uninstall
 - update
 - validate
- profiles
 - create | cre
 - base-profile | base
 - cics-profile | cics
 - db2-profile | db2
 - ims-profile | ims
 - mq-profile | mq
 - ssh-profile | ssh
 - tso-profile | tso
 - zftp-profile | zftp
 - zosmf-profile | zosmf
 - delete | rm
 - base-profile | base
 - cics-profile | cics
 - db2-profile | db2
 - ims-profile | ims
 - mq-profile | mq
 - ssh-profile | ssh
 - tso-profile | tso
 - zftp-profile | zftp
 - zosmf-profile | zosmf
 - list | ls
 - base-profiles | base
 - cics-profiles | cics
 - db2-profiles | db2
 - ims-profiles | ims
 - mq-profiles | mq
 - ssh-profiles | ssh
 - tso-profiles | tso
 - zftp-profiles | zftp
 - zosmf-profiles | zosmf
 - set-default | set

- base-profile | base
- cics-profile | cics
- db2-profile | db2
- ims-profile | ims
- mq-profile | mq
- ssh-profile | ssh
- tso-profile | tso
- zftp-profile | zftp
- zosmf-profile | zosmf
- update | upd
 - base-profile | base
 - cics-profile | cics
 - db2-profile | db2
 - ims-profile | ims
 - mq-profile | mq
 - ssh-profile | ssh
 - tso-profile | tso
 - zftp-profile | zftp
 - zosmf-profile | zosmf
- provisioning | pv
 - delete | del
 - instance | i
 - list | ls
 - catalog-templates | ct
 - instance-info | ii
 - instance-variables | iv
 - registry-instances | ri
 - template-info | ti
 - perform | perf
 - action | act
 - provision | prov
 - template | tem
- zos-console | console
 - collect
 - sync-responses | sr
 - issue
 - command | cmd
- zos-files | files
 - copy | cp
 - data-set | ds

- create | cre
 - data-set | ds
 - data-set-binary | bin
 - data-set-c | dsc
 - data-set-classic | classic
 - data-set-partitioned | pds
 - data-set-sequential | ps
 - data-set-vsam | vsam
 - uss-directory | dir
 - uss-file | file
 - zos-file-system | zfs
- delete | del
 - data-set | ds
 - data-set-vsam | vsam
 - migrated-data-set | mds
 - uss-file | uf | uss
 - zos-file-system | zfs
- download | dl
 - all-members | am
 - data-set | ds
 - uss-file | uf | uss
- invoke | call
 - ams-file | af
 - ams-statements | as
- list | ls
 - all-members | am
 - data-set | ds
 - file-system | fs
 - uss-files | uf | uss
- migrate | hmigr | hMigrate
 - data-set | ds
- mount
 - file-system | fs
- recall | hrec | hRecall
 - data-set | ds
- rename
 - data-set | ds
 - data-set-member | dsm
- unmount | umount
 - file-system | fs

- upload | ul
 - dir-to-pds | dtp
 - dir-to-uss | dtu
 - file-to-data-set | ftds
 - file-to-uss | ftu
 - stdin-to-data-set | stds
- zos-ftp | zftp
 - allocate | alloc
 - data-set | ds
 - delete | del
 - data-set | ds
 - job | j
 - uss-file | uss | uf
 - download | dl
 - all-spool-by-jobid | asbj
 - data-set | ds
 - uss-file | uss | uf
 - list | ls
 - data-set | ds
 - data-set-members | members
 - jobs | j | js
 - spool-files-by-jobid | sfbj
 - uss-files | uss | uf
 - make | mk
 - uss-directory | dir
 - rename | mv
 - data-set | ds
 - uss-file | uss | uf
 - submit | sub
 - data-set | ds
 - local-file | lf
 - stdin | si | in
 - upload | ul
 - file-to-data-set | ftds
 - file-to-uss-file | ftuf | ftu
 - stdin-to-data-set | stds
 - stdin-to-uss-file | stuf | stu
 - view | vw
 - all-spool-by-jobid | asbj
 - data-set | ds

- job-status-by-jobid | jsbj
- spool-file-by-id | sfbi
- uss-file | uss | uf
- zos-jobs | jobs
 - cancel | can
 - job
 - delete | del
 - job
 - download | dl
 - output | o
 - list | ls
 - jobs | js
 - spool-files-by-jobid | sfbj
 - submit | sub
 - data-set | ds
 - local-file | lf
 - stdin | in
 - view | vw
 - job-status-by-jobid | jsbj
 - spool-file-by-id | sfbi
- zos-logs | logs
 - list | ls
 - logs
- zos-ssh | ssh | zos-uss | uss
 - issue | iss
 - command | cmd | ssh
- zos-tso | tso
 - issue
 - command | cmd
 - ping
 - address-space | as
 - send
 - address-space | as
 - start | st
 - address-space | as
 - stop | sp
 - address-space | as
- zos-workflows | wf
 - archive
 - active-workflow | aw

- create | cre
 - workflow-from-data-set | wfds
 - workflow-from-local-file | wflf
 - workflow-from-uss-file | wfuf
- delete | del
 - active-workflow | aw
 - archived-workflow | arw
- list | ls
 - active-workflow-details | awd
 - active-workflows | aw
 - archived-workflows | arw
 - definition-file-details | dfd
- start | sta
 - workflow-full | wf
 - workflow-step | ws
- zosmf
 - check
 - status
 - list
 - systems

zowe › auth

Connect to Zowe API Mediation Layer authentication service and obtain a token, or disconnect from the authentication service and revoke the token.

The token provides authentication to services that support the API ML SSO (Single Sign-On) capability. When you log in, the token is stored in your default base profile until it expires. Base profiles store connection information shared by multiple services (e.g., z/OSMF), and are used if you do not supply connection information in a service profile. To take advantage of the API ML SSO capability, you should omit username and password in service profiles so that the token in the base profile is used.

zowe › auth › login

Log in to an authentication service.

zowe › auth › login › apiml

Log in to Zowe API Mediation Layer authentication service and obtain or update a token.

The token provides authentication to services that support the API ML SSO (Single Sign-On) capability. When you log in, the token is stored in your default base profile until it expires. Base profiles store connection information shared by multiple services (e.g., z/OSMF), and are used if you do not supply connection information in a service profile. To take advantage of the API ML SSO capability, you should omit username and password in service profiles so that the token in the base profile is used.

Usage

```
zowe auth login apiml [options]
```

Options

- `--show-token` | `--st` (*boolean*)
 - Show the token when login is successful. If specified, does not save the token to a profile.

Base Connection Options

- `--host` | `-H` (*string*)

- Host name of service on the mainframe.
- `--port` | `-P` (*number*)
 - Port number of service on the mainframe.
- `--user` | `-u` (*string*)
 - User name to authenticate to service on the mainframe.
- `--password` | `--pass` | `--pw` (*string*)
 - Password to authenticate to service on the mainframe.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
Default value: true
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Examples

- Log in to an API ML instance to obtain or update the token stored in your base profile:
 - `zowe auth login apiml`
- Log in to an API ML instance to obtain a token without storing it in a profile:
 - `zowe auth login apiml --show-token`

[zowe](#) › [auth](#) › [logout](#)

Log out of an authentication service.

[zowe](#) › [auth](#) › [logout](#) › [apiml](#)

Log out of the Zowe API Mediation Layer authentication service and revoke the token so it can no longer authenticate. Also remove the token from the default base profile, if it is stored on disk.

Usage

```
zowe auth logout apiml [options]
```

Base Connection Options

- `--host` | `-H` (*string*)
 - Host name of service on the mainframe.
- `--port` | `-P` (*number*)
 - Port number of service on the mainframe.
- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.

Allowed values: apimlAuthenticationToken, jwtToken, LtpaToken2

- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true

Profile Options

- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Examples

- Log out of an API ML instance to revoke the token that was in use and remove it from your base profile:

- `zowe auth logout apiml`
- Log out of an API ML instance to revoke a token that was not stored in a profile:
 - `zowe auth logout apiml --token-value <token>`

zowe › cics

Interact with IBM CICS programs and transactions.

zowe › cics › add-to-list

Add new resources (for example, CSD Groups to CSD Lists) to CICS through IBM CMCI.

zowe › cics › add-to-list › csdGroup

Add a CSD Group to a CICS CSD List.

Usage

```
zowe cics add-to-list csdGroup <name> <csdList> [options]
```

Positional Arguments

- `name` (*string*)
 - The name of the CSD Group to add. The maximum length of the CSD Group name is eight characters
- `csdList` (*string*)
 - The name of the CSD List to add the group to. The maximum length of the CSD List name is eight characters

Options

- `--region-name` (*string*)
 - The CICS region name to which to add the CSD Group to the CSD List
- `--cics-plex` (*string*)
 - The name of the CICSplex to which to add the CSD Group to the CSD List

Cics Connection Options

- `--host` | `-H` (*string*)
 - The CICS server host name.

- `--port` | `-P` (*number*)
 - The CICS server port.
 - Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (CICS) user name, which can be the same as your TSO login.
- `--password` | `--pw` (*string*)
 - Mainframe (CICS) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
 - Default value: true
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).
 - Default value: https
 - Allowed values: http, https

Profile Options

- `--cics-profile` | `--cics-p` (*string*)
 - The name of a (cics) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Add the CSD Group MYGRP to the CSD List MYLIST in the region named MYREG:
 - `zowe cics add-to-list csdGroup MYGRP MYLIST --region-name MYREG`

zowe › cics › define

Define new resources (for example, programs) to CICS through IBM CMCI.

zowe › cics › define › program

Define a new program to CICS.

Usage

```
zowe cics define program <programName> <csdGroup> [options]
```

Positional Arguments

- `programName` (*string*)
 - The name of the new program to define. The maximum length of the program name is eight characters.
- `csdGroup` (*string*)
 - The CICS system definition (CSD) Group for the new program that you want to define. The maximum length of the group name is eight characters.

Options

- `--region-name` (*string*)
 - The CICS region name to which to define the new program
- `--cics-plex` (*string*)

- The name of the CICSplex to which to define the new program

Cics Connection Options

- `--host` | `-H` (*string*)
 - The CICS server host name.
- `--port` | `-P` (*number*)
 - The CICS server port.
Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (CICS) user name, which can be the same as your TSO login.
- `--password` | `--pw` (*string*)
 - Mainframe (CICS) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
Default value: true
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).
Default value: https
Allowed values: http, https

Profile Options

- `--cics-profile` | `--cics-p` (*string*)
 - The name of a (cics) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)

- The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Define a program named PGM123 to the region name MYREGION in the CSD group MYGRP:
 - `zowe cics define program PGM123 MYGRP --region-name MYREGION`

[zowe](#) › [cics](#) › [define](#) › [transaction](#)

Define a new transaction to CICS.

Usage

```
zowe cics define transaction <transactionName> <programName> <csdGroup> [options]
```

Positional Arguments

- `transactionName` (*string*)
 - The name of the new transaction to define. The maximum length of the transaction name is four characters.
- `programName` (*string*)
 - The name of the program that the transaction uses. The maximum length of the program name is eight characters.
- `csdGroup` (*string*)
 - The CICS system definition (CSD) Group for the new transaction that you want to define. The maximum length of the group name is eight characters.

Options

- `--region-name` (*string*)
 - The CICS region name to which to define the new transaction
- `--cics-plex` (*string*)
 - The name of the CICSplex to which to define the new transaction

Cics Connection Options

- `--host` | `-H` (*string*)
 - The CICS server host name.
- `--port` | `-P` (*number*)
 - The CICS server port.
Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (CICS) user name, which can be the same as your TSO login.
- `--password` | `--pw` (*string*)
 - Mainframe (CICS) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
Default value: true
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).
Default value: https
Allowed values: http, https

Profile Options

- `--cics-profile` | `--cics-p` (*string*)
 - The name of a (cics) profile to load for this command execution.

- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Define a transaction named TRN1 for the program named PGM123 to the region named MYREGION in the CSD group MYGRP:
 - `zowe cics define transaction TRN1 PGM123 MYGRP --region-name MYREGION`

[zowe](#) › [cics](#) › [define](#) › [urimap-client](#)

Define a new URIMAP of type client to CICS. This acts as an HTTP(S) client

Usage

```
zowe cics define urimap-client <urimapName> <csdGroup> [options]
```

Positional Arguments

- `urimapName` (*string*)
 - The name of the URIMAP to create. The maximum length of the urimap name is eight characters.
- `csdGroup` (*string*)

- The CICS system definition (CSD) Group for the new urimap that you want to define. The maximum length of the group name is eight characters.

Required Options

- `--urimap-path` | `--up` (*string*)
 - The path component of the URI.
- `--urimap-host` | `--uh` (*string*)
 - The host component of the URI.

Options

- `--urimap-scheme` | `--us` (*string*)
 - The scheme component to be used with the request (http or https).

Default value: https
Allowed values: http, https
- `--authenticate` | `--auth` (*string*)
 - The authentication and identification scheme to be used for client URIMAPS.

Allowed values: NO, BASIC
- `--certificate` | `--cert` (*string*)
 - The label of a certificate in the keyring that is to be used as the client certificate in SSL handshakes
- `--description` | `--desc` (*string*)
 - Description of the URIMAP resource being defined.
- `--region-name` (*string*)
 - The CICS region name to which to define the new URIMAP.
- `--cics-plex` (*string*)
 - The name of the CICSplex to which to define the new URIMAP.
- `--enable` (*boolean*)

- Whether or not the URIMAP is to be enabled on install by default.

Default value: true

Cics Connection Options

- `--host` | `-H` (*string*)

- The CICS server host name.

- `--port` | `-P` (*number*)

- The CICS server port.

Default value: 443

- `--user` | `-u` (*string*)

- Mainframe (CICS) user name, which can be the same as your TSO login.

- `--password` | `--pw` (*string*)

- Mainframe (CICS) password, which can be the same as your TSO password.

- `--reject-unauthorized` | `--ru` (*boolean*)

- Reject self-signed certificates.

Default value: true

- `--protocol` | `-o` (*string*)

- Specifies CMCI protocol (http or https).

Default value: https

Allowed values: http, https

Profile Options

- `--cics-profile` | `--cics-p` (*string*)

- The name of a (cics) profile to load for this command execution.

- `--base-profile` | `--base-p` (*string*)

- The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Define a URIMAP named URIMAPA to the region named MYREGION in the CSD group MYGRP where the host is www.example.com and the path is /example/index.html:
 - ```
zowe cics define urimap-client URIMAPA MYGRP --urimap-path /example/index.html --urimap-host www.example.com --region-name MYREGION
```

## zowe › cics › define › urimap-pipeline

Define a new URIMAP of type pipeline to CICS. This processes incoming HTTP(S) requests

### Usage

```
zowe cics define urimap-pipeline <urimapName> <csdGroup> [options]
```

### Positional Arguments

- `urimapName` (*string*)
  - The name of the URIMAP to create. The maximum length of the urimap name is eight characters.
- `csdGroup` (*string*)
  - The CICS system definition (CSD) Group for the new urimap that you want to define. The maximum length of the group name is eight characters.

### Required Options

- `--urimap-path` | `--up` (*string*)
  - The path component of the URI.
- `--urimap-host` | `--uh` (*string*)
  - The host component of the URI.
- `--pipeline-name` | `--pn` (*string*)
  - The name of the PIPELINE resource definition for the URIMAP. The maximum length of the pipeline name is eight characters.

## Options

- `--urimap-scheme` | `--us` (*string*)
  - The scheme component to be used with the request (http or https).

Default value: https  
Allowed values: http, https
- `--description` | `--desc` (*string*)
  - Description of the URIMAP resource being defined.
- `--transaction-name` | `--tn` (*string*)
  - The name of the TRANSACTION resource definition for the URIMAP. The maximum length of the transaction name is four characters.
- `--webservice-name` | `--wn` (*string*)
  - The name of the WEBSERVICE resource definition for the URIMAP. The maximum length of the transaction name is 32 characters.
- `--tcpip-service` | `--tcpip` (*string*)
  - The TCPIP SERVICE to which the URIMAP definition applies.
- `--region-name` (*string*)
  - The CICS region name to which to define the new URIMAP.
- `--cics-plex` (*string*)
  - The name of the CICS Plex to which to define the new URIMAP.



- `--enable` (*boolean*)
  - Whether or not the URIMAP is to be enabled on install by default.Default value: true

## Cics Connection Options

- `--host` | `-H` (*string*)
  - The CICS server host name.
- `--port` | `-P` (*number*)
  - The CICS server port.Default value: 443
- `--user` | `-u` (*string*)
  - Mainframe (CICS) user name, which can be the same as your TSO login.
- `--password` | `--pw` (*string*)
  - Mainframe (CICS) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.Default value: true
- `--protocol` | `-o` (*string*)
  - Specifies CMCI protocol (http or https).Default value: https  
Allowed values: http, https

## Profile Options

- `--cics-profile` | `--cics-p` (*string*)
  - The name of a (cics) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Examples

- Define a URIMAP named URIMAPA for the pipeline named PIPE123 to the region named MYREGION in the CSD group MYGRP where the host is [www.example.com](http://www.example.com) and the path is `/example/index.html`:
  - ```
zowe cics define urimap-pipeline URIMAPA MYGRP --urimap-path /example/index.html --urimap-host www.example.com --pipeline-name PIPE123 --region-name MYREGION
```

[zowe](#) › [cics](#) › [define](#) › [urimap-server](#)

Define a new URIMAP of type server to CICS. This acts as an HTTP(S) server

Usage

```
zowe cics define urimap-server <urimapName> <csdGroup> [options]
```

Positional Arguments

- `urimapName` (*string*)
 - The name of the URIMAP to create. The maximum length of the urimap name is eight characters.
- `csdGroup` (*string*)

- The CICS system definition (CSD) Group for the new urimap that you want to define. The maximum length of the group name is eight characters.

Required Options

- `--urimap-path` | `--up` (*string*)
 - The path component of the URI.
- `--urimap-host` | `--uh` (*string*)
 - The host component of the URI.
- `--program-name` | `--pn` (*string*)
 - The application program that makes or handles the requests.

Options

- `--urimap-scheme` | `--us` (*string*)
 - The scheme component to be used with the request (http or https).

Default value: https
Allowed values: http, https
- `--description` | `--desc` (*string*)
 - Description of the URIMAP resource being defined.
- `--tcpip-service` | `--tcpip` (*string*)
 - The TCPIP SERVICE to which the URIMAP definition applies.
- `--region-name` (*string*)
 - The CICS region name to which to define the new URIMAP.
- `--cics-plex` (*string*)
 - The name of the CICS Plex to which to define the new URIMAP.
- `--enable` (*boolean*)
 - Whether or not the URIMAP is to be enabled on install by default.

Default value: true

Cics Connection Options

- `--host` | `-H` (*string*)
 - The CICS server host name.
- `--port` | `-P` (*number*)
 - The CICS server port.
 - Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (CICS) user name, which can be the same as your TSO login.
- `--password` | `--pw` (*string*)
 - Mainframe (CICS) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
 - Default value: true
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).
 - Default value: https
 - Allowed values: http, https

Profile Options

- `--cics-profile` | `--cics-p` (*string*)
 - The name of a (cics) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)

- The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Define a URIMAP named URIMAPA for the program named PGM123 to the region named MYREGION in the CSD group MYGRP where the host is www.example.com and the path is `/example/index.html`:

```
zowe cics define urimap-server URIMAPA MYGRP --urimap-path
/example/index.html --urimap-host www.example.com --program-name PGM123 --
region-name MYREGION
```

[zowe](#) › [cics](#) › [define](#) › [webservice](#)

Define a new web service to CICS.

Usage

```
zowe cics define webservice <webserviceName> <csdGroup> [options]
```

Positional Arguments

- `webserviceName` (*string*)
 - The name of the WEBSERVICE to create. The maximum length of the web service name is eight characters.
- `csdGroup` (*string*)
 - The CICS system definition (CSD) Group for the new web service that you want to define. The maximum length of the group name is eight characters.

Required Options

- `--pipeline-name` | `--pn` (*string*)
 - The name of the PIPELINE resource definition for the web service. The maximum length of the pipeline name is eight characters
- `--wsbind` (*string*)
 - The file name of the web service binding file on HFS.

Options

- `--description` | `--desc` (*string*)
 - Description of the web service resource being defined.
- `--validation` (*boolean*)
 - Specifies whether full validation of SOAP messages against the corresponding schema in the web service description should be performed at run time.

Default value: false
- `--wsdlfile` | `--wsdl` (*string*)
 - The file name of the web service description (WSDL) file on HFS.
- `--region-name` (*string*)
 - The CICS region name to which to define the new web service.
- `--cics-plex` (*string*)
 - The name of the CICSplex to which to define the new web service.

Cics Connection Options

- `--host` | `-H` (*string*)
 - The CICS server host name.
- `--port` | `-P` (*number*)
 - The CICS server port.

Default value: 443
- `--user` | `-u` (*string*)

- Mainframe (CICS) user name, which can be the same as your TSO login.
- `--password` | `--pw` (*string*)
 - Mainframe (CICS) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).

Default value: https
Allowed values: http, https

Profile Options

- `--cics-profile` | `--cics-p` (*string*)
 - The name of a (cics) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Define a webservice named WEBSVCA for the pipeline named PIPE123 to the region named MYREGION in the CSD group MYGRP where the binding file is /u/exampleapp/wsbind/example.log:
 - `zowe cics define webservice WEBSVCA MYGRP --pipeline-name PIPELINE --wsbind /u/exampleapp/wsbind/example.log --region-name MYREGION`

zowe › cics › delete

Delete resources (for example, programs) from CICS through IBM CMCI.

zowe › cics › delete › program

Delete a program from CICS.

Usage

```
zowe cics delete program <programName> <csdGroup> [options]
```

Positional Arguments

- `programName` (*string*)
 - The name of the program to delete. The maximum length of the program name is eight characters.
- `csdGroup` (*string*)
 - The CICS system definition (CSD) Group for the program that you want to delete. The maximum length of the group name is eight characters.

Options

- `--region-name` (*string*)
 - The CICS region name from which to delete the program
- `--cics-plex` (*string*)
 - The name of the CICSplex from which to delete the program

Cics Connection Options

- `--host` | `-H` (*string*)
 - The CICS server host name.
- `--port` | `-P` (*number*)
 - The CICS server port.
Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (CICS) user name, which can be the same as your TSO login.
- `--password` | `--pw` (*string*)
 - Mainframe (CICS) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
Default value: true
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).
Default value: https
Allowed values: http, https

Profile Options

- `--cics-profile` | `--cics-p` (*string*)
 - The name of a (cics) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.

- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Delete a program named PGM123 from the region named MYREGION:
 - `zowe cics delete program PGM123 --region-name MYREGION`

[zowe](#) › [cics](#) › [delete](#) › [transaction](#)

Delete a transaction from CICS.

Usage

```
zowe cics delete transaction <transactionName> <csdGroup> [options]
```

Positional Arguments

- `transactionName` (*string*)
 - The name of the transaction to delete. The maximum length of the transaction name is four characters.
- `csdGroup` (*string*)
 - The CICS system definition (CSD) Group for the transaction that you want to delete. The maximum length of the group name is eight characters.

Options

- `--region-name` (*string*)
 - The CICS region name from which to delete the transaction
- `--cics-plex` (*string*)
 - The name of the CICSplex from which to delete the transaction

Cics Connection Options

- `--host` | `-H` (*string*)
 - The CICS server host name.
- `--port` | `-P` (*number*)
 - The CICS server port.
 - Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (CICS) user name, which can be the same as your TSO login.
- `--password` | `--pw` (*string*)
 - Mainframe (CICS) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
 - Default value: true
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).
 - Default value: https
 - Allowed values: http, https

Profile Options

- `--cics-profile` | `--cics-p` (*string*)
 - The name of a (cics) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)

- The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Delete a transaction named TRN1 from the region named MYREGION:
 - `zowe cics delete transaction TRN1 MYGRP --region-name MYREGION`

[zowe](#) › [cics](#) › [delete](#) › [urimap](#)

Delete a urimap from CICS.

Usage

```
zowe cics delete urimap <urimapName> <csdGroup> [options]
```

Positional Arguments

- `urimapName` (*string*)
 - The name of the urimap to delete. The maximum length of the urimap name is eight characters.
- `csdGroup` (*string*)
 - The CICS system definition (CSD) Group for the urimap that you want to delete. The maximum length of the group name is eight characters.

Options

- `--region-name` (*string*)
 - The CICS region name from which to delete the urimap

Cics Connection Options

- `--host` | `-H` (*string*)
 - The CICS server host name.
- `--port` | `-P` (*number*)
 - The CICS server port.
Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (CICS) user name, which can be the same as your TSO login.
- `--password` | `--pw` (*string*)
 - Mainframe (CICS) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
Default value: true
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).
Default value: https
Allowed values: http, https

Profile Options

- `--cics-profile` | `--cics-p` (*string*)
 - The name of a (cics) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)

- The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Delete a urimap named URIMAPA from the region named MYREGION belonging to the csdgroup MYGRP:
 - `zowe cics delete urimap URIMAPA MYGRP --region-name MYREGION`

zowe › cics › delete › webservice

Delete a web service from CICS.

Usage

```
zowe cics delete webservice <webserviceName> <csdGroup> [options]
```

Positional Arguments

- `webserviceName` (*string*)
 - The name of the web service to delete. The maximum length of the web service name is eight characters.
- `csdGroup` (*string*)
 - The CICS system definition (CSD) Group for the web service that you want to delete. The maximum length of the group name is eight characters.

Options

- `--region-name` (*string*)

- The CICS region name from which to delete the web service

Cics Connection Options

- `--host` | `-H` (*string*)
 - The CICS server host name.
- `--port` | `-P` (*number*)
 - The CICS server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (CICS) user name, which can be the same as your TSO login.
- `--password` | `--pw` (*string*)
 - Mainframe (CICS) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).

Default value: https
Allowed values: http, https

Profile Options

- `--cics-profile` | `--cics-p` (*string*)
 - The name of a (cics) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)

- The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Delete a web service named WEBSVCA from the region named MYREGION belonging to the csdgroup MYGRP:
 - `zowe cics delete webservice WEBSVCA MYGRP --region-name MYREGION`

[zowe](#) › [cics](#) › [disable](#)

Disable resources (for example, urimaps) from CICS through IBM CMCI.

[zowe](#) › [cics](#) › [disable](#) › [urimap](#)

Disable a urimap from CICS.

Usage

```
zowe cics disable urimap <urimapName> [options]
```

Positional Arguments

- `urimapName` (*string*)
 - The name of the urimap to disable. The maximum length of the urimap name is eight characters.

Options

- `--region-name` (*string*)

- The CICS region name in which to disable the urimap

Cics Connection Options

- `--host` | `-H` (*string*)
 - The CICS server host name.
- `--port` | `-P` (*number*)
 - The CICS server port.
Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (CICS) user name, which can be the same as your TSO login.
- `--password` | `--pw` (*string*)
 - Mainframe (CICS) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
Default value: true
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).
Default value: https
Allowed values: http, https

Profile Options

- `--cics-profile` | `--cics-p` (*string*)
 - The name of a (cics) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)

- The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Disable a urimap named URIMAPA from the region named MYREGION:
 - `zowe cics disable urimap URIMAPA --region-name MYREGION`

zowe › cics › discard

Discard resources (for example, programs) from CICS through IBM CMCI.

zowe › cics › discard › program

Discard a program from CICS.

Usage

```
zowe cics discard program <programName> [options]
```

Positional Arguments

- `programName` (*string*)
 - The name of the program to discard. The maximum length of the program name is eight characters.

Options

- `--region-name` (*string*)
 - The CICS region name from which to discard the program

- `--cics-plex` (*string*)
 - The name of the CICSplex from which to discard the program

Cics Connection Options

- `--host` | `-H` (*string*)
 - The CICS server host name.
- `--port` | `-P` (*number*)
 - The CICS server port.
Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (CICS) user name, which can be the same as your TSO login.
- `--password` | `--pw` (*string*)
 - Mainframe (CICS) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
Default value: true
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).
Default value: https
Allowed values: http, https

Profile Options

- `--cics-profile` | `--cics-p` (*string*)
 - The name of a (cics) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Discard a program named PGM123 from the region named MYREGION:
 - `zowe cics discard program PGM123 --region-name MYREGION`

[zowe](#) › [cics](#) › [discard](#) › [transaction](#)

Discard a transaction from CICS.

Usage

```
zowe cics discard transaction <transactionName> [options]
```

Positional Arguments

- `transactionName` (*string*)
 - The name of the transaction to discard. The maximum length of the transaction name is four characters.

Options

- `--region-name` (*string*)
 - The CICS region name from which to discard the transaction
- `--cics-plex` (*string*)
 - The name of the CICSplex from which to discard the transaction

Cics Connection Options

- `--host` | `-H` (*string*)
 - The CICS server host name.
- `--port` | `-P` (*number*)
 - The CICS server port.
Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (CICS) user name, which can be the same as your TSO login.
- `--password` | `--pw` (*string*)
 - Mainframe (CICS) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
Default value: true
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).
Default value: https
Allowed values: http, https

Profile Options

- `--cics-profile` | `--cics-p` (*string*)
 - The name of a (cics) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)

- The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Discard a transaction named TRN1 from the region named MYREGION:
 - `zowe cics discard transaction TRN1 --region-name MYREGION`

[zowe](#) › [cics](#) › [discard](#) › [urimap](#)

Discard a urimap from CICS.

Usage

```
zowe cics discard urimap <urimapName> [options]
```

Positional Arguments

- `urimapName` (*string*)
 - The name of the urimap to discard. The maximum length of the urimap name is eight characters.

Options

- `--region-name` (*string*)
 - The CICS region name from which to discard the urimap

Cics Connection Options

- `--host` | `-H` (*string*)
 - The CICS server host name.

- `--port` | `-P` (*number*)
 - The CICS server port.
 - Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (CICS) user name, which can be the same as your TSO login.
- `--password` | `--pw` (*string*)
 - Mainframe (CICS) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
 - Default value: true
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).
 - Default value: https
 - Allowed values: http, https

Profile Options

- `--cics-profile` | `--cics-p` (*string*)
 - The name of a (cics) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Discard a urimap named URIMAPA from the region named MYREGION:
 - `zowe cics discard urimap URIMAPA --region-name MYREGION`

zowe › cics › enable

Enable resources (for example, urimaps) from CICS through IBM CMCI.

zowe › cics › enable › urimap

Enable a urimap from CICS.

Usage

```
zowe cics enable urimap <urimapName> [options]
```

Positional Arguments

- `urimapName` (*string*)
 - The name of the urimap to enable. The maximum length of the urimap name is eight characters.

Options

- `--region-name` (*string*)
 - The CICS region name in which to enable the urimap

Cics Connection Options

- `--host` | `-H` (*string*)
 - The CICS server host name.
- `--port` | `-P` (*number*)

- The CICS server port.

Default value: 443

- `--user` | `-u` (*string*)
 - Mainframe (CICS) user name, which can be the same as your TSO login.
- `--password` | `--pw` (*string*)
 - Mainframe (CICS) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).

Default value: https
Allowed values: http, https

Profile Options

- `--cics-profile` | `--cics-p` (*string*)
 - The name of a (cics) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)

- The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Enable a urimap named URIMAPA from the region named MYREGION:
 - `zowe cics enable urimap URIMAPA --region-name MYREGION`

zowe › cics › get

Get resources (for example, programs or transactions) from CICS through IBM CMCI.

zowe › cics › get › resource

Get resources (for example, programs or transactions) from CICS.

Usage

```
zowe cics get resource <resourceName> [options]
```

Positional Arguments

- `resourceName` (*string*)
 - The name of the resource to get.

Options

- `--region-name` | `--rn` (*string*)
 - The CICS region name from which to get the resources
- `--cics-plex` | `--cp` (*string*)
 - The name of the CICSplex from which to get the resources
- `--criteria` | `-c` (*string*)
 - The criteria by which to filter the resource
- `--parameter` | `-p` (*string*)

- The parameter by which to refine the resource

Cics Connection Options

- `--host` | `-H` (*string*)
 - The CICS server host name.
- `--port` | `-P` (*number*)
 - The CICS server port.
Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (CICS) user name, which can be the same as your TSO login.
- `--password` | `--pw` (*string*)
 - Mainframe (CICS) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
Default value: true
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).
Default value: https
Allowed values: http, https

Profile Options

- `--cics-profile` | `--cics-p` (*string*)
 - The name of a (cics) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)

- The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Response Format Options

- `--response-format-filter` | `--rff` (*array*)
 - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '--response-format-type' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
 - The command response output format type. Must be one of the following:

table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.

list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.

object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
 - If "--response-format-type table" is specified, include the column headers in the output.

Examples

- Get program resources from the region named MYREGION:
 - `zowe cics get resource CICSPROGRAM --region-name MYREGION`
- Get local transaction resources from the region named MYREGION:
 - `zowe cics get resource CICSLOCALTRANSACTION --region-name MYREGION`
- Get local file resources from the region named MYREGION:
 - `zowe cics get resource CICSLOCALFILE --region-name MYREGION`
- Get program definition resources from the CSD group named GRP1 and the region named MYREGION:
 - `zowe cics get resource CICSDEFINITIONPROGRAM --region-name MYREGION --parameter "CSDGROUP(GRP1)"`
- Get transaction definition resources from the CSD group named GRP1 and the region named MYREGION:
 - `zowe cics get resource CICSDEFINITIONTRANSACTION --region-name MYREGION --parameter "CSDGROUP(GRP1)"`
- Get URIMap definition resources from the CSD group named GRP1 and the region named MYREGION:
 - `zowe cics get resource CICSDEFINITIONURIMAP --region-name MYREGION --parameter "CSDGROUP(GRP1)"`
- Get program resources that start with the name PRG from the region named MYREGION:
 - `zowe cics get resource CICSPROGRAM --region-name MYREGION --criteria "PROGRAM=PRG*"`
- Get a local transaction resource named TRAN from the region named MYREGION:
 - `zowe cics get resource CICSLOCALTRANSACTION --region-name MYREGION --criteria "TRANID=TRAN"`
- Get program resources that start with the name MYPRG from the region named MYREGION and display various fields as a table:
 - `zowe cics get resource CICSPROGRAM --region-name MYREGION --criteria "PROGRAM=MYPRG*" --rft table --rfh --rff program length status`

zowe › cics › install

Install resources (for example, programs) to CICS through IBM CMCI.

zowe › cics › install › program

Install a program to CICS.

Usage

```
zowe cics install program <programName> <csdGroup> [options]
```

Positional Arguments

- `programName` (*string*)
 - The name of the program to install. The maximum length of the program name is eight characters.
- `csdGroup` (*string*)
 - The CICS system definition (CSD) Group for the program that you want to install. The maximum length of the group name is eight characters.

Options

- `--region-name` (*string*)
 - The CICS region name to which to install the program
- `--cics-plex` (*string*)
 - The name of the CICSplex to which to install the program

Cics Connection Options

- `--host` | `-H` (*string*)
 - The CICS server host name.
- `--port` | `-P` (*number*)
 - The CICS server port.

Default value: 443

- `--user` | `-u` (*string*)
 - Mainframe (CICS) user name, which can be the same as your TSO login.
- `--password` | `--pw` (*string*)
 - Mainframe (CICS) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).

Default value: https
Allowed values: http, https

Profile Options

- `--cics-profile` | `--cics-p` (*string*)
 - The name of a (cics) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)

- The file path to a certificate key file to use for authentication

Examples

- Install a program named PGM123 to the region named MYREGION in the CSD group MYGRP:
 - `zowe cics install program PGM123 MYGRP --region-name MYREGION`

zowe › cics › install › transaction

Install a transaction to CICS.

Usage

```
zowe cics install transaction <transactionName> <csdGroup> [options]
```

Positional Arguments

- `transactionName` (*string*)
 - The name of the transaction to install. The maximum length of the transaction name is four characters.
- `csdGroup` (*string*)
 - The CICS system definition (CSD) Group for the transaction that you want to install. The maximum length of the group name is eight characters.

Options

- `--region-name` (*string*)
 - The CICS region name to which to install the transaction
- `--cics-plex` (*string*)
 - The name of the CICSplex to which to install the transaction

Cics Connection Options

- `--host` | `-H` (*string*)
 - The CICS server host name.
- `--port` | `-P` (*number*)

- The CICS server port.

Default value: 443

- `--user` | `-u` (*string*)
 - Mainframe (CICS) user name, which can be the same as your TSO login.
- `--password` | `--pw` (*string*)
 - Mainframe (CICS) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
Default value: true
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).
Default value: https
Allowed values: http, https

Profile Options

- `--cics-profile` | `--cics-p` (*string*)
 - The name of a (cics) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)

- The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Install a transaction named TRN1 to the region named MYREGION in the CSD group MYGRP:
 - `zowe cics install transaction TRN1 MYGRP --region-name MYREGION`

[zowe](#) › [cics](#) › [install](#) › [urimap](#)

Install a urimap to CICS.

Usage

```
zowe cics install urimap <urimapName> <csdGroup> [options]
```

Positional Arguments

- `urimapName` (*string*)
 - The name of the urimap to install. The maximum length of the urimap name is eight characters.
- `csdGroup` (*string*)
 - The CICS system definition (CSD) Group for the urimap that you want to install. The maximum length of the group name is eight characters.

Options

- `--region-name` (*string*)
 - The CICS region name to which to install the urimap

Cics Connection Options

- `--host` | `-H` (*string*)
 - The CICS server host name.
- `--port` | `-P` (*number*)

- The CICS server port.

Default value: 443

- `--user` | `-u` (*string*)
 - Mainframe (CICS) user name, which can be the same as your TSO login.
- `--password` | `--pw` (*string*)
 - Mainframe (CICS) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).

Default value: https
Allowed values: http, https

Profile Options

- `--cics-profile` | `--cics-p` (*string*)
 - The name of a (cics) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)

- The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Install a urimap named URIMAPA to the region named MYREGION belonging to the csdgroup MYGRP:
 - `zowe cics install urimap URIMAPA CSDGROUP --region-name MYREGION`

zowe › cics › refresh

Refresh a program on CICS through IBM CMCI.

zowe › cics › refresh › program

Refresh a program on CICS.

Usage

```
zowe cics refresh program <programName> [options]
```

Positional Arguments

- `programName` (*string*)
 - The name of the program to refresh. The maximum length of the program name is eight characters.

Options

- `--region-name` (*string*)
 - The CICS region name on which you want to refresh the program
- `--cics-plex` (*string*)
 - The name of the CICSplex on which to refresh the program

Cics Connection Options

- `--host` | `-H` (*string*)

- The CICS server host name.
- `--port` | `-P` (*number*)
 - The CICS server port.
 - Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (CICS) user name, which can be the same as your TSO login.
- `--password` | `--pw` (*string*)
 - Mainframe (CICS) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
 - Default value: true
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).
 - Default value: https
 - Allowed values: http, https

Profile Options

- `--cics-profile` | `--cics-p` (*string*)
 - The name of a (cics) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)

- The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Refresh a program named PGM123 from the region named MYREGION:
 - `zowe cics refresh program PGM123 --region-name MYREGION`

zowe › cics › remove-from-list

Remove resources (for example, CSD Groups in CSD Lists) from CICS through IBM CMCI.

zowe › cics › remove-from-list › csdGroup

Remove a CSD Group from a CICS CSD List.

Usage

```
zowe cics remove-from-list csdGroup <name> <csdList> [options]
```

Positional Arguments

- `name` (*string*)
 - The name of the CSD Group to remove. The maximum length of the CSD Group name is eight characters
- `csdList` (*string*)
 - The name of the CSD List to remove the group from. The maximum length of the CSD List name is eight characters

Options

- `--region-name` (*string*)
 - The CICS region name to which to remove the CSD Group from the CSD List

- `--cics-plex` (*string*)
 - The name of the CICSplex to which to remove the CSD Group from the CSD List

Cics Connection Options

- `--host` | `-H` (*string*)
 - The CICS server host name.
- `--port` | `-P` (*number*)
 - The CICS server port.
Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (CICS) user name, which can be the same as your TSO login.
- `--password` | `--pw` (*string*)
 - Mainframe (CICS) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
Default value: true
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).
Default value: https
Allowed values: http, https

Profile Options

- `--cics-profile` | `--cics-p` (*string*)
 - The name of a (cics) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Remove the CSD Group MYGRP from the CSD List MYLIST in the region named MYREG:
 - `zowe cics remove-from-list csdGroup MYGRP MYLIST --region-name MYREG`

zowe › config

Manage JSON project and global configuration

zowe › config › auto-init

Automatically generate a config from APIML

Usage

zowe config auto-init [options]

Automatic Config Initialization Options

- `--user-config` | `--uc` (*boolean*)
 - Save config in the user layer
 - Default value: false
- `--global-config` | `--gc` (*boolean*)
 - Save config in the global layer
 - Default value: false
- `--dry-run` | `--dr` | `--dry` (*boolean*)
 - Display the outcome of the initialization without saving
- `--edit` | `-e` (*boolean*)
 - Open in editor after initializing the configuration
- `--overwrite` | `--ow` (*boolean*)
 - Replaces an existing configuration with a new configuration
 - Default value: false
- `--for-sure` | `-f` (*boolean*)
 - Confirms the overwrite option
 - Default value: false

APIML Connection Options

- `--host` | `-H` (*string*)
 - Host name of the mainframe running the API Mediation Layer.
- `--port` | `-P` (*number*)
 - Port number of API Mediation Layer on the mainframe.
- `--user` | `-u` (*string*)
 - User name to authenticate to the API Mediation Layer on the mainframe.
- `--password` | `--pass` | `--pw` (*string*)
 - Password to authenticate to the API Mediation Layer on the mainframe.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API Mediation Layer. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API Mediation Layer.

Profile Options

- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

[zowe](#) › [config](#) › [convert-profiles](#)

Convert v1 profiles to a global zowe.config.json file.

Usage

`zowe config convert-profiles [options]`

Options

- `--prompt` (*boolean*)
 - Prompt for confirmation. Use `--no-prompt` to disable prompting.
Default value: true
- `--delete` (*boolean*)
 - Delete the existing profiles on disk and any securely stored secrets.

Examples

- Convert profiles to team config without prompting:
 - `zowe config convert-profiles --no-prompt`
- Convert profiles to team config and delete the old profiles:
 - `zowe config convert-profiles --delete`

[zowe](#) › [config](#) › [edit](#)

Edit an existing config file in your system's default text editor.

In a graphical environment, the application associated with JSON files will be launched. In a command-line environment, vi will be launched. To override the command-line editor used, specify it in the `ZOWE_EDITOR` environment variable.

Usage

```
zowe config edit [options]
```

Options

- `--global-config` | `--gc` (*boolean*)
 - Target the global config files.
Default value: false
- `--user-config` | `--uc` (*boolean*)
 - Target the user config files.
Default value: false

Examples

- Edit global config file:
 - `zowe config edit --global-config`

zowe › config › import

Import config files from another location on disk or from an Internet URL.

If the config ``$schema`` property points to a relative path, the schema will also be imported.

Usage

```
zowe config import <location> [options]
```

Positional Arguments

- `location` (*string*)
 - File path or URL to import from.

Options

- `--global-config` | `--gc` (*boolean*)
 - Target the global config files.
 - Default value: false
- `--user-config` | `--uc` (*boolean*)
 - Target the user config files.
 - Default value: false
- `--overwrite` | `--ow` (*boolean*)
 - Overwrite config file if one already exists.
 - Default value: false

Examples

- Import config from local file on disk:
 - `zowe config import ~/Downloads/zowe.config.json`

- Import global config from Internet URL:

- `zowe config import https://example.com/zowe.config.json --global-config`

zowe › **config** › **init**

Initialize config files. Defaults to initializing "zowe.config.json" in the current working directory unless otherwise specified.

Use "--user-config" to init "zowe.config.user.json". Use "--global-config" to initialize the configuration files in your home "~/.zowe" directory.

Use "--no-prompt" to skip prompting for values in a CI environment.

Usage

`zowe config init [options]`

Options

- `--global-config` | `--gc` (*boolean*)
 - Target the global config files.
Default value: false
- `--user-config` | `--uc` (*boolean*)
 - Target the user config files.
Default value: false
- `--prompt` (*boolean*)
 - Prompt for missing values in the base profile. Useful for disabling prompting in CI environments.
Default value: true
- `--overwrite` | `--ow` (*boolean*)
 - Replace existing config files instead of merging the new changes.
- `--for-sure` | `--fs` (*boolean*)
 - Confirms the overwrite option.

Default value: false

- `--dry-run` | `--dr` | `--dry` (*boolean*)
 - Display the outcome of the initialization without saving it.
- `--edit` | `-e` (*boolean*)
 - Open in editor after initializing the configuration

Examples

- Initialize configuration files in your home "~/.zowe" directory.:
 - `zowe config init --global-config`
- Do a dry run of initializing configuration files in your home "~/.zowe" directory.:
 - `zowe config init --global-config --dry-run`
- Initialize the user config files.:
 - `zowe config init --user-config`
- Initialize the user config files and do not prompt for secure values.:
 - `zowe config init --user-config --prompt false`
- Do a dry run of initializing the user config files and do not prompt for secure values.:
 - `zowe config init --user-config --prompt false --dry-run`
- Overwrite any existing global config files.:
 - `zowe config init --global-config --overwrite --for-sure`
- Overwrite any existing user config files.:
 - `zowe config init --user-config --overwrite --for-sure`

[zowe](#) › [config](#) › [list](#)

List config properties

Usage

```
zowe config list [property] [options]
```

Positional Arguments

- `property` (*string*)
 - The config property to list. Blank to list all properties.

Options

- `--locations` (*boolean*)
 - Separate the config properties into their respective config file locations. Helpful to determine where configuration value is specified.
- `--root` (*boolean*)
 - List only the root level property names. For example, specify in addition to '--locations' to get a list of config file paths only.

Examples

- List property names for a specified config property.:
 - `zowe config list "defaults"`
- List only root level property names for a specified config property.:
 - `zowe config list "defaults" --root`
- List config properties by separating them by their respective config file locations.:
 - `zowe config list --locations`
- List only the root level configuration property names.:
 - `zowe config list --root`
- List only the root level configuration properties by separating them by their respective config file locations.:
 - `zowe config list --locations --root`

[zowe](#) › [config](#) › [profiles](#)

Displays profile paths.

Usage

zowe config profiles [options]

Examples

- Display profile paths.:
 - `zowe config profiles`

zowe › config › schema

Dumps the JSON schema for the config. The schema is dynamically created based on your available plugins. Direct the output of this command to a file and include in your config with '\$schema' property to get editor completion.

Usage

zowe config schema [options]

Examples

- Display the JSON schema for the config.:
 - `zowe config schema`

zowe › config › secure

prompt for secure configuration properties

Usage

zowe config secure [options]

Options

- `--global-config` | `--gc` (*boolean*)
 - Secure properties in global config.
Default value: false
- `--user-config` | `--uc` (*boolean*)
 - Secure properties in user config.
Default value: false

Examples

- Secure the properties in global config.:
 - `zowe config secure --global-config`
- Secure the properties in user config.:
 - `zowe config secure --user-config`

zowe › config › set

create or update a configuration property

Usage

`zowe config set <property> [value] [options]`

Positional Arguments

- `property` (*string*)
 - The property to set. You may specify a path using dot notation (e.g. `profiles.host1.profiles.service1.properties.setting`)
- `value` (*string*)
 - The property value to set. The value may be JSON. Use `'--json'` to indicate.

Options

- `--global-config` | `--gc` (*boolean*)
 - Set the property in global config.
Default value: false
- `--user-config` | `--uc` (*boolean*)
 - Set the property in user config.
Default value: false
- `--json` (*boolean*)
 - The property value is JSON.

Default value: false

- `--secure` (*boolean*)
 - Store the property value securely. If omitted, any property named in the secure array of the config file will be saved securely.

Examples

- Set the property in global config.:
 - `zowe config set "profiles.host1.profiles.service1.properties.setting" "value" --global-config`
- Set the property in user config.:
 - `zowe config set "profiles.host1.profiles.service2.properties.setting" "value" --user-config`
- Set property value to JSON.:
 - `zowe config set "profiles.host1.profiles.service3.properties.setting" '{"property":"value"}' --json`
- Store the property value:
 - `zowe config set "profiles.host1.profiles.service1.properties.setting" "value" --secure`

[zowe](#) › [config](#) › [update-schemas](#)

Update schema files by looking up the directory structure.

Schema files up in higher level directories will always be updated. To also update schema files down in lower level directories, specify the `--depth` flag.

Usage

```
zowe config update-schemas [options]
```

Options

- `--depth` (*number*)
 - Specifies how many levels down the directory structure should the schemas be updated.

Default value: 0

Examples

- Update all schema files found in higher level directories:
 - `zowe config update-schemas`
- Update all schema files found in higher level directories and 2 levels down the directory structure:
 - `zowe config update-schemas --depth 2`

zowe › daemon

Perform operations that control the daemon-mode functionality of the Zowe CLI. Daemon-mode runs the CLI command processor as a daemon to improve performance.

zowe › daemon › disable

Disables daemon-mode operation of the Zowe CLI.

Usage

zowe daemon disable [options]

Examples

- Disable daemon-mode:
 - `zowe daemon disable`

zowe › daemon › enable

Enables daemon-mode operation of the Zowe CLI. You only need to run the enable command once after each new installation of the Zowe CLI. Afterwards, any zowe command will automatically start a daemon as needed.

Usage

zowe daemon enable [options]

Examples

- Enable daemon-mode:
 - `zowe daemon enable`

zowe › daemon › restart

Restart the Zowe CLI daemon.

Usage

zowe daemon restart [options]

Examples

- Restart daemon:
 - `zowe daemon restart`

zowe › db2

Interact with IBM Db2 for z/OS

zowe › db2 › call

Call a Db2 stored procedure

zowe › db2 › call › procedure

Call a Db2 stored procedure. Specify the stored procedure name and optionally provide values.

Usage

```
zowe db2 call procedure <routine> [options]
```

Positional Arguments

- `routine` (*string*)
 - The name of a Db2 stored procedure

Options

- `--parameters` | `-p` (*array*)
 - Values to bind to the stored procedure parameters

DB2 Connection Options

- `--host` | `-H` (*string*)
 - The Db2 server host name
- `--port` | `-P` (*number*)
 - The Db2 server port number
- `--user` | `-u` (*string*)
 - The Db2 user ID (may be the same as the TSO login)
- `--password` | `--pass` | `--pw` (*string*)

- The Db2 password (may be the same as the TSO password)
- `--database` | `--db` (*string*)
 - The name of the database
- `--sslFile` | `--ssl` (*string*)
 - Path to an SSL Certificate file

Profile Options

- `--db2-profile` | `--db2-p` (*string*)
 - The name of a (db2) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
 - Default value: true
- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Call stored procedure DEMO.SP1:

- `zowe db2 call procedure "DEMO.SP1"`
- Call a stored procedure and pass values for parameter indicators:
 - `zowe db2 call procedure "DEMO.SP2(?, ?)" --parameters "Hello" "world!"`
- Call a stored procedure and pass values for two output parameters. The first output requires a 2-character buffer. The second output is a message that will be truncated to the length of the placeholder.:
 - `zowe db2 call procedure "DEMO.SP3(NULL, ?, ?)" --parameters "00"
"message_placeholder_message_placeholder"`

[zowe](#) › [db2](#) › [execute](#)

Execute SQL queries against a Db2 region and retrieve the response. Enclose the query in quotes and escape any symbols that have a special meaning to the shell.

[zowe](#) › [db2](#) › [execute](#) › [sql](#)

Execute one or multiple SQL statements separated by a semicolon from a command line or from a file.

Usage

```
zowe db2 execute sql [options]
```

Options

- `--query` | `-q` (*string*)
 - The SQL statement verbatim to execute
- `--file` | `-f` (*string*)
 - A local file containing the SQL statements to execute

DB2 Connection Options

- `--host` | `-H` (*string*)
 - The Db2 server host name
- `--port` | `-P` (*number*)

- The Db2 server port number
- `--user` | `-u` (*string*)
 - The Db2 user ID (may be the same as the TSO login)
- `--password` | `--pass` | `--pw` (*string*)
 - The Db2 password (may be the same as the TSO password)
- `--database` | `--db` (*string*)
 - The name of the database
- `--sslFile` | `--ssl` (*string*)
 - Path to an SSL Certificate file

Profile Options

- `--db2-profile` | `--db2-p` (*string*)
 - The name of a (db2) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
 - Default value: true
- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication

- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Execute a dummy SQL query:
 - `zowe db2 execute sql --query "SELECT 'Hello World' FROM SYSIBM.SYSDUMMY1"`
- Retrieve the employees table and total number of rows:
 - `zowe db2 execute sql -q "SELECT * FROM SAMPLE.EMP; SELECT COUNT(*) AS TOTAL FROM SAMPLE.EMP"`
- Execute a file with SQL statements:
 - `zowe db2 execute sql --file backup_sample_database.sql`

zowe › db2 › export

Export data from a Db2 table

zowe › db2 › export › table

Export a Db2 table to the stdout or a file.

Usage

```
zowe db2 export table <table> [options]
```

Positional Arguments

- `table` (*string*)
 - The name of the table to export

Options

- `--outfile` | `-o` (*string*)
 - The path to the output file
- `--separator` | `--sep` (*string*)
 - Specify whether to add a separator between statements when exporting a table

DB2 Connection Options

- `--host` | `-H` (*string*)
 - The Db2 server host name
- `--port` | `-P` (*number*)
 - The Db2 server port number
- `--user` | `-u` (*string*)
 - The Db2 user ID (may be the same as the TSO login)
- `--password` | `--pass` | `--pw` (*string*)
 - The Db2 password (may be the same as the TSO password)
- `--database` | `--db` (*string*)
 - The name of the database
- `--sslFile` | `--ssl` (*string*)
 - Path to an SSL Certificate file

Profile Options

- `--db2-profile` | `--db2-p` (*string*)
 - The name of a (db2) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.

- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Export employees data from the table SAMPLE.EMP and save it to the file 'employees.sql':
 - `zowe db2 export table SAMPLE.EMP --outfile employees.sql`

zowe › ims

Interact with IBM IMS programs and transactions.

zowe › ims › query

Query application programs, regions or transactions across an IMSplex. The query returns information about application programs, regions and transactions. This command submits a 'QUERY PGM', 'DIS ACT' or 'QUERY TRAN' IMS command and returns the output.

zowe › ims › query › program

Query an IMS application program.

Usage

```
zowe ims query program [name...] [options]
```

Positional Arguments

- `name...` (*string*)
 - Specifies the name of the program(s) to query.

Options

- `--attributes` | `--att` (*array*)
 - Specifies the application program output fields to return.

Default value: ALL
Allowed values: ALL, BMPTYPE, DEFN, DEFNTYPE, DOPT, FP, GLOBAL, IMSID, GPSB, LANG, LOCAL, MODEL, RESIDENT, SCHDTYPE, STATUS, TIMESTAMP, TRANSTAT, EXPORTNEEDED, DB, RTC, TRAN, WORK
- `--status` | `--st` (*array*)
 - Selects programs for display that possess at least one of the specified program statuses.

Allowed values: DB-NOTAVL, IOPREV, LOCK, NOTINIT, STOSCHD, TRACE
- `--route` | `--rt` (*array*)

- Specifies the routes to return.

IMS Connection Options

- `--host` | `-H` (*string*)
 - The IMS Operations API server host name.
- `--port` | `-P` (*number*)
 - The IMS Operations API server port.
- `--ims-connect-host` | `--ich` (*string*)
 - The hostname of your instance of IMS Connect. This is typically the hostname of the mainframe LPAR where IMS Connect is running.
- `--ims-connect-port` | `--icp` (*number*)
 - The port of your instance of IMS Connect. This port can be found in your IMS Connect configuration file on the mainframe.
- `--plex` | `-x` (*string*)
 - The name of the IMS plex.
- `--user` | `-u` (*string*)
 - The web server user name where the IMS Operations API resides.
- `--password` | `--pass` (*string*)
 - The web server user password where the IMS Operations API resides.
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - Specifies protocol (http or https).

Default value: https

Allowed values: http, https

- `--reject-unauthorized` | `--ru` (*boolean*)

- Reject self-signed certificates.

Default value: true

Profile Options

- `--ims-profile` | `--ims-p` (*string*)

- The name of a (ims) profile to load for this command execution.

- `--base-profile` | `--base-p` (*string*)

- The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)

- The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.

- `--token-value` | `--tv` (*string*)

- The value of the token to pass to the API.

- `--cert-file` (*local file path*)

- The file path to a certificate file to use for authentication

- `--cert-key-file` (*local file path*)

- The file path to a certificate key file to use for authentication

Response Format Options

- `--response-format-filter` | `--rff` (*array*)

- Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '--response-format-type' to reduce the output of a command to a single field/property or a list of a single field/property.

- `--response-format-type` | `--rft` (*string*)

- The command response output format type. Must be one of the following:

table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.

list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.

object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string

- `--response-format-header` | `--rfh` (*boolean*)
 - If "`--response-format-type table`" is specified, include the column headers in the output.

Examples

- Query information for an application program named PGM123:
 - `zowe ims query program "PGM123"`
- Query information for application programs named ABC and XYZ:
 - `zowe ims query program "ABC XYZ"`
- Query information for application programs starting with PROG using the wild card character '*':
 - `zowe ims query program "PROG*"`
- Query information for all application programs (default is all):
 - `zowe ims query program`
- Query information for all application programs specifying optional parameters:
 - `zowe ims query program --attributes "BMPTYPE TIMESTAMP" --status "NOTINIT" -
-route "IMS1 IMS2"`
- Query information for all application programs specifying optional connection parameters:
 - `zowe ims query program --user "username" --pass "pass1234" --host
"localhost" --port 8080 --ich "zos1" --icp 9999 --plex "PLEX1"`

zowe › ims › query › region

Query an IMS region.

Usage

```
zowe ims query region [options]
```

Options

- `--dc` (*boolean*)
 - Displays only the DC subset of the outputDefault value: true
- `--region` (*boolean*)
 - Displays only the REGION subset of the output. The display consists of active regionsDefault value: true
- `--route` | `--rt` (*array*)
 - Specifies the routes to return.

IMS Connection Options

- `--host` | `-H` (*string*)
 - The IMS Operations API server host name.
- `--port` | `-P` (*number*)
 - The IMS Operations API server port.
- `--ims-connect-host` | `--ich` (*string*)
 - The hostname of your instance of IMS Connect. This is typically the hostname of the mainframe LPAR where IMS Connect is running.
- `--ims-connect-port` | `--icp` (*number*)
 - The port of your instance of IMS Connect. This port can be found in your IMS Connect configuration file on the mainframe.
- `--plex` | `-x` (*string*)

- The name of the IMS plex.
- `--user` | `-u` (*string*)
 - The web server user name where the IMS Operations API resides.
- `--password` | `--pass` (*string*)
 - The web server user password where the IMS Operations API resides.
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - Specifies protocol (http or https).

Default value: https
Allowed values: http, https
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true

Profile Options

- `--ims-profile` | `--ims-p` (*string*)
 - The name of a (ims) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)

- The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Response Format Options

- `--response-format-filter` | `--rff` (*array*)
 - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '`--response-format-type`' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
 - The command response output format type. Must be one of the following:

table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.

list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.

object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
 - If "`--response-format-type table`" is specified, include the column headers in the output.

Examples

- Query information for regions on route IMS1:
 - `zowe ims query region "IMS1"`

- Query information for regions on routes IMS1 and IMS2:
 - `zowe ims query region "IMS1 IMS2"`
- Query DC and region information for regions on routes IMS1 and IMS2:
 - `zowe ims query region "IMS1 IMS2" --dc true --region true`
- Query information for regions specifying optional connection parameters:
 - `zowe ims query region --user "username" --pass "pass1234" --host "localhost" --port 8080 --ich "zos1" --icp 9999 --plex "PLEX1"`

zowe › ims › query › transaction

Query an IMS transaction.

Usage

`zowe ims query transaction [name...] [options]`

Positional Arguments

- `name...` (*string*)
 - Specifies the name of transaction(s) to query. You can use an * character as a wildcard to select multiple transactions.

Options

- `--attributes` | `--att` (*array*)
 - Specifies the transaction output fields to return.

Allowed values: ALL, BMPTYPE, DEFN, DEFNTYPE, DOPT, FP, GLOBAL, IMSID, GPSB, LANG, LOCAL, MODEL, RESIDENT, SCHDTYPE, STATUS, TIMESTAMP, TRANSTAT, EXPORTNEEDED, DB, RTC, TRAN, WORK
- `--status` | `--st` (*array*)
 - Selects transactions that possess at least one of the specified transaction statuses.

Allowed values: AFFIN, BAL, CONV, CPIC, DYN, IOPREV, LCK, NOTINIT, QERR, QSTP, SUSPEND, STOQ, STOSCHD, TRACE, USTO
- `--route` | `--rt` (*array*)

- Specifies the routes to return.
- `--class` | `--cl` (*array*)
 - Selects transactions by the classes you specify.
- `--queue-count-operator` | `--qco` (*array*)
 - The compare operator used to select transactions based on queue count. Valid values: LT, LE, GT, GE, EQ or NE.
- `--queue-count-value` | `--qcv` (*number*)
 - The numeric value used with 'queue_count_operator' to select transactions based on queue count.
- `--conversation-attributes` | `--ca` (*string*)
 - Selects transactions by the conversational attributes you specify.
- `--fast-path-options` | `--fpo` (*string*)
 - Selects transactions by the Fast Path options you specify.
- `--remote-option-specified` | `--ros` (*string*)
 - Selects transactions by the remote option you specify.
- `--response-mode-option-specified` | `--rmos` (*string*)
 - Selects transactions by the response mode option you specify.

IMS Connection Options

- `--host` | `-H` (*string*)
 - The IMS Operations API server host name.
- `--port` | `-P` (*number*)
 - The IMS Operations API server port.
- `--ims-connect-host` | `--ich` (*string*)
 - The hostname of your instance of IMS Connect. This is typically the hostname of the mainframe LPAR where IMS Connect is running.
- `--ims-connect-port` | `--icp` (*number*)

- The port of your instance of IMS Connect. This port can be found in your IMS Connect configuration file on the mainframe.
- `--plex` | `-x` (*string*)
 - The name of the IMS plex.
- `--user` | `-u` (*string*)
 - The web server user name where the IMS Operations API resides.
- `--password` | `--pass` (*string*)
 - The web server user password where the IMS Operations API resides.
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - Specifies protocol (http or https).

Default value: https
Allowed values: http, https
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true

Profile Options

- `--ims-profile` | `--ims-p` (*string*)
 - The name of a (ims) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)

- The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Response Format Options

- `--response-format-filter` | `--rff` (*array*)
 - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '--response-format-type' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
 - The command response output format type. Must be one of the following:

table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.

list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.

object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
 - If "--response-format-type table" is specified, include the column headers in the output.

Examples

- Query transaction information for transaction named TRN12:
 - `zowe ims query transaction "TRN12"`
- Query transaction information for transactions named TRAN1 and TRAN2:
 - `zowe ims query transaction "TRAN1 TRAN2"`
- Query transaction information for transactions starting with TRAN using the wild card character '*':
 - `zowe ims query transaction "TRAN*"`
- Query transaction information for all transactions (default is all):
 - `zowe ims query transaction`
- Query transaction information for all transactions specifying optional parameters:
 - `zowe ims query transaction --attributes "AFFIN TIMESTAMP" --status "NOTINIT" --route "IMS1 IMS2"`
- Query transaction information for all transactions specifying optional connection parameters:
 - `zowe ims query transaction --user "username" --pass "pass1234" --host "localhost" --port 8080 --ich "zos1" --icp 9999 --plex "PLEX1"`

[zowe](#) › [ims](#) › [start](#)

Starts a region, application program, or transaction and makes IMS resources available for reference and use. This command submits a '/START REGION', 'UPDATE PGM' or 'UPDATE TRAN' IMS command and returns the output.

[zowe](#) › [ims](#) › [start](#) › [program](#)

Start an IMS application program.

Usage

```
zowe ims start program [name...] [options]
```

Positional Arguments

- `name...` (*string*)

- The name of the application program(s) to start. The maximum length of a program name is eight characters.

Options

- `--attributes` | `--att` (*array*)
 - The attributes that are to be started

Default value: SCHED
Allowed values: SCHED, TRACE, REFRESH
- `--route` | `--rte` (*array*)
 - The region(s) to route the command to

IMS Connection Options

- `--host` | `-H` (*string*)
 - The IMS Operations API server host name.
- `--port` | `-P` (*number*)
 - The IMS Operations API server port.
- `--ims-connect-host` | `--ich` (*string*)
 - The hostname of your instance of IMS Connect. This is typically the hostname of the mainframe LPAR where IMS Connect is running.
- `--ims-connect-port` | `--icp` (*number*)
 - The port of your instance of IMS Connect. This port can be found in your IMS Connect configuration file on the mainframe.
- `--plex` | `-x` (*string*)
 - The name of the IMS plex.
- `--user` | `-u` (*string*)
 - The web server user name where the IMS Operations API resides.
- `--password` | `--pass` (*string*)
 - The web server user password where the IMS Operations API resides.

- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - Specifies protocol (http or https).

Default value: https
Allowed values: http, https
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true

Profile Options

- `--ims-profile` | `--ims-p` (*string*)
 - The name of a (ims) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Response Format Options

- `--response-format-filter` | `--rff` (*array*)
 - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '`--response-format-type`' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
 - The command response output format type. Must be one of the following:
 - table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.
 - list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.
 - object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.
 - string: Formats output data as a string. JSON objects/arrays are stringified.
 - Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
 - If "`--response-format-type table`" is specified, include the column headers in the output.

Examples

- Start an application program named PGM123:
 - `zowe ims start program "PGM123"`
- Start all application programs beginning with ACC*:
 - `zowe ims start program "ACC*"`
- Start an application program named PGM234 and start tracing:
 - `zowe ims start program "PGM234" --attributes "SCHD TRACE"`
- Start an application program named PGM890 routing to control regions IMS1 and IMS2:

- `zowe ims start program "PGM890" --route "IMS1 IMS2"`
- Start an application programs named XYZ1 specifying optional connection parameters:
 - `zowe ims start program "XYZ1" --user "username" --pass "pass1234" --host "localhost" --port 8080 --ich "zos1" --icp 9999 --plex "PLEX1"`

[zowe](#) › [ims](#) › [start](#) › [region](#)

Start an IMS region.

Usage

```
zowe ims start region [memberName] [options]
```

Positional Arguments

- `memberName` (*string*)
 - The name of the member that contains JCL for the region to start. The maximum length of the member name is eight characters. If no member name is specified, the default member name is used

Options

- `--route` | `--rte` (*array*)
 - The region(s) to route the command to
- `--local` | `-l` (*boolean*)
 - If you specify the `--local` option, IMS overrides the symbolic IMSID parameter in the JCL of the default or specified member. `--local` is the default if you specify the `--job-name` option.
- `--job-name` | `--jn` (*string*)
 - Use this option to override the job name on the JOB statement of the default or specified JCL member for a dependent region.

IMS Connection Options

- `--host` | `-H` (*string*)
 - The IMS Operations API server host name.

- `--port` | `-P` (*number*)
 - The IMS Operations API server port.
- `--ims-connect-host` | `--ich` (*string*)
 - The hostname of your instance of IMS Connect. This is typically the hostname of the mainframe LPAR where IMS Connect is running.
- `--ims-connect-port` | `--icp` (*number*)
 - The port of your instance of IMS Connect. This port can be found in your IMS Connect configuration file on the mainframe.
- `--plex` | `-x` (*string*)
 - The name of the IMS plex.
- `--user` | `-u` (*string*)
 - The web server user name where the IMS Operations API resides.
- `--password` | `--pass` (*string*)
 - The web server user password where the IMS Operations API resides.
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - Specifies protocol (http or https).

Default value: https
Allowed values: http, https
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true

Profile Options

- `--ims-profile` | `--ims-p` (*string*)
 - The name of a (ims) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Response Format Options

- `--response-format-filter` | `--rff` (*array*)
 - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '`--response-format-type`' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
 - The command response output format type. Must be one of the following:

table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.

list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.

object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string

- `--response-format-header` | `--rfh` (*boolean*)
 - If "`--response-format-type table`" is specified, include the column headers in the output.

Examples

- Start a region stored in a member named MEM1:
 - `zowe ims start region "MEM1"`
- Start a region stored in a member named MEM2 specifying the region to route the command:
 - `zowe ims start region "MEM2" --route "IMS1"`
- Start a region stored in a member named MEM3 and override the job name:
 - `zowe ims start region "MEM3" --job-name "JOB9"`
- Start a region stored in a member named MEM4 routing to control regions IMS1 and IMS2:
 - `zowe ims start region "MEM4" --route "IMS1 IMS2"`
- Start a region stored in a member named MEM5 specifying optional connection parameters:
 - `zowe ims start region "MEM5" --user "username" --pass "pass1234" --host "localhost" --port 8080 --ich "zos1" --icp 9999 --plex "PLEX1"`

[zowe](#) › [ims](#) › [start](#) › [transaction](#)

Start an IMS transaction.

Usage

```
zowe ims start transaction [name...] [options]
```

Positional Arguments

- `name...` (*string*)

- The name of the transaction(s) to start. The maximum length of a transaction name is eight characters.

Options

- `--attributes` | `--att` (*array*)
 - The attributes that are to be started

Default value: SCHD
Allowed values: Q, SCHD, SUSPEND, TRACE
- `--route` | `--rte` (*array*)
 - The region(s) to route the command to

IMS Connection Options

- `--host` | `-H` (*string*)
 - The IMS Operations API server host name.
- `--port` | `-P` (*number*)
 - The IMS Operations API server port.
- `--ims-connect-host` | `--ich` (*string*)
 - The hostname of your instance of IMS Connect. This is typically the hostname of the mainframe LPAR where IMS Connect is running.
- `--ims-connect-port` | `--icp` (*number*)
 - The port of your instance of IMS Connect. This port can be found in your IMS Connect configuration file on the mainframe.
- `--plex` | `-x` (*string*)
 - The name of the IMS plex.
- `--user` | `-u` (*string*)
 - The web server user name where the IMS Operations API resides.
- `--password` | `--pass` (*string*)
 - The web server user password where the IMS Operations API resides.

- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - Specifies protocol (http or https).
 Default value: https
 Allowed values: http, https
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
 Default value: true

Profile Options

- `--ims-profile` | `--ims-p` (*string*)
 - The name of a (ims) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Response Format Options

- `--response-format-filter` | `--rff` (*array*)
 - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '`--response-format-type`' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
 - The command response output format type. Must be one of the following:
 - table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.
 - list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.
 - object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.
 - string: Formats output data as a string. JSON objects/arrays are stringified.
 - Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
 - If "`--response-format-type table`" is specified, include the column headers in the output.

Examples

- Start a transaction named TRN1:
 - `zowe ims start transaction "TRN1"`
- Start all transactions beginning with TRN*:
 - `zowe ims start transaction "TRN*"`
- Start a transaction named TRN2 and start tracing:
 - `zowe ims start transaction "TRN2" --attributes "SCHD TRACE"`
- Start a transaction named TRN3 routing to control regions IMS1 and IMS2:

- `zowe ims start transaction "TRN3" --route "IMS1 IMS2"`
- Start a transaction named TRN4 specifying optional connection parameters:
 - `zowe ims start transaction "TRN4" --user "username" --pass "pass1234" --host "localhost" --port 8080 --ich "zos1" --icp 9999 --plex "PLEX1"`

[zowe](#) › [ims](#) › [stop](#)

Stops a running region, application program or transaction. This command submits a '/STOP REGION', 'UPDATE PGM' or 'UPDATE TRAN' IMS command and returns the output.",

[zowe](#) › [ims](#) › [stop](#) › [program](#)

Stop an IMS application program.

Usage

```
zowe ims stop program [name...] [options]
```

Positional Arguments

- `name...` (*string*)
 - The name(of the program(s) to stop. The maximum length of a program name is eight characters.

Options

- `--attributes` | `--att` (*array*)
 - The attributes that are to be stopped
Default value: SCHED
Allowed values: SCHED, TRACE
- `--route` | `--rte` (*array*)
 - The region(s) to route the command

IMS Connection Options

- `--host` | `-H` (*string*)
 - The IMS Operations API server host name.

- `--port` | `-P` (*number*)
 - The IMS Operations API server port.
- `--ims-connect-host` | `--ich` (*string*)
 - The hostname of your instance of IMS Connect. This is typically the hostname of the mainframe LPAR where IMS Connect is running.
- `--ims-connect-port` | `--icp` (*number*)
 - The port of your instance of IMS Connect. This port can be found in your IMS Connect configuration file on the mainframe.
- `--plex` | `-x` (*string*)
 - The name of the IMS plex.
- `--user` | `-u` (*string*)
 - The web server user name where the IMS Operations API resides.
- `--password` | `--pass` (*string*)
 - The web server user password where the IMS Operations API resides.
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - Specifies protocol (http or https).

Default value: https
Allowed values: http, https
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true

Profile Options

- `--ims-profile` | `--ims-p` (*string*)
 - The name of a (ims) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Response Format Options

- `--response-format-filter` | `--rff` (*array*)
 - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '`--response-format-type`' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
 - The command response output format type. Must be one of the following:

table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.

list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.

object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string

- `--response-format-header` | `--rfh` (*boolean*)
 - If "`--response-format-type table`" is specified, include the column headers in the output.

Examples

- Stop an application program named PGM123:
 - `zowe ims stop program "PGM123"`
- Stop all application programs beginning with ACC*:
 - `zowe ims stop program "ACC*"`
- Stop tracing an application program named PGM234:
 - `zowe ims stop program "PGM234" --attributes "TRACE"`
- Stop an application program named PGM890 routing to control regions IMS1 and IMS2:
 - `zowe ims stop program "PGM890" --route "IMS1 IMS2"`
- Stop an application programs named XYZ1 specifying optional connection parameters:
 - `zowe ims stop program "XYZ1" --user "username" --pass "pass1234" --host "localhost" --port 8080 --ich "zos1" --icp 9999 --plex "PLEX1"`

[zowe](#) › [ims](#) › [stop](#) › [region](#)

Stop an IMS region.

Usage

```
zowe ims stop region [options]
```

Options

- `--region-ids` | `--ri` (*array*)

- Region identifier numbers for the regions you want to stop. You must specify either this option or --job-name.
- `--job-name` | `--jn` (*string*)
 - The name of the job for the IMS region you want to stop. You must specify either this option or --region-ids.
- `--route` | `--rte` (*array*)
 - The region(s) to route the command to
- `--abdump` (*string*)
 - Specify this option to cause abnormal termination (ABEND) of an application program. If the transaction indicated by this argument is currently running in the specified region, an error message is received at the master terminal, indicating an application program ABEND. The region will remain active, but the transaction will be stopped. The command is ignored if the transaction is not currently scheduled in the region.
- `--cancel` (*boolean*)
 - Use this option if the region cannot be stopped with a stop region --abdump command. To use this option, you must have already submitted a stop region command using the --abdump option.
- `--transaction` (*string*)
 - Specify a transaction in wait-for-input mode to stop its message processing within the specified region.

IMS Connection Options

- `--host` | `-H` (*string*)
 - The IMS Operations API server host name.
- `--port` | `-P` (*number*)
 - The IMS Operations API server port.
- `--ims-connect-host` | `--ich` (*string*)
 - The hostname of your instance of IMS Connect. This is typically the hostname of the mainframe LPAR where IMS Connect is running.

- `--ims-connect-port` | `--icp` (*number*)
 - The port of your instance of IMS Connect. This port can be found in your IMS Connect configuration file on the mainframe.
- `--plex` | `-x` (*string*)
 - The name of the IMS plex.
- `--user` | `-u` (*string*)
 - The web server user name where the IMS Operations API resides.
- `--password` | `--pass` (*string*)
 - The web server user password where the IMS Operations API resides.
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - Specifies protocol (http or https).

Default value: https
Allowed values: http, https
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true

Profile Options

- `--ims-profile` | `--ims-p` (*string*)
 - The name of a (ims) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Response Format Options

- `--response-format-filter` | `--rff` (*array*)
 - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '`--response-format-type`' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
 - The command response output format type. Must be one of the following:

table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.

list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.

object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
 - If "`--response-format-type table`" is specified, include the column headers in the output.

Examples

- Stop a region with job name JOBNM1:
 - `zowe ims stop region --job-name "JOBNM1"`
- Stop multiple regions with region identifiers:
 - `zowe ims stop region --region-ids 4 5`
- Stop a region with region identifier and cause the abnormal termination (ABEND) of the application program:
 - `zowe ims stop region --region-ids 4 --abdump "TRAN1"`
- Stop a region with region identifier and specify 'cancel' because the 'abdump' option failed to stop the region:
 - `zowe ims stop region --region-ids 4 --cancel true`
- Stop a region with job name JOBNM4 specifying optional connection parameters:
 - `zowe ims stop region --job-name "JOBNM4" --user "username" --pass "pass1234" --host "localhost" --port 8080 --ich "zos1" --icp 9999 --plex "PLEX1"`

[zowe](#) › [ims](#) › [stop](#) › [transaction](#)

Stop an IMS transaction.

Usage

```
zowe ims stop transaction <name...> [options]
```

Positional Arguments

- `name...` (*string*)
 - The name of the transaction(s) to stop. The maximum length of a transaction name is eight characters.

Options

- `--attributes` | `--att` (*array*)
 - The attributes that are to be stopped

Default value: SCHED

Allowed values: Q, SCHED, TRACE

- `--route` | `--rte` (*array*)
 - The region(s) to route the command

IMS Connection Options

- `--host` | `-H` (*string*)
 - The IMS Operations API server host name.
- `--port` | `-P` (*number*)
 - The IMS Operations API server port.
- `--ims-connect-host` | `--ich` (*string*)
 - The hostname of your instance of IMS Connect. This is typically the hostname of the mainframe LPAR where IMS Connect is running.
- `--ims-connect-port` | `--icp` (*number*)
 - The port of your instance of IMS Connect. This port can be found in your IMS Connect configuration file on the mainframe.
- `--plex` | `-x` (*string*)
 - The name of the IMS plex.
- `--user` | `-u` (*string*)
 - The web server user name where the IMS Operations API resides.
- `--password` | `--pass` (*string*)
 - The web server user password where the IMS Operations API resides.
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)

- Specifies protocol (http or https).

Default value: https

Allowed values: http, https

- `--reject-unauthorized` | `--ru` (*boolean*)

- Reject self-signed certificates.

Default value: true

Profile Options

- `--ims-profile` | `--ims-p` (*string*)

- The name of a (ims) profile to load for this command execution.

- `--base-profile` | `--base-p` (*string*)

- The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)

- The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.

- `--token-value` | `--tv` (*string*)

- The value of the token to pass to the API.

- `--cert-file` (*local file path*)

- The file path to a certificate file to use for authentication

- `--cert-key-file` (*local file path*)

- The file path to a certificate key file to use for authentication

Response Format Options

- `--response-format-filter` | `--rff` (*array*)

- Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields.

In addition, you can use this option in conjunction with '--response-format-type' to reduce the output of a command to a single field/property or a list of a single field/property.

- `--response-format-type` | `--rft` (*string*)

- The command response output format type. Must be one of the following:

`table`: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.

`list`: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.

`object`: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

`string`: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string

- `--response-format-header` | `--rfh` (*boolean*)

- If "--response-format-type table" is specified, include the column headers in the output.

Examples

- Stop a transaction named TRN1:

- `zowe ims stop transaction "TRN1"`

- Stop all transactions beginning with TRN*:

- `zowe ims stop transaction "TRN*"`

- Stop tracing a transaction named TRN2:

- `zowe ims stop transaction "TRN2" --attributes "TRACE"`

- Stop a transaction named TRN3 routing to control regions IMS1 and IMS2:

- `zowe ims stop transaction "TRN3" --route "IMS1 IMS2"`

- Stop a transaction named TRN4 specifying optional connection parameters:

- `zowe ims stop transaction "TRN4" --user "username" --pass "pass1234" --host "localhost" --port 8080 --ich "zos1" --icp 9999 --plex "PLEX1"`

zowe › ims › update

Updates the setting(s) for application program or transaction. This command submits a 'UPDATE PGM' or 'UPDATE TRAN' IMS command and returns the output.

zowe › ims › update › program

Update an IMS application program.

Usage

```
zowe ims update program [name...] [options]
```

Positional Arguments

- `name...` (*string*)
 - The name of the application program(s) to update. The maximum length of a program name is eight characters.

Options

- `--bmp-type` | `--bmptype` (*string*)
 - Specifies whether the program runs in a BMP type region or not. (N or Y).
Allowed values: N, Y
- `--dynamic` | `--dopt` (*string*)
 - Specifies the dynamic option (N or Y).
Allowed values: N, Y
- `--fast-path` | `--fp` (*string*)
 - Specifies the Fast Path option (E or N).
Allowed values: E, N
- `--generated-psb` | `--gpsb` (*string*)
 - Specifies the generated PSB option (N or Y).
Allowed values: N, Y

- `--language` | `--lang` (*string*)
 - Specifies the language interface of the program or a GPSB or defined a DOPT(Y) program as using the JAVA language (ASSEM, COBOL, JAVA, PASCAL, PLI).
Allowed values: ASSEM, COBOL, JAVA, PASCAL, PLI
- `--lock` | `-l` (*string*)
 - Specifies the LOCK status is to be set (ON or OFF).
Allowed values: ON, OFF
- `--option` | `-o` (*string*)
 - Specifies to return response lines for all resources that are processed. It is only valid with `--name *` (ALLRSP).
Allowed values: ALLRSP
- `--resident` | `-r` (*string*)
 - Specifies the resident option (N or Y).
Allowed values: N, Y
- `--route` | `--rte` (*array*)
 - Specifies the region(s) to route the command.
- `--schedule-type` | `--schdtype` (*string*)
 - Specifies whether this application program can be scheduled into more than one message region or batch message region simultaneously (PARALLEL or SERIAL).
Allowed values: PARALLEL, SERIAL
- `--transaction-level-stat` | `--transtat` (*string*)
 - Specifies whether transaction level statistics should be logged (N or Y).
Allowed values: N, Y

IMS Connection Options

- `--host` | `-H` (*string*)
 - The IMS Operations API server host name.

- `--port` | `-P` (*number*)
 - The IMS Operations API server port.
- `--ims-connect-host` | `--ich` (*string*)
 - The hostname of your instance of IMS Connect. This is typically the hostname of the mainframe LPAR where IMS Connect is running.
- `--ims-connect-port` | `--icp` (*number*)
 - The port of your instance of IMS Connect. This port can be found in your IMS Connect configuration file on the mainframe.
- `--plex` | `-x` (*string*)
 - The name of the IMS plex.
- `--user` | `-u` (*string*)
 - The web server user name where the IMS Operations API resides.
- `--password` | `--pass` (*string*)
 - The web server user password where the IMS Operations API resides.
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - Specifies protocol (http or https).

Default value: https
Allowed values: http, https
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true

Profile Options

- `--ims-profile` | `--ims-p` (*string*)
 - The name of a (ims) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Response Format Options

- `--response-format-filter` | `--rff` (*array*)
 - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '`--response-format-type`' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
 - The command response output format type. Must be one of the following:

table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.

list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.

object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string

- `--response-format-header` | `--rfh` (*boolean*)
 - If "`--response-format-type table`" is specified, include the column headers in the output.

Examples

- Update an application program named PGM123 to execute exclusively as Fast Path:
 - `zowe ims update program "PGM123" --fp "E"`
- Update all application programs beginning with ACC* to not run in a BMP type region:
 - `zowe ims update program "ACC*" --bmptype "N"`
- Unlock all programs beginning with PGM* to allow scheduling:
 - `zowe ims update program "PGM*" --lock "OFF"`
- Update an application program named PGM890 to execute as Fast Path routing to control regions IMS1 and IMS2:
 - `zowe ims update program "PGM890" --fp "E" --route "IMS1 IMS2"`
- Unlock an application programs named XYZ1 to allow scheduling specifying optional connection parameters:
 - `zowe ims update program "XYZ1" --lock "OFF" --user "username" --pass "pass1234" --host "localhost" --port 8080 --ich "zos1" --icp 9999 --plex "PLEX1"`

[zowe](#) › [ims](#) › [update](#) › [transaction](#)

Update an IMS transaction.

Usage

```
zowe ims update transaction [name...] [options]
```

Positional Arguments

- `name...` (*string*)
 - The name of the transaction(s) to update. The maximum length of a transaction name is eight characters.

Options

- `--aoi-cmd` | `--aocmd` (*string*)
 - Specifies the AOI option that you want to change (N, CMD, TRAN, Y).
Allowed values: N, CMD, TRAN, Y
- `--class` | `-c` (*array*)
 - Selects the transactions associated with the specified class or classes to be updated.
- `--commit-mode` | `--cmtmode` (*string*)
 - Specifies when database updates and non-express output messages are committed (SNGL, MULT).
Allowed values: SINGLE, MODE
- `--conversation` | `--conv` (*string*)
 - Specifies the conversation option (N or Y).
Allowed values: N, Y
- `--current-priority` | `--cpri` (*number*)
 - Specifies a new value for the current priority of a transaction.
- `--directed-routing` | `--dirroute` (*string*)
 - Specifies the MSC directed routing option (N or Y).
Allowed values: N, Y
- `--edit-routine` | `--editrtn` (*string*)
 - Specifies the 1- to 8-character name of your transaction input edit routine that edits messages before the program receives the message.
- `--edit-uppercase` | `--edituc` (*string*)
 - Specifies the edit to uppercase option (N or Y).

Allowed values: N, Y

- `--emh-buffer-size` | `--emhbsz` (*number*)
 - Specifies the EMH buffer size required to run the Fast Path transaction.
- `--expiration-time` | `--exptime` (*number*)
 - Specifies the elapsed time in seconds that IMS can use to cancel the input transaction.
- `--fast-path` | `--fp` (*string*)
 - Specifies the Fast Path option (E, N, P).

Allowed values: E, N, P

- `--inquiry` | `--inq` (*string*)
 - Specifies the inquiry option (N or Y).

Allowed values: N, Y

- `--limit-count` | `--lct` (*number*)
 - Specifies the limit count.
- `--limit-priority` | `--lpri` (*number*)
 - Specifies the limit priority.
- `--lock` | `-l` (*string*)
 - Specifies that the LOCK status is to be set on or off. Cannot be specified with any other SET attribute(ON or OFF).

Allowed values: ON, OFF

- `--log-write-ahead` | `--dc1wa` (*string*)
 - Specifies the log write-ahead option (N or Y).

Allowed values: N, Y

- `--maximum-regions` | `--maxrgn` (*number*)
 - Specifies a new value for the maximum number of regions that can be simultaneously scheduled for a given transaction.

- `--message-type` | `--msgtype` (*string*)
 - Specifies the message type (single segment or multiple segment) (MULTSEG or SNGLSEG).

Allowed values: MULTSEG, SNGLSEG
- `--msname` | `--mn` (*string*)
 - Specifies the one- to eight-character name of the logical link path in a multiple IMS system configuration (MSC).
- `--normal-scheduling-priority` | `--npri` (*number*)
 - Specifies the normal scheduling priority.
- `--option` | `-o` (*string*)
 - Specifies functions to be performed along with the command (AFFIN or ALLRSP).

Allowed values: ALLRSP
- `--parallel-processing-limit` | `--parlim` (*number*)
 - Specifies the parallel processing limit count.
- `--program` | `--pgm` (*string*)
 - Specifies the name of the application program associated with the transaction.
- `--processing-limit-count` | `--plct` (*number*)
 - Specifies the processing limit count.
- `--processing-limit-count-time` | `--plcttime` (*number*)
 - Specifies the processing limit count time.
- `--recover` | `-r` (*string*)
 - Specifies the recovery option (N or Y).

Allowed values: N, Y
- `--remote` | `--re` (*string*)
 - Specifies the remote option (N or Y).

Allowed values: N, Y

- `--response-mode` | `--resp` (*string*)
 - Specifies the response mode option (N or Y).

Allowed values: N, Y

- `--route` | `--rte` (*array*)
 - Specifies the region(s) to route the command.

- `--segment-number` | `--segno` (*number*)
 - Specifies the segment number.

- `--segment-size` | `--segsz` (*number*)
 - Specifies the segment size.

- `--serial` | `--sr` (*string*)
 - Specifies the serial option (N or Y).

Allowed values: N, Y

- `--set-class` | `--sc` (*number*)
 - Specifies the transaction class, which is an attribute used to select a transaction for scheduling.

- `--system-identification-local` | `--sidl` (*number*)
 - Specifies the system identification (SYSID) of the local system in a multiple-IMS system (MSC) configuration.

- `--system-identification-remote` | `--sidr` (*number*)
 - Specifies the system identification (SYSID) of the remote system in a multiple-IMS system (MSC) configuration.

- `--scratchpad-area-size` | `--spasz` (*number*)
 - Specifies the scratchpad area (SPA) size, in bytes, for a conversational transaction. The value can be a number from 16 and 32767.

- `--scratchpad-area-truncation` | `--spatrunc` (*string*)

- Specifies the scratchpad area (SPA) truncation option of a conversational transaction (S or R).

Allowed values: S, R

- `--transaction-level-stat` | `--transtat` (*string*)

- Specifies whether transaction level statistics should be logged for message driven programs (N or Y).

Allowed values: N, Y

- `--wait-for-input` | `--wfi` (*string*)

- Specifies the wait-for input option (N or Y).

Allowed values: N, Y

IMS Connection Options

- `--host` | `-H` (*string*)

- The IMS Operations API server host name.

- `--port` | `-P` (*number*)

- The IMS Operations API server port.

- `--ims-connect-host` | `--ich` (*string*)

- The hostname of your instance of IMS Connect. This is typically the hostname of the mainframe LPAR where IMS Connect is running.

- `--ims-connect-port` | `--icp` (*number*)

- The port of your instance of IMS Connect. This port can be found in your IMS Connect configuration file on the mainframe.

- `--plex` | `-x` (*string*)

- The name of the IMS plex.

- `--user` | `-u` (*string*)

- The web server user name where the IMS Operations API resides.

- `--password` | `--pass` (*string*)

- The web server user password where the IMS Operations API resides.
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - Specifies protocol (http or https).
 - Default value: https
 - Allowed values: http, https
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
 - Default value: true

Profile Options

- `--ims-profile` | `--ims-p` (*string*)
 - The name of a (ims) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)

- The file path to a certificate key file to use for authentication

Response Format Options

- `--response-format-filter` | `--rff` (*array*)
 - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '`--response-format-type`' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
 - The command response output format type. Must be one of the following:
 - table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.
 - list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.
 - object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.
 - string: Formats output data as a string. JSON objects/arrays are stringified.
 - Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
 - If "`--response-format-type table`" is specified, include the column headers in the output.

Examples

- Update a transaction named TRN1 to process exclusively as Fast Path:
 - `zowe ims update transaction "TRN1" --fp "E"`
- Unlock to allow scheduling all transactions beginning with TRN* and associated with class CLASSA:
 - `zowe ims update transaction "TRN*" --class "CLASSA" --lock "OFF"`
- Set response mode on for transaction named TRN2 and associated with classes CLASS1 and CLASS2:

- `zowe ims update transaction "TRN2" --class "CLASS1 CLASS2" --resp "Y"`
- Update a transaction named TRN3 to process exclusively as Fast Path routing to control regions IMS1 and IMS2:
 - `zowe ims update transaction "TRN3" -fp "E" --route "IMS1 IMS2"`
- Associate PGM1 with transaction named TRN4 specifying optional connection parameters:
 - `zowe ims update transaction "TRN4" --pgm "PGM1" --user "username" --pass "pass1234" --host "localhost" --port 8080 --ich "zos1" --icp 9999 --plex "PLEX1"`

zowe › mq

Interact with IBM MQ for z/OS.

zowe › mq › run

MQ Utilities

zowe › mq › run › mqsc

MQ Utilities

Usage

```
zowe mq run mqsc <qmgr> <cmd> [options]
```

Positional Arguments

- `qmgr` (*string*)
 - The queue manager to apply the command to
- `cmd` (*string*)
 - The MQSC command

MQ Connection Options

- `--host` | `-H` (*string*)
 - The host name used to access the IBM MQ REST API. This might be the host name of the IBM MQ mqweb server, or the Zowe API Mediation Layer..
- `--port` | `-P` (*number*)
 - The port number used to access the IBM MQ REST API. This might be the port number of the IBM MQ mqweb server, or the Zowe API Mediation Layer.
- `--user` | `-u` (*string*)
 - The mainframe (MQ) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)

- The mainframe (MQ) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
Default value: false
- `--protocol` (*string*)
 - Specifies the MQ protocol (http or https).
Default value: http
Allowed values: http, https

Profile Options

- `--mq-profile` | `--mq-p` (*string*)
 - The name of a (mq) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- The following sequence shows how to query a server-connection channel that is called NEWSVRCONN on an MQ queue manager - our example queue manager is called MQ99:
 - `zowe mq run mqsc MQ99 "DISPLAY CHANNEL(NEWSVRCONN)"`

zowe › plugins

Install and manage plug-ins.

zowe › plugins › install

Install plug-ins to an application.

Usage

```
zowe plugins install [plugin...] [options]
```

Positional Arguments

- `plugin...` (*string*)
 - A space-separated list of plug-ins to install. A plug-in can be any format that is accepted by the ``npm install`` command (local directory, TAR file, git URL, public package, private package, etc...).

To use a relative local directory, at least one `'/'` or `'\'` must exist in the plug-in path. For example, you have a local plug-in in a folder called `'test-plugin'` that you want to install. Specify the relative local directory by issuing the following command:

```
zowe plugins install ./test-plugin
```

If you omit the `'./'`, then the install command looks for `'test-plugin'` in an npm registry.

If the plugin argument is omitted, the `plugins.json` file will determine which plug-ins are installed. For more information on the `plugins.json` file, see the `--file` option.

Options

- `--file` (*local file path*)
 - Specifies the location of a `plugins.json` file that contains the plug-ins you want to install.

All plug-ins specified in `plugins.json` will be installed to the base CLI and the contents will be placed into `/home/<user>/.zowe/plugins/plugins.json`.

If you do not specify a `plugins.json` file and do not specify a plug-in, the default `plugin.json` file (`/home/<user>/.zowe/plugins/plugin.json`) will be used. This provides a way to install plug-ins that were lost or corrupted after reinstalling or updating Zowe CLI.

- `--registry` (*string*)
 - The npm registry that is used when installing remote packages. When this value is omitted, the value returned by ``npm config get registry`` is used.

For more information about npm registries, see: <https://docs.npmjs.com/misc/registry>
- `--login` (*boolean*)
 - The flag to add a registry user account to install from secure registry. It saves credentials to the `.npmrc` file using ``npm adduser``. When this value is omitted, credentials from `.npmrc` file is used. If you used this flag once for specific registry, you don't have to use it again, it uses credentials from `.npmrc` file.

For more information about npm registries, see: <https://docs.npmjs.com/cli/adduser>

Examples

- Install plug-ins saved in `/home/<user>/.zowe/plugins/plugins.json`:
 - `zowe plugins install`
- Install plug-ins saved in a properly formatted config file:
 - `zowe plugins install --file /some/file/path/file_name.json`
- Install a remote plug-in:
 - `zowe plugins install my-plugin`
- Install a remote plug-in using semver:
 - `zowe plugins install my-plugin@"^1.2.3"`
- Install a remote plug-in from the specified registry:
 - `zowe plugins install my-plugin --registry https://registry.npmjs.org/`
- Install a local folder, local TAR file, and a git URL:
 - `zowe plugins install ./local-file /root/tar/some-tar.tgz
git://github.com/project/repository.git#v1.0.0`
- Install a remote plug-in from the registry which requires authorization(don't need to use this flag if you have already logged in before):

- `zowe plugins install my-plugin --registry https://registry.npmjs.org/ --login`

zowe › plugins › list

List all plug-ins installed.

Usage

`zowe plugins list [options]`

Options

- `--short` | `-s` (*boolean*)
 - Show output in abbreviated format

zowe › plugins › uninstall

Uninstall plug-ins.

Usage

`zowe plugins uninstall [plugin...] [options]`

Positional Arguments

- `plugin...` (*string*)
 - The name of the plug-in to uninstall.

If the plug-in argument is omitted, no action is taken.

Examples

- Uninstall a plug-in:
 - `zowe plugins uninstall my-plugin`

zowe › plugins › update

Update plug-ins.

Usage

`zowe plugins update [plugin...] [options]`

Positional Arguments

- `plugin...` (*string*)
 - The name of the plug-in to update.

If the plug-in argument is omitted, no action is taken.

Options

- `--registry` (*string*)
 - The npm registry that is used when installing remote packages. When this value is omitted, the value returned by ``npm config get registry`` is used.

For more information about npm registries, see: <https://docs.npmjs.com/misc/registry>
- `--login` (*boolean*)
 - The flag to add a registry user account to install from secure registry. It saves credentials to the `.npmrc` file using ``npm adduser``. When this value is omitted, credentials from `.npmrc` file is used. If you used this flag once for specific registry, you don't have to use it again, it uses credentials from `.npmrc` file.

For more information about npm registries, see: <https://docs.npmjs.com/cli/adduser>

Examples

- Update a plug-in:
 - `zowe plugins update my-plugin`
- Update a remote plug-in from the registry which requires authorization(don't need to use this flag if you have already logged in before):
 - `zowe plugins update my-plugin --registry https://registry.npmjs.org/ --login`

[zowe](#) › [plugins](#) › [validate](#)

Validate a plug-in that has been installed.

Usage

```
zowe plugins validate [plugin] [options]
```

Positional Arguments

- `plugin` (*string*)
 - The name of the plug-in to validate.
Validation issues identified for this plug-in are displayed.

If the plug-in argument is omitted, all installed plug-ins are validated.

Options

- `--fail-on-error` | `--foe` (*boolean*)
 - Enables throwing an error and setting an error code if plugin validation detects an error

Default value: true
- `--fail-on-warning` | `--fow` (*boolean*)
 - Treat validation warnings as errors. Requires fail-on-error.

Default value: false

Examples

- Validate a plug-in named my-plugin:
 - `zowe plugins validate my-plugin`
- Validate all installed plug-ins:
 - `zowe plugins validate`
- Validate a plug-in named my-plugin, and treat warnings as errors:
 - `zowe plugins validate my-plugin --fail-on-warning`

zowe › profiles

Create and manage configuration profiles.

Warning: This group has been deprecated.

Recommended replacement: The 'config init' command

zowe › profiles › create

Create new configuration profiles.

Warning: This group has been deprecated.

Recommended replacement: The 'config init' command

zowe › profiles › create › base-profile

Base profile that stores values shared by multiple service profiles

Warning: This command has been deprecated.

Recommended replacement: The 'config init' command

Usage

```
zowe profiles create base-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the new base profile. You can load this profile by using the name on commands that support the "--base-profile" option.

Base Connection Options

- `--host` | `-H` (*string*)
 - Host name of service on the mainframe.
- `--port` | `-P` (*number*)
 - Port number of service on the mainframe.
- `--user` | `-u` (*string*)

- User name to authenticate to service on the mainframe.
- `--password` | `--pass` | `--pw` (*string*)
 - Password to authenticate to service on the mainframe.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
 - Default value: true
- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Options

- `--overwrite` | `--ow` (*boolean*)
 - Overwrite the base profile when a profile of the same name exists.
- `--disable-defaults` | `--dd` (*boolean*)
 - Disable populating profile values of undefined properties with default values.

Examples

- Create a profile called 'base1' to connect to host example.com and port 443:
 - `zowe profiles create base-profile base1 --host example.com --port 443 --user admin --password 123456`

- Create a profile called 'base2' to connect to host example.com (default port - 443) and allow self-signed certificates:
 - `zowe profiles create base-profile base2 --host example.com --user admin --password 123456 --reject-unauthorized false`
- Create a profile called 'base3' to connect to host example.com and port 1443, not specifying a username or password so they are not stored on disk; these will need to be specified on every command:
 - `zowe profiles create base-profile base3 --host example.com --port 1443`
- Create a zosmf profile called 'base4' to connect to default port 443 and allow self-signed certificates, not specifying a username, password, or host so they are not stored on disk; these will need to be specified on every command:
 - `zowe profiles create base-profile base4 --reject-unauthorized false`

[zowe](#) › [profiles](#) › [create](#) › [cics-profile](#)

A cics profile is required to issue commands in the cics command group that interact with CICS regions. The cics profile contains your host, port, user name, and password for the IBM CICS management client interface (CMCI) server of your choice.

Warning: This command has been deprecated.

Recommended replacement: The 'config init' command

Usage

```
zowe profiles create cics-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the new cics profile. You can load this profile by using the name on commands that support the "--cics-profile" option.

Options

- `--host` | `-H` (*string*)
 - The CMCI server host name
- `--port` | `-P` (*number*)

- The CMCI server port

Default value: 1490

- `--user` | `-u` (*string*)
 - Your username to connect to CICS
- `--password` | `-p` (*string*)
 - Your password to connect to CICS
- `--region-name` (*string*)
 - The name of the CICS region name to interact with
- `--cics-plex` (*string*)
 - The name of the CICSplex to interact with
- `--overwrite` | `--ow` (*boolean*)
 - Overwrite the cics profile when a profile of the same name exists.
- `--disable-defaults` | `--dd` (*boolean*)
 - Disable populating profile values of undefined properties with default values.

Cics Connection Options

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).

Default value: https
Allowed values: http, https

Examples

- Create a cics profile named 'cics123' to connect to CICS at host zos123 and port 1490:

- `zowe profiles create cics-profile cics123 --host zos123 --port 1490 --user ibmuser --password myp4ss`

zowe › **profiles** › **create** › **db2-profile**

A profile for interaction with Db2 for the z/OS region

Warning: This command has been deprecated.

Recommended replacement: The 'config init' command

Usage

`zowe profiles create db2-profile <profileName> [options]`

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the new db2 profile. You can load this profile by using the name on commands that support the "--db2-profile" option.

Options

- `--host` | `-H` (*string*)
 - The Db2 server host name
- `--port` | `-P` (*number*)
 - The Db2 server port number
- `--user` | `-u` (*string*)
 - The Db2 user ID (may be the same as the TSO login)
- `--password` | `--pass` | `--pw` (*string*)
 - The Db2 password (may be the same as the TSO password)
- `--database` | `-d` (*string*)
 - The name of the database
- `--ssl-file` | `-s` (*string*)
 - Path to an SSL Certificate file

- `--overwrite` | `--ow` (*boolean*)
 - Overwrite the db2 profile when a profile of the same name exists.
- `--disable-defaults` | `--dd` (*boolean*)
 - Disable populating profile values of undefined properties with default values.

[zowe](#) › [profiles](#) › [create](#) › [ims-profile](#)

An ims profile is used to issue commands in the `ims` command group that interact with IMS regions. The `ims` profile contains your IMS Operations API web server host, port, user name and password, IMS Connect host and port and IMS plex name.

Warning: This command has been deprecated.

Recommended replacement: The `'config init'` command

Usage

```
zowe profiles create ims-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the new `ims` profile. You can load this profile by using the name on commands that support the `"--ims-profile"` option.

IMS Connection Options

- `--host` | `-H` (*string*)
 - The IMS Operations API server host name.
- `--port` | `-P` (*number*)
 - The IMS Operations API server port.
- `--ims-connect-host` | `--ich` (*string*)
 - The hostname of your instance of IMS Connect. This is typically the hostname of the mainframe LPAR where IMS Connect is running.
- `--ims-connect-port` | `--icp` (*number*)

- The port of your instance of IMS Connect. This port can be found in your IMS Connect configuration file on the mainframe.
- `--plex` | `-x` (*string*)
 - The name of the IMS plex.
- `--user` | `-u` (*string*)
 - The web server user name where the IMS Operations API resides.
- `--password` | `--pass` (*string*)
 - The web server user password where the IMS Operations API resides.
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - Specifies protocol (http or https).

Default value: https
Allowed values: http, https
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true

Options

- `--overwrite` | `--ow` (*boolean*)
 - Overwrite the ims profile when a profile of the same name exists.
- `--disable-defaults` | `--dd` (*boolean*)
 - Disable populating profile values of undefined properties with default values.

Examples

- Create a ims profile named 'ims123' to connect to IMS APIs at host zos123 and port 1490. The name of the IMS plex in this example is 'PLEX1' and the IMS region we want to communicate with has a host of zos124 and a port of 1491:
 - `zowe profiles create ims-profile ims123 --host zos123 --port 1490 --user ibmuser --pass myp4ss --plex PLEX1 --ich zos124 --icp 1491`

[zowe](#) › [profiles](#) › [create](#) › [mq-profile](#)

An MQREST profile is required to issue commands in the MQ command group that interacts with MQSC. The mq profile contains your host, port, user name, and password for the IBM MQ System Console interface

Warning: This command has been deprecated.
Recommended replacement: The 'config init' command

Usage

```
zowe profiles create mq-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the new mq profile. You can load this profile by using the name on commands that support the "--mq-profile" option.

MQ Connection Options

- `--host` | `-H` (*string*)
 - The host name used to access the IBM MQ REST API. This might be the host name of the IBM MQ mqweb server, or the Zowe API Mediation Layer..
- `--port` | `-P` (*number*)
 - The port number used to access the IBM MQ REST API. This might be the port number of the IBM MQ mqweb server, or the Zowe API Mediation Layer.
- `--user` | `-u` (*string*)
 - The mainframe (MQ) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - The mainframe (MQ) password, which can be the same as your TSO password.

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: false
- `--protocol` (*string*)
 - Specifies the MQ protocol (http or https).

Default value: http
Allowed values: http, https

Options

- `--overwrite` | `--ow` (*boolean*)
 - Overwrite the mq profile when a profile of the same name exists.
- `--disable-defaults` | `--dd` (*boolean*)
 - Disable populating profile values of undefined properties with default values.

Examples

- Create an MQ profile named 'mqprofile' to connect to MQ at host zos123 and port 1234:
 - `zowe profiles create mq-profile mq --host mq123 --port 1234 --user ibmuser -password myp4ss`

[zowe](#) › [profiles](#) › [create](#) › [ssh-profile](#)

z/OS SSH Profile

Warning: This command has been deprecated.

Recommended replacement: The 'config init' command

Usage

```
zowe profiles create ssh-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)

- Specifies the name of the new ssh profile. You can load this profile by using the name on commands that support the "--ssh-profile" option.

z/OS Ssh Connection Options

- `--host` | `-H` (*string*)
 - The z/OS SSH server host name.
- `--port` | `-P` (*number*)
 - The z/OS SSH server port.

Default value: 22
- `--user` | `-u` (*string*)
 - Mainframe user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe password, which can be the same as your TSO password.
- `--privateKey` | `--key` | `--pk` (*string*)
 - Path to a file containing your private key, that must match a public key stored in the server for authentication
- `--keyPassphrase` | `--passphrase` | `--kp` (*string*)
 - Private key passphrase, which unlocks the private key.
- `--handshakeTimeout` | `--timeout` | `--to` (*number*)
 - How long in milliseconds to wait for the SSH handshake to complete.

Options

- `--overwrite` | `--ow` (*boolean*)
 - Overwrite the ssh profile when a profile of the same name exists.
- `--disable-defaults` | `--dd` (*boolean*)
 - Disable populating profile values of undefined properties with default values.

Examples

- Create a ssh profile called 'ssh111' to connect to z/OS SSH server at host 'zos123' and default port 22:
 - `zowe profiles create ssh-profile ssh111 --host sshhost --user ibmuser --password myp4ss`
- Create a ssh profile called 'ssh222' to connect to z/OS SSH server at host 'zos123' and port 13022:
 - `zowe profiles create ssh-profile ssh222 --host sshhost --port 13022 --user ibmuser --password myp4ss`
- Create a ssh profile called 'ssh333' to connect to z/OS SSH server at host 'zos123' using a privatekey '/path/to/privatekey' and its decryption passphrase 'privateKeyPassphrase' for privatekey authentication:
 - `zowe profiles create ssh-profile ssh333 --host sshhost --user ibmuser --privateKey /path/to/privatekey --keyPassphrase privateKeyPassphrase`
- Create a ssh profile called 'ssh444' to connect to z/OS SSH server on default port 22, without specifying username, host, or password, preventing those values from being stored on disk:
 - `zowe profiles create ssh-profile ssh444 --privateKey /path/to/privatekey`

[zowe](#) › [profiles](#) › [create](#) › [tso-profile](#)

z/OS TSO/E User Profile

Warning: This command has been deprecated.

Recommended replacement: The 'config init' command

Usage

`zowe profiles create tso-profile <profileName> [options]`

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the new tso profile. You can load this profile by using the name on commands that support the "--tso-profile" option.

TSO ADDRESS SPACE OPTIONS

- `--account` | `-a` (*string*)

- Your z/OS TSO/E accounting information.
- `--character-set` | `--cs` (*string*)
 - Character set for address space to convert messages and responses from UTF-8 to EBCDIC.
 - Default value: 697
- `--code-page` | `--cp` (*string*)
 - Codepage value for TSO/E address space to convert messages and responses from UTF-8 to EBCDIC.
 - Default value: 1047
- `--columns` | `--cols` (*number*)
 - The number of columns on a screen.
 - Default value: 80
- `--logon-procedure` | `-l` (*string*)
 - The logon procedure to use when creating TSO procedures on your behalf.
 - Default value: IZUFPROC
- `--region-size` | `--rs` (*number*)
 - Region size for the TSO/E address space.
 - Default value: 4096
- `--rows` (*number*)
 - The number of rows on a screen.
 - Default value: 24

Options

- `--overwrite` | `--ow` (*boolean*)
 - Overwrite the tso profile when a profile of the same name exists.
- `--disable-defaults` | `--dd` (*boolean*)

- Disable populating profile values of undefined properties with default values.

Examples

- Create a tso profile called 'myprof' with default settings and JES accounting information of 'IZUACCT':

- `zowe profiles create tso-profile myprof -a IZUACCT`

- Create a tso profile called 'largeregion' with a region size of 8192, a logon procedure of MYPROC, and JES accounting information of '1234':

- `zowe profiles create tso-profile largeregion -a 1234 --rs 8192`

- Create a tso profile called 'myprof2' with default settings and region size of 8192, without storing the user account on disk:

- `zowe profiles create tso-profile myprof2 --rs 8192`

[zowe](#) › [profiles](#) › [create](#) › [zftp-profile](#)

Configuration profile for z/OS FTP

Warning: This command has been deprecated.

Recommended replacement: The 'config init' command

Usage

```
zowe profiles create zftp-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the new zftp profile. You can load this profile by using the name on commands that support the "--zftp-profile" option.

FTP Connection options

- `--host` | `-H` (*string*)
 - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
 - The port of the z/OS FTP server.

Default value: 21

- `--user` | `-u` (*string*)
 - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
 - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
 - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true

- `--connection-timeout` | `--ct` (*number*)
 - How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
 - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

Options

- `--overwrite` | `--ow` (*boolean*)
 - Overwrite the zftp profile when a profile of the same name exists.
- `--disable-defaults` | `--dd` (*boolean*)
 - Disable populating profile values of undefined properties with default values.

Examples

- Create a zftp profile called 'myprofile' with default settings (port, timeout, etc.) to connect with the host system 123.:
 - `zowe profiles create zftp-profile myprofile -u ibmuser -p ibmp4ss -H sys123`

zowe › profiles › create › zosmf-profile

z/OSMF Profile

Warning: This command has been deprecated.

Recommended replacement: The 'config init' command

Usage

```
zowe profiles create zosmf-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the new zosmf profile. You can load this profile by using the name on commands that support the "--zosmf-profile" option.

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.
Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)

- Reject self-signed certificates.

Default value: true

- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

Options

- `--encoding` | `--ec` (*string*)
 - The encoding for download and upload of z/OS data set and USS files. The default encoding if not specified is IBM-1047.
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600
- `--overwrite` | `--ow` (*boolean*)
 - Overwrite the zosmf profile when a profile of the same name exists.
- `--disable-defaults` | `--dd` (*boolean*)
 - Disable populating profile values of undefined properties with default values.

Examples

- Create a zosmf profile called 'zos123' to connect to z/OSMF at host zos123 and port 1443:
 - `zowe profiles create zosmf-profile zos123 --host zos123 --port 1443 --user ibmuser --password myp4ss`
- Create a zosmf profile called 'zos124' to connect to z/OSMF at the host zos124 (default port - 443) and allow self-signed certificates:
 - `zowe profiles create zosmf-profile zos124 --host zos124 --user ibmuser --password myp4ss --reject-unauthorized false`
- Create a zosmf profile called 'zos125' to connect to z/OSMF at the host zos125 and port 1443, not specifying a username or password so they are not stored on disk; these will need to be specified on every command:
 - `zowe profiles create zosmf-profile zos125 --host zos125 --port 1443`
- Create a zosmf profile called 'zos126' to connect to z/OSMF on the default port 443 and allow self-signed certificates, not specifying a username, password, or host so they are not stored on disk; these will need to be specified on every command:
 - `zowe profiles create zosmf-profile zos126 --reject-unauthorized false`
- Create a zosmf profile called 'zos124' to connect to z/OSMF at the host zos124 (default port - 443) and allow self-signed certificates:
 - `zowe profiles create zosmf-profile zosAPIML --host zosAPIML --port 2020 --user ibmuser --password myp4ss --reject-unauthorized false --base-path basePath`

[zowe](#) › [profiles](#) › [delete](#)

Delete existing profiles.

Warning: This group has been deprecated.

Recommended replacement: Edit your Zowe V2 configuration `zowe.config.json`

[zowe](#) › [profiles](#) › [delete](#) › [base-profile](#)

Delete a base profile. You must specify a profile name to be deleted. To find a list of available profiles for deletion, issue the `profiles list` command. By default, you will be prompted to confirm the profile removal.

Warning: This command has been deprecated.

Recommended replacement: Edit your Zowe V2 configuration `zowe.config.json`

Usage

`zowe profiles delete base-profile <profileName> [options]`

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the base profile to be deleted. You can also load this profile by using the name on commands that support the "--base-profile" option.

Options

- `--force` (*boolean*)
 - Force deletion of profile, and dependent profiles if specified. No prompt will be displayed before deletion occurs.

Examples

- Delete a base profile named `profileName`:
 - `zowe profiles delete base-profile profileName`

[zowe](#) › [profiles](#) › [delete](#) › [cics-profile](#)

Delete a cics profile. You must specify a profile name to be deleted. To find a list of available profiles for deletion, issue the `profiles list` command. By default, you will be prompted to confirm the profile removal.

Warning: This command has been deprecated.

Recommended replacement: Edit your Zowe V2 configuration `zowe.config.json`

Usage

`zowe profiles delete cics-profile <profileName> [options]`

Positional Arguments

- `profileName` (*string*)

- Specifies the name of the cics profile to be deleted. You can also load this profile by using the name on commands that support the "--cics-profile" option.

Options

- `--force` (*boolean*)
 - Force deletion of profile, and dependent profiles if specified. No prompt will be displayed before deletion occurs.

Examples

- Delete a cics profile named profilename:
 - `zowe profiles delete cics-profile profilename`

[zowe](#) › [profiles](#) › [delete](#) › [db2-profile](#)

Delete a db2 profile. You must specify a profile name to be deleted. To find a list of available profiles for deletion, issue the profiles list command. By default, you will be prompted to confirm the profile removal.

Warning: This command has been deprecated.

Recommended replacement: Edit your Zowe V2 configuration `zowe.config.json`

Usage

```
zowe profiles delete db2-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the db2 profile to be deleted. You can also load this profile by using the name on commands that support the "--db2-profile" option.

Options

- `--force` (*boolean*)
 - Force deletion of profile, and dependent profiles if specified. No prompt will be displayed before deletion occurs.

Examples

- Delete a db2 profile named profilename:
 - `zowe profiles delete db2-profile profilename`

[zowe](#) › [profiles](#) › [delete](#) › [ims-profile](#)

Delete a ims profile. You must specify a profile name to be deleted. To find a list of available profiles for deletion, issue the profiles list command. By default, you will be prompted to confirm the profile removal.

Warning: This command has been deprecated.

Recommended replacement: Edit your Zowe V2 configuration `zowe.config.json`

Usage

```
zowe profiles delete ims-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the ims profile to be deleted. You can also load this profile by using the name on commands that support the "--ims-profile" option.

Options

- `--force` (*boolean*)
 - Force deletion of profile, and dependent profiles if specified. No prompt will be displayed before deletion occurs.

Examples

- Delete a ims profile named profilename:
 - `zowe profiles delete ims-profile profilename`

[zowe](#) › [profiles](#) › [delete](#) › [mq-profile](#)

Delete a mq profile. You must specify a profile name to be deleted. To find a list of available profiles for deletion, issue the profiles list command. By default, you will be prompted to confirm the profile removal.

Warning: This command has been deprecated.

Recommended replacement: Edit your Zowe V2 configuration `zowe.config.json`

Usage

`zowe profiles delete mq-profile <profileName> [options]`

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the mq profile to be deleted. You can also load this profile by using the name on commands that support the "--mq-profile" option.

Options

- `--force` (*boolean*)
 - Force deletion of profile, and dependent profiles if specified. No prompt will be displayed before deletion occurs.

Examples

- Delete a mq profile named profilename:
 - `zowe profiles delete mq-profile profilename`

[zowe](#) › [profiles](#) › [delete](#) › [ssh-profile](#)

Delete a ssh profile. You must specify a profile name to be deleted. To find a list of available profiles for deletion, issue the profiles list command. By default, you will be prompted to confirm the profile removal.

Warning: This command has been deprecated.

Recommended replacement: Edit your Zowe V2 configuration `zowe.config.json`

Usage

`zowe profiles delete ssh-profile <profileName> [options]`

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the ssh profile to be deleted. You can also load this profile by using the name on commands that support the "--ssh-profile" option.

Options

- `--force` (*boolean*)
 - Force deletion of profile, and dependent profiles if specified. No prompt will be displayed before deletion occurs.

Examples

- Delete a ssh profile named profilename:
 - `zowe profiles delete ssh-profile profilename`

[zowe](#) › [profiles](#) › [delete](#) › [tso-profile](#)

Delete a tso profile. You must specify a profile name to be deleted. To find a list of available profiles for deletion, issue the profiles list command. By default, you will be prompted to confirm the profile removal.

Warning: This command has been deprecated.

Recommended replacement: Edit your Zowe V2 configuration `zowe.config.json`

Usage

```
zowe profiles delete tso-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the tso profile to be deleted. You can also load this profile by using the name on commands that support the "--tso-profile" option.

Options

- `--force` (*boolean*)
 - Force deletion of profile, and dependent profiles if specified. No prompt will be displayed before deletion occurs.

Examples

- Delete a tso profile named profilename:
 - `zowe profiles delete tso-profile profilename`

[zowe](#) › [profiles](#) › [delete](#) › [zftp-profile](#)

Delete a zftp profile. You must specify a profile name to be deleted. To find a list of available profiles for deletion, issue the profiles list command. By default, you will be prompted to confirm the profile removal.

Warning: This command has been deprecated.

Recommended replacement: Edit your Zowe V2 configuration `zowe.config.json`

Usage

```
zowe profiles delete zftp-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the zftp profile to be deleted. You can also load this profile by using the name on commands that support the "--zftp-profile" option.

Options

- `--force` (*boolean*)
 - Force deletion of profile, and dependent profiles if specified. No prompt will be displayed before deletion occurs.

Examples

- Delete a zftp profile named `profilename`:
 - `zowe profiles delete zftp-profile profilename`

[zowe](#) › [profiles](#) › [delete](#) › [zosmf-profile](#)

Delete a zosmf profile. You must specify a profile name to be deleted. To find a list of available profiles for deletion, issue the profiles list command. By default, you will be prompted to confirm the profile removal.

Warning: This command has been deprecated.

Recommended replacement: Edit your Zowe V2 configuration `zowe.config.json`

Usage

```
zowe profiles delete zosmf-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the zosmf profile to be deleted. You can also load this profile by using the name on commands that support the "--zosmf-profile" option.

Options

- `--force` (*boolean*)
 - Force deletion of profile, and dependent profiles if specified. No prompt will be displayed before deletion occurs.

Examples

- Delete a zosmf profile named profilename:
 - `zowe profiles delete zosmf-profile profilename`

[zowe](#) › [profiles](#) › [list](#)

List profiles of the type `{{type}}`.

Warning: This group has been deprecated.

Recommended replacement: The 'config list' command

[zowe](#) › [profiles](#) › [list](#) › [base-profiles](#)

Base profile that stores values shared by multiple service profiles

Warning: This command has been deprecated.

Recommended replacement: The 'config list' command

Usage

```
zowe profiles list base-profiles [options]
```

Options

- `--show-contents` | `--sc` (*boolean*)
 - List base profiles and their contents. All profile details will be printed as part of command output.

Examples

- List profiles of type base:
 - `zowe profiles list base-profiles`
- List profiles of type base and display their contents:
 - `zowe profiles list base-profiles --sc`

[zowe](#) › [profiles](#) › [list](#) › [cics-profiles](#)

A cics profile is required to issue commands in the cics command group that interact with CICS regions. The cics profile contains your host, port, user name, and password for the IBM CICS management client interface (CMCI) server of your choice.

Warning: This command has been deprecated.

Recommended replacement: The 'config list' command

Usage

`zowe profiles list cics-profiles [options]`

Options

- `--show-contents` | `--sc` (*boolean*)
 - List cics profiles and their contents. All profile details will be printed as part of command output.

Examples

- List profiles of type cics:
 - `zowe profiles list cics-profiles`
- List profiles of type cics and display their contents:
 - `zowe profiles list cics-profiles --sc`

[zowe](#) › [profiles](#) › [list](#) › [db2-profiles](#)

A profile for interaction with Db2 for the z/OS region

Warning: This command has been deprecated.

Recommended replacement: The 'config list' command

Usage

zowe profiles list db2-profiles [options]

Options

- `--show-contents` | `--sc` (*boolean*)
 - List db2 profiles and their contents. All profile details will be printed as part of command output.

Examples

- List profiles of type db2:
 - `zowe profiles list db2-profiles`
- List profiles of type db2 and display their contents:
 - `zowe profiles list db2-profiles --sc`

[zowe](#) › [profiles](#) › [list](#) › [ims-profiles](#)

An ims profile is used to issue commands in the ims command group that interact with IMS regions. The ims profile contains your IMS Operations API web server host, port, user name and password, IMS Connect host and port and IMS plex name.

Warning: This command has been deprecated.

Recommended replacement: The 'config list' command

Usage

zowe profiles list ims-profiles [options]

Options

- `--show-contents` | `--sc` (*boolean*)
 - List ims profiles and their contents. All profile details will be printed as part of command output.

Examples

- List profiles of type ims:
 - `zowe profiles list ims-profiles`
- List profiles of type ims and display their contents:

- `zowe profiles list ims-profiles --sc`

[zowe](#) › [profiles](#) › [list](#) › [mq-profiles](#)

An MQREST profile is required to issue commands in the MQ command group that interacts with MQSC. The mq profile contains your host, port, user name, and password for the IBM MQ System Console interface

Warning: This command has been deprecated.

Recommended replacement: The 'config list' command

Usage

`zowe profiles list mq-profiles [options]`

Options

- `--show-contents` | `--sc` (*boolean*)
 - List mq profiles and their contents. All profile details will be printed as part of command output.

Examples

- List profiles of type mq:
 - `zowe profiles list mq-profiles`
- List profiles of type mq and display their contents:
 - `zowe profiles list mq-profiles --sc`

[zowe](#) › [profiles](#) › [list](#) › [ssh-profiles](#)

z/OS SSH Profile

Warning: This command has been deprecated.

Recommended replacement: The 'config list' command

Usage

`zowe profiles list ssh-profiles [options]`

Options

- `--show-contents` | `--sc` (*boolean*)
 - List ssh profiles and their contents. All profile details will be printed as part of command output.

Examples

- List profiles of type ssh:
 - `zowe profiles list ssh-profiles`
- List profiles of type ssh and display their contents:
 - `zowe profiles list ssh-profiles --sc`

[zowe](#) › [profiles](#) › [list](#) › [tso-profiles](#)

z/OS TSO/E User Profile

Warning: This command has been deprecated.
Recommended replacement: The 'config list' command

Usage

`zowe profiles list tso-profiles [options]`

Options

- `--show-contents` | `--sc` (*boolean*)
 - List tso profiles and their contents. All profile details will be printed as part of command output.

Examples

- List profiles of type tso:
 - `zowe profiles list tso-profiles`
- List profiles of type tso and display their contents:
 - `zowe profiles list tso-profiles --sc`

[zowe](#) › [profiles](#) › [list](#) › [zftp-profiles](#)

Configuration profile for z/OS FTP

Warning: This command has been deprecated.
Recommended replacement: The 'config list' command

Usage

zowe profiles list zftp-profiles [options]

Options

- `--show-contents` | `--sc` (*boolean*)
 - List zftp profiles and their contents. All profile details will be printed as part of command output.

Examples

- List profiles of type zftp:
 - `zowe profiles list zftp-profiles`
- List profiles of type zftp and display their contents:
 - `zowe profiles list zftp-profiles --sc`

[zowe](#) › [profiles](#) › [list](#) › [zosmf-profiles](#)

z/OSMF Profile

Warning: This command has been deprecated.
Recommended replacement: The 'config list' command

Usage

zowe profiles list zosmf-profiles [options]

Options

- `--show-contents` | `--sc` (*boolean*)
 - List zosmf profiles and their contents. All profile details will be printed as part of command output.

Examples

- List profiles of type zosmf:

- `zowe profiles list zosmf-profiles`
- List profiles of type zosmf and display their contents:
 - `zowe profiles list zosmf-profiles --sc`

[zowe](#) › [profiles](#) › [set-default](#)

Set which profiles are loaded by default.

Warning: This group has been deprecated.

Recommended replacement: The 'config set' command

[zowe](#) › [profiles](#) › [set-default](#) › [base-profile](#)

The base set default-profiles command allows you to set the default profiles for this command group. When a base command is issued and no profile override options are specified, the default profiles for the command group are automatically loaded for the command based on the commands profile requirements.

Warning: This command has been deprecated.

Recommended replacement: The 'config set' command

Usage

```
zowe profiles set-default base-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specify a profile for default usage within the base group. When you issue commands within the base group without a profile specified as part of the command, the default will be loaded instead.

Examples

- Set the default profile for type base to the profile named 'profilename':
 - `zowe profiles set-default base-profile profilename`

[zowe](#) › [profiles](#) › [set-default](#) › [cics-profile](#)

The `cics set default-profiles` command allows you to set the default profiles for this command group. When a `cics` command is issued and no profile override options are specified, the default profiles for the command group are automatically loaded for the command based on the commands profile requirements.

Warning: This command has been deprecated.

Recommended replacement: The 'config set' command

Usage

```
zowe profiles set-default cics-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specify a profile for default usage within the `cics` group. When you issue commands within the `cics` group without a profile specified as part of the command, the default will be loaded instead.

Examples

- Set the default profile for type `cics` to the profile named 'profilename':
 - `zowe profiles set-default cics-profile profilename`

[zowe](#) › [profiles](#) › [set-default](#) › [db2-profile](#)

The `db2 set default-profiles` command allows you to set the default profiles for this command group. When a `db2` command is issued and no profile override options are specified, the default profiles for the command group are automatically loaded for the command based on the commands profile requirements.

Warning: This command has been deprecated.

Recommended replacement: The 'config set' command

Usage

```
zowe profiles set-default db2-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)

- Specify a profile for default usage within the db2 group. When you issue commands within the db2 group without a profile specified as part of the command, the default will be loaded instead.

Examples

- Set the default profile for type db2 to the profile named 'profilename':

- `zowe profiles set-default db2-profile profilename`

[zowe](#) › [profiles](#) › [set-default](#) › [ims-profile](#)

The `ims set default-profiles` command allows you to set the default profiles for this command group. When a `ims` command is issued and no profile override options are specified, the default profiles for the command group are automatically loaded for the command based on the commands profile requirements.

Warning: This command has been deprecated.

Recommended replacement: The 'config set' command

Usage

```
zowe profiles set-default ims-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specify a profile for default usage within the `ims` group. When you issue commands within the `ims` group without a profile specified as part of the command, the default will be loaded instead.

Examples

- Set the default profile for type `ims` to the profile named 'profilename':

- `zowe profiles set-default ims-profile profilename`

[zowe](#) › [profiles](#) › [set-default](#) › [mq-profile](#)

The `mq set default-profiles` command allows you to set the default profiles for this command group. When a `mq` command is issued and no profile override options are specified, the default

profiles for the command group are automatically loaded for the command based on the commands profile requirements.

Warning: This command has been deprecated.

Recommended replacement: The 'config set' command

Usage

```
zowe profiles set-default mq-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specify a profile for default usage within the mq group. When you issue commands within the mq group without a profile specified as part of the command, the default will be loaded instead.

Examples

- Set the default profile for type mq to the profile named 'profileName':
 - `zowe profiles set-default mq-profile profileName`

[zowe](#) › [profiles](#) › [set-default](#) › [ssh-profile](#)

The ssh set default-profiles command allows you to set the default profiles for this command group. When a ssh command is issued and no profile override options are specified, the default profiles for the command group are automatically loaded for the command based on the commands profile requirements.

Warning: This command has been deprecated.

Recommended replacement: The 'config set' command

Usage

```
zowe profiles set-default ssh-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specify a profile for default usage within the ssh group. When you issue commands within the ssh

group without a profile specified as part of the command, the default will be loaded instead.

Examples

- Set the default profile for type ssh to the profile named 'profilename':

- `zowe profiles set-default ssh-profile profilename`

[zowe](#) › [profiles](#) › [set-default](#) › [tso-profile](#)

The tso set default-profiles command allows you to set the default profiles for this command group. When a tso command is issued and no profile override options are specified, the default profiles for the command group are automatically loaded for the command based on the commands profile requirements.

Warning: This command has been deprecated.

Recommended replacement: The 'config set' command

Usage

```
zowe profiles set-default tso-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specify a profile for default usage within the tso group. When you issue commands within the tso group without a profile specified as part of the command, the default will be loaded instead.

Examples

- Set the default profile for type tso to the profile named 'profilename':

- `zowe profiles set-default tso-profile profilename`

[zowe](#) › [profiles](#) › [set-default](#) › [zftp-profile](#)

The zftp set default-profiles command allows you to set the default profiles for this command group. When a zftp command is issued and no profile override options are specified, the default profiles for the command group are automatically loaded for the command based on the commands profile requirements.

Warning: This command has been deprecated.

Recommended replacement: The 'config set' command

Usage

```
zowe profiles set-default zftp-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specify a profile for default usage within the zftp group. When you issue commands within the zftp group without a profile specified as part of the command, the default will be loaded instead.

Examples

- Set the default profile for type zftp to the profile named 'profileName':
 - `zowe profiles set-default zftp-profile profileName`

[zowe](#) › [profiles](#) › [set-default](#) › [zosmf-profile](#)

The zosmf set default-profiles command allows you to set the default profiles for this command group. When a zosmf command is issued and no profile override options are specified, the default profiles for the command group are automatically loaded for the command based on the commands profile requirements.

Warning: This command has been deprecated.

Recommended replacement: The 'config set' command

Usage

```
zowe profiles set-default zosmf-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specify a profile for default usage within the zosmf group. When you issue commands within the zosmf group without a profile specified as part of the command, the default will be loaded instead.

Examples

- Set the default profile for type zosmf to the profile named 'profilename':
 - `zowe profiles set-default zosmf-profile profilename`

zowe › profiles › update

Update a {{type}} profile. You can update any property present within the profile configuration. The updated profile will be printed so that you can review the result of the updates.

Warning: This group has been deprecated.

Recommended replacement: The 'config set' command

zowe › profiles › update › base-profile

Base profile that stores values shared by multiple service profiles

Warning: This command has been deprecated.

Recommended replacement: The 'config set' command

Usage

```
zowe profiles update base-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the new base profile. You can load this profile by using the name on commands that support the "--base-profile" option.

Base Connection Options

- `--host` | `-H` (*string*)
 - Host name of service on the mainframe.
- `--port` | `-P` (*number*)
 - Port number of service on the mainframe.
- `--user` | `-u` (*string*)
 - User name to authenticate to service on the mainframe.

- `--password` | `--pass` | `--pw` (*string*)
 - Password to authenticate to service on the mainframe.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Update a base profile named 'base1' with a new username and password:
 - `zowe profiles update base-profile base1 --user newuser --password newp4ss`

[zowe](#) › [profiles](#) › [update](#) › [cics-profile](#)

A cics profile is required to issue commands in the cics command group that interact with CICS regions. The cics profile contains your host, port, user name, and password for the IBM CICS management client interface (CMCI) server of your choice.

Warning: This command has been deprecated.

Recommended replacement: The 'config set' command

Usage

```
zowe profiles update cics-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)

- Specifies the name of the new cics profile. You can load this profile by using the name on commands that support the "--cics-profile" option.

Options

- `--host` | `-H` (*string*)
 - The CMCI server host name
- `--port` | `-P` (*number*)
 - The CMCI server port
- `--user` | `-u` (*string*)
 - Your username to connect to CICS
- `--password` | `-p` (*string*)
 - Your password to connect to CICS
- `--region-name` (*string*)
 - The name of the CICS region name to interact with
- `--cics-plex` (*string*)
 - The name of the CICSplex to interact with

Cics Connection Options

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
- `--protocol` | `-o` (*string*)
 - Specifies CMCI protocol (http or https).

Allowed values: http, https

[zowe](#) › [profiles](#) › [update](#) › [db2-profile](#)

A profile for interaction with Db2 for the z/OS region

Warning: This command has been deprecated.

Recommended replacement: The 'config set' command

Usage

```
zowe profiles update db2-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the new db2 profile. You can load this profile by using the name on commands that support the "--db2-profile" option.

Options

- `--host` | `-H` (*string*)
 - The Db2 server host name
- `--port` | `-P` (*number*)
 - The Db2 server port number
- `--user` | `-u` (*string*)
 - The Db2 user ID (may be the same as the TSO login)
- `--password` | `--pass` | `--pw` (*string*)
 - The Db2 password (may be the same as the TSO password)
- `--database` | `-d` (*string*)
 - The name of the database
- `--ssl-file` | `-s` (*string*)
 - Path to an SSL Certificate file

[zowe](#) › [profiles](#) › [update](#) › [ims-profile](#)

An ims profile is used to issue commands in the ims command group that interact with IMS regions. The ims profile contains your IMS Operations API web server host, port, user name and password, IMS Connect host and port and IMS plex name.

Warning: This command has been deprecated.

Recommended replacement: The 'config set' command

Usage

zowe profiles update ims-profile <profileName> [options]

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the new ims profile. You can load this profile by using the name on commands that support the "--ims-profile" option.

IMS Connection Options

- `--host` | `-H` (*string*)
 - The IMS Operations API server host name.
- `--port` | `-P` (*number*)
 - The IMS Operations API server port.
- `--ims-connect-host` | `--ich` (*string*)
 - The hostname of your instance of IMS Connect. This is typically the hostname of the mainframe LPAR where IMS Connect is running.
- `--ims-connect-port` | `--icp` (*number*)
 - The port of your instance of IMS Connect. This port can be found in your IMS Connect configuration file on the mainframe.
- `--plex` | `-x` (*string*)
 - The name of the IMS plex.
- `--user` | `-u` (*string*)
 - The web server user name where the IMS Operations API resides.
- `--password` | `--pass` (*string*)
 - The web server user password where the IMS Operations API resides.
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.

- `--protocol` (*string*)
 - Specifies protocol (http or https).
Allowed values: http, https
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

[zowe](#) › [profiles](#) › [update](#) › [mq-profile](#)

An MQREST profile is required to issue commands in the MQ command group that interacts with MQSC. The mq profile contains your host, port, user name, and password for the IBM MQ System Console interface

Warning: This command has been deprecated.

Recommended replacement: The 'config set' command

Usage

```
zowe profiles update mq-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the new mq profile. You can load this profile by using the name on commands that support the "--mq-profile" option.

MQ Connection Options

- `--host` | `-H` (*string*)
 - The host name used to access the IBM MQ REST API. This might be the host name of the IBM MQ mqweb server, or the Zowe API Mediation Layer..
- `--port` | `-P` (*number*)
 - The port number used to access the IBM MQ REST API. This might be the port number of the IBM MQ mqweb server, or the Zowe API Mediation Layer.
- `--user` | `-u` (*string*)
 - The mainframe (MQ) user name, which can be the same as your TSO login.

- `--password` | `--pass` | `--pw` (*string*)
 - The mainframe (MQ) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
- `--protocol` (*string*)
 - Specifies the MQ protocol (http or https).

Allowed values: http, https

[zowe](#) › [profiles](#) › [update](#) › [ssh-profile](#)

z/OS SSH Profile

Warning: This command has been deprecated.

Recommended replacement: The 'config set' command

Usage

`zowe profiles update ssh-profile <profileName> [options]`

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the new ssh profile. You can load this profile by using the name on commands that support the "--ssh-profile" option.

z/OS Ssh Connection Options

- `--host` | `-H` (*string*)
 - The z/OS SSH server host name.
- `--port` | `-P` (*number*)
 - The z/OS SSH server port.
- `--user` | `-u` (*string*)
 - Mainframe user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)

- Mainframe password, which can be the same as your TSO password.
- `--privateKey` | `--key` | `--pk` (*string*)
 - Path to a file containing your private key, that must match a public key stored in the server for authentication
- `--keyPassphrase` | `--passphrase` | `--kp` (*string*)
 - Private key passphrase, which unlocks the private key.
- `--handshakeTimeout` | `--timeout` | `--to` (*number*)
 - How long in milliseconds to wait for the SSH handshake to complete.

[zowe](#) › [profiles](#) › [update](#) › [tso-profile](#)

z/OS TSO/E User Profile

Warning: This command has been deprecated.

Recommended replacement: The 'config set' command

Usage

`zowe profiles update tso-profile <profileName> [options]`

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the new tso profile. You can load this profile by using the name on commands that support the "--tso-profile" option.

TSO ADDRESS SPACE OPTIONS

- `--account` | `-a` (*string*)
 - Your z/OS TSO/E accounting information.
- `--character-set` | `--cs` (*string*)
 - Character set for address space to convert messages and responses from UTF-8 to EBCDIC.
- `--code-page` | `--cp` (*string*)

- Codepage value for TSO/E address space to convert messages and responses from UTF-8 to EBCDIC.
- `--columns` | `--cols` (*number*)
 - The number of columns on a screen.
- `--logon-procedure` | `-l` (*string*)
 - The logon procedure to use when creating TSO procedures on your behalf.
- `--region-size` | `--rs` (*number*)
 - Region size for the TSO/E address space.
- `--rows` (*number*)
 - The number of rows on a screen.

Examples

- Update a tso profile called myprof with new JES accounting information:
 - `zowe profiles update tso-profile myprof -a NEWACCT`

[zowe](#) › [profiles](#) › [update](#) › [zftp-profile](#)

Configuration profile for z/OS FTP

Warning: This command has been deprecated.

Recommended replacement: The 'config set' command

Usage

```
zowe profiles update zftp-profile <profileName> [options]
```

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the new zftp profile. You can load this profile by using the name on commands that support the "--zftp-profile" option.

FTP Connection options

- `--host` | `-H` (*string*)

- The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
 - The port of the z/OS FTP server.
- `--user` | `-u` (*string*)
 - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
 - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
 - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.
- `--connection-timeout` | `--ct` (*number*)
 - How long (in milliseconds) to wait for the control connection to be established.

TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
 - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

[zowe](#) › [profiles](#) › [update](#) › [zosmf-profile](#)

z/OSMF Profile

Warning: This command has been deprecated.

Recommended replacement: The 'config set' command

Usage

zowe profiles update zosmf-profile <profileName> [options]

Positional Arguments

- `profileName` (*string*)
 - Specifies the name of the new zosmf profile. You can load this profile by using the name on commands that support the "--zosmf-profile" option.

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)

- The protocol used (HTTP or HTTPS)

Allowed values: http, https

Options

- `--encoding` | `--ec` (*string*)
 - The encoding for download and upload of z/OS data set and USS files. The default encoding if not specified is IBM-1047.
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Examples

- Update a zosmf profile named 'zos123' with a new username and password:
 - `zowe profiles update zosmf-profile zos123 --user newuser --password newp4ss`

zowe › provisioning

Perform z/OSMF provisioning tasks on Published Templates in the Service Catalog and Provisioned Instances in the Service Registry.

zowe › provisioning › delete

Deletes instance previously provisioned with z/OSMF cloud provisioning services.

zowe › provisioning › delete › instance

Deletes selected deprovisioned instance.

Usage

```
zowe provisioning delete instance <name> [options]
```

Positional Arguments

- `name` (*string*)
 - Deprovisioned Instance name.

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.
Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)

- Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)

- The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.

- `--protocol` (*string*)

- The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)

- The file path to a certificate file to use for authentication

- `--cert-key-file` (*local file path*)

- The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)

- The name of a (zosmf) profile to load for this command execution.

- `--base-profile` | `--base-p` (*string*)

- The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)

- The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.

- `--token-value` | `--tv` (*string*)

- The value of the token to pass to the API.

Examples

- Delete deprovisioned instance "instance1":
 - `zowe provisioning delete instance instance1`

[zowe](#) › [provisioning](#) › [list](#)

Lists z/OSMF provisioning information such as the provisioned instances from the registry, the provisioned instance details, the available provisioning templates and provisioning template details.

[zowe](#) › [provisioning](#) › [list](#) › [catalog-templates](#)

Lists the z/OSMF service catalog published templates.

Usage

`zowe provisioning list catalog-templates [options]`

Options

- `--all-info` | `--ai` (*boolean*)
 - Display information about published z/OSMF service catalog templates (summary information is printed by default).

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)

- Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)

- The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.

- `--protocol` (*string*)

- The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)

- The file path to a certificate file to use for authentication

- `--cert-key-file` (*local file path*)

- The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)

- The name of a (zosmf) profile to load for this command execution.

- `--base-profile` | `--base-p` (*string*)

- The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)

- The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.

- `--token-value` | `--tv` (*string*)

- The value of the token to pass to the API.

Examples

- List all published templates in the z/OSMF service catalog (with full detail):

- `zowe provisioning list catalog-templates --all-info`

[zowe](#) › [provisioning](#) › [list](#) › [instance-info](#)

List details about an instance provisioned with z/OSMF.

Usage

```
zowe provisioning list instance-info <name> [options]
```

Positional Arguments

- `name` (*string*)
 - Provisioned Instance Name

Options

- `--display` (*string*)
 - Level of information to display for the provisioned instance. Possible values:

summary - summary information, no actions or variables
actions - (default) summary with actions, no variables
vars - summary information with variables, no actions
extended - extended information with actions
full - all available information

Allowed values: extended, summary, vars, actions, full

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)

- Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)

- The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- List summary information with a list of actions for an instance with the name "instance1":
 - `zowe provisioning list instance-info instance1`
- Show extended general information with actions for a provisioned instance with the name "instance1":
 - `zowe provisioning list instance-info instance1 --display extended`

[zowe](#) › [provisioning](#) › [list](#) › [instance-variables](#)

List a set of variables and their values for a given name.

Usage

```
zowe provisioning list instance-variables <name> [options]
```

Positional Arguments

- `name` (*string*)
 - Provisioned Instance Name

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443

- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.

- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.

- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Response Format Options

- `--response-format-filter` | `--rff` (*array*)
 - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '`--response-format-type`' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
 - The command response output format type. Must be one of the following:
 - table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.
 - list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.
 - object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.
 - string: Formats output data as a string. JSON objects/arrays are stringified.
 - Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
 - If "`--response-format-type table`" is specified, include the column headers in the output.

Examples

- List instance variables of "instance1":
 - `zowe provisioning list instance-variables instance1`

[zowe](#) › [provisioning](#) › [list](#) › [registry-instances](#)

List the provisioned instances from the z/OSMF software registry.

Usage

zowe provisioning list registry-instances [options]

Options

- `--all-info` | `--ai` (*boolean*)
 - Display all available information about provisioned instances (summary by default).
- `--filter-by-type` | `--fbt` (*string*)
 - Filter the list of provisioned instances by type (e.g. DB2 or CICS).
- `--filter-by-external-name` | `--fben` (*string*)
 - Filter the list of provisioned instances by External Name.
- `--types` | `-t` (*boolean*)
 - Display a list of all types for provisioned instances (e.g. DB2 or CICS).

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)

- The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- List all provisioned instances (with full detail):
 - `zowe provisioning list registry-instances --all-info`

List details about a template published with z/OSMF Cloud Provisioning.

Usage

```
zowe provisioning list template-info <name> [options]
```

Positional Arguments

- `name` (*string*)
 - The name of a z/OSMF cloud provisioning template.

Options

- `--all-info` | `--ai` (*boolean*)
 - Display detailed information about published z/OSMF service catalog template (summary information is printed by default).

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.
Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
Default value: true
- `--base-path` | `--bp` (*string*)

- The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)
 - Default value: https
 - Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- List summary information for template "template1":
 - `zowe provisioning list template-info template1`

zowe › provisioning › perform

Perform actions against instances provisioned with z/OSMF.

zowe › provisioning › perform › action

Perform actions on instances previously provisioned with z/OSMF cloud provisioning services. To view the list of provisioned instances, use the "zowe provisioning list registry-instances" command. Once you have obtained an instance name you can use the "zowe provisioning list instance-info <name>" command to view the available instance actions.

Usage

```
zowe provisioning perform action <name> <actionname> [options]
```

Positional Arguments

- `name` (*string*)
 - Provisioned Instance name.
- `actionname` (*string*)
 - The action name. Use the "zowe provisioning list instance-info <name>" command to view available instance actions.

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Perform the "start" action on the provisioned instance "instance1":
 - `zowe provisioning perform action instance1 start`

zowe › provisioning › provision

Using z/OSMF cloud provisioning services provision available templates.

zowe › provisioning › provision › template

Using z/OSMF cloud provisioning services, provision available templates.

You can view available templates using the `zowe provisioning list catalog-templates` command.

Usage

```
zowe provisioning provision template <name> [options]
```

Positional Arguments

- `name` (*string*)
 - The name of a z/OSMF cloud provisioning template.

Options

- `--properties` | `-p` (*string*)
 - A sequence of string enclosed "name=value" pairs of prompt variables.
e.g: "CSQ_MQ_SSID=ZCT1,CSQ_CMD_PFX=!ZCT1".
- `--properties-file` | `--pf` (*string*)
 - Path to .yml file containing properties.
- `--domain-name` | `--dn` (*string*)
 - Required if the user has consumer authorization to more than one domain with this template name.
- `--tenant-name` | `--tn` (*string*)
 - Required if the user has consumer authorization to more than one tenant in the same domain that contains this template name.

- `--user-data-id` | `--udi` (*string*)
 - ID for the user data specified with `user-data`. Passed into the software services registry.
- `--user-data` | `--ud` (*string*)
 - User data that is passed into the software services registry. Can be specified only if `user-data-id` is provided.
- `--account-info` | `--ai` (*string*)
 - Account information to use in the JCL JOB statement. The default is the account information that is associated with the resource pool for the tenant.
- `--system-nick-names` | `--snn` (*string*)
 - Each string is the nickname of the system upon which to provision the software service defined by the template. The field is required if the resource pool associated with the tenant used for this operation is not set up to automatically select a system. Only one nickname is allowed. If the field is provided it is validated.
e.g: "SYSNAME1,SYSNAME2".

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Provision a published software service template.:
 - `zowe provisioning provision template template1`

zowe › zos-console

Interact with z/OSMF console services. Issue z/OS console commands and collect responses. z/OS console services establishes extended MCS (EMCS) consoles on behalf of the user, which are used to issue the commands and collect responses.

Important! Before you use commands in the zos-console command group, ensure that you understand the implications of issuing z/OS console commands in your environment.

zowe › zos-console › collect

z/OSMF console services provides a command response key upon successful issue of a console command. You can use this key to collect additional console message responses.

zowe › zos-console › collect › sync-responses

The z/OSMF console REST APIs return a "solicited response key" after successfully issuing a synchronous console command that produces solicited responses. You can use the "solicited response key" on the "sync-responses" command to collect any additional outstanding solicited responses from the console the command was issued.

In general, when issuing a z/OS console command, z/OS applications route responses to the originating console. The command response messages are referred to as "solicited command responses" (i.e. direct responses to the command issued). When issuing a z/OS console command using Zowe CLI, collection of all solicited command responses is attempted by default. However, there is no z/OS mechanism that indicates the total number of response messages that may be produced from a given command. Therefore, the Zowe CLI console APIs return a "solicited response key" that can be used to "follow-up" and collect any additional solicited command responses.

Usage

```
zowe zos-console collect sync-responses <responsekey> [options]
```

Positional Arguments

- `responsekey` (*string*)
 - The "solicited response key" provided in response to a previously issued console command. Used by the z/OSMF console API to collect any additional outstanding

solicited responses from a previously issued console command. Must match regular expression: `^\[a\ -zA\ -Z0\ -9\]\+$`

Options

- `--console-name` | `--cn` | `-c` (*string*)
 - The name of the z/OS extended MCS console to direct the command. You must have the required authority to access the console specified. You may also specify an arbitrary name, if your installation allows dynamic creation of consoles with arbitrary names.

Allowed values: `^\[a-zA-Z0-9\]+`

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)

- The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Collect any outstanding additional solicited response messages:
 - `zowe zos-console collect sync-responses C4866969`

[zowe](#) › [zos-console](#) › [issue](#)

Issue z/OS console commands and optionally collect responses.

[zowe](#) › [zos-console](#) › [issue](#) › [command](#)

Issue a z/OS console command and print command responses (known as "solicited command responses").

In general, when issuing a z/OS console command, z/OS applications route responses to the originating console. The command response messages are referred to as "solicited command responses" (i.e. direct responses to the command issued). When issuing a z/OS console command using Zowe CLI, collection of all solicited command responses is attempted by default. However, there is no z/OS mechanism that indicates the total number of response messages that may be produced from a given command. Therefore, the Zowe CLI console APIs return a "solicited response key" that can be used to "follow-up" and collect any additional solicited command responses.

Zowe CLI will issue "follow-up" API requests by default to collect any additional outstanding solicited command responses until a request returns no additional responses. At that time, Zowe CLI will attempt a final collection attempt. If no messages are present, the command is complete. If additional messages are present, the process is repeated. However, this does not guarantee that all messages produced in direct response (i.e. solicited) have been collected. The z/OS application may produce additional messages in direct response to your command at some point in the future. You can manually collect additional responses using the "command response key" OR specify additional processing options to, for example, delay collection attempts by a specified interval.

Usage

```
zowe zos-console issue command <commandtext> [options]
```

Positional Arguments

- `commandtext` (*string*)
 - The z/OS console command to issue.

Options

- `--console-name` | `--cn` | `-c` (*string*)
 - The name of the z/OS extended MCS console to direct the command. You must have the required authority to access the console specified. You may also specify an arbitrary name, if your installation allows dynamic creation of consoles with arbitrary names.

Allowed values: `^[a-zA-Z0-9]+$`

- `--include-details` | `--id` | `-i` (*boolean*)

- Include additional details at the end of the Zowe CLI command response, such as the "command response key" and the z/OSMF command response URL.
- `--key-only` | `--ko` | `-k` (*boolean*)
 - Displays only the "command response key" returned from the z/OSMF console API. You can collect additional messages using the command key with 'zowe zos-console collect sync-responses <key>'. Note that when using this option, you will not be presented with the "first set" of command response messages (if present in the API response). However, you can view them by using the `--response-format-json` option.
- `--return-first` | `--rf` | `-r` (*boolean*)
 - Indicates that Zowe CLI should return immediately with the response message set returned in the first z/OSMF API request (even if no responses are present). Using this option may result in partial or no response, but quicker Zowe CLI command response time. The z/OSMF console API has an implicit wait when collecting the first set of console command responses, i.e you will normally receive at least one set of response messages.
- `--solicited-keyword` | `--sk` | `-s` (*string*)
 - For solicited responses (direct command responses) the response is considered complete if the keyword specified is present. If the keyword is detected, the command will immediately return, meaning the full command response may not be provided. The key only applies to the first request issued, follow up requests do not support searching for the keyword.
- `--sysplex-system` | `--ss` | `--sys` (*string*)
 - Specifies the z/OS system (LPAR) in the current SYSPLEX (where your target z/OSMF resides) to route the z/OS console command.
- `--wait-to-collect` | `--wtc` | `-w` (*number*)
 - Indicates that Zowe CLI wait at least the specified number of seconds before attempting to collect additional solicited response messages. If additional messages are collected on "follow-up" requests, the timer is reset until an attempt is made that results in no additional response messages.
- `--follow-up-attempts` | `--fua` | `-a` (*number*)
 - Number of request attempts if no response returned.

Default value: 1

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.
Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)
Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Issue a z/OS console command to display the IPL information for the system:
 - `zowe zos-console issue command "D IPLINFO"`
- Issue a z/OS console command to display the local and coordinated universal time and date:
 - `zowe zos-console issue command "D T"`
- Issue a Db2 command to display information about the status and configuration of DDF:
 - `zowe zos-console issue command "\-DB1G DISPLAY DDF"`

zowe › zos-files

Manage z/OS data sets, create data sets, and more.

zowe › zos-files › copy

Copy a data set.

zowe › zos-files › copy › data-set

Copy a data set to another data set

Usage

```
zowe zos-files copy data-set <fromDataSetName> <toDataSetName> [options]
```

Positional Arguments

- `fromDataSetName` (*string*)
 - The name of the data set that you want to copy from
- `toDataSetName` (*string*)
 - The name of the data set that you want to copy to (data set must be preallocated)

Options

- `--replace` | `--rep` (*boolean*)
 - Specify this option as true if you wish to replace like-named members in the target dataset
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)

- The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.
 - Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
 - Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)
 - Default value: https
 - Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.

- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Copy the data set named 'USER.FROM.SET' to the data set named 'USER.TO.SET':
 - `zowe zos-files copy data-set "USER.FROM.SET" "USER.TO.SET"`
- Copy the data set member named 'USER.FROM.SET(MEM1)' to the data set member named 'USER.TO.SET(MEM2)':
 - `zowe zos-files copy data-set "USER.FROM.SET(mem1)" "USER.TO.SET(mem2)"`
- Copy the data set named 'USER.FROM.SET' to the data set member named 'USER.TO.SET(MEM2)':
 - `zowe zos-files copy data-set "USER.FROM.SET" "USER.TO.SET(mem2)"`
- Copy the data set member named 'USER.FROM.SET(MEM1)' to the data set named 'USER.TO.SET':
 - `zowe zos-files copy data-set "USER.FROM.SET(mem1)" "USER.TO.SET"`
- Copy the data set named 'USER.FROM.SET' to the data set named 'USER.TO.SET' and replace like-named members:
 - `zowe zos-files copy data-set "USER.FROM.SET" "USER.TO.SET" --replace`

[zowe](#) › [zos-files](#) › [create](#)

Create data sets.

[zowe](#) › [zos-files](#) › [create](#) › [data-set](#)

Create data sets based on the properties of an existing data set

Usage

```
zowe zos-files create data-set <dataSetName> [options]
```

Positional Arguments

- `dataSetName` (*string*)
 - The name of the data set that you want to create

Options

- `--attributes` | `-a` (*boolean*)
 - Show the full allocation attributes
- `--block-size` | `--bs` | `--blksize` (*number*)
 - The block size for the data set (for example, 6160)
- `--data-class` | `--dc` (*string*)
 - The SMS data class to use for the allocation
- `--data-set-type` | `--dst` | `--dsntype` (*string*)
 - The data set type (BASIC, EXTPREF, EXTREQ, HFS, LARGE, PDS, LIBRARY, PIPE)
- `--device-type` | `--dt` | `--unit` (*string*)
 - The device type, also known as 'unit'
- `--directory-blocks` | `--db` | `--dirblks` (*number*)
 - The number of directory blocks (for example, 25)
- `--like` | `--lk` (*string*)
 - Name of an existing data set to base your new data set's properties on
- `--management-class` | `--mc` (*string*)
 - The SMS management class to use for the allocation

- `--primary-space` | `--ps` (*number*)
 - The primary space allocation (for example, 5)
- `--record-format` | `--rf` | `--recfm` (*string*)
 - The record format for the data set (for example, FB for "Fixed Block")
- `--record-length` | `--r1` | `--lrec1` (*number*)
 - The logical record length. Analogous to the length of a line (for example, 80)
- `--secondary-space` | `--ss` (*number*)
 - The secondary space allocation (for example, 1)
- `--size` | `--sz` (*string*)
 - The size of the data set (specified as nCYL or nTRK - where n is the number of cylinders or tracks). Sets the primary allocation (the secondary allocation becomes ~10% of the primary).
- `--storage-class` | `--sc` (*string*)
 - The SMS storage class to use for the allocation
- `--volume-serial` | `--vs` | `--volser` (*string*)
 - The volume serial (VOLSER) on which you want the data set to be placed. A VOLSER is analogous to a drive name on a PC.
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443

- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Create a data set with default parameters and like flag:
 - `zowe zos-files create data-set NEW.DATASET --like EXISTING.DATASET`
- Create a data set with default parameters and like flag and lrecl flag:
 - `zowe zos-files create data-set NEW.DATASET --like EXISTING.DATASET --lrecl 1024`
- Create a data set with type LIBRARY:
 - `zowe zos-files create data-set NEW.DATASET --data-set-type LIBRARY`

[zowe](#) › [zos-files](#) › [create](#) › [data-set-binary](#)

Create executable data sets

Usage

```
zowe zos-files create data-set-binary <dataSetName> [options]
```

Positional Arguments

- `dataSetName` (*string*)
 - The name of the data set that you want to create

Options

- `--attributes` | `-a` (*boolean*)
 - Show the full allocation attributes
- `--block-size` | `--bs` | `--blksize` (*number*)

- The block size for the data set (for example, 6160)

Default value: 27998

- `--data-class` | `--dc` (*string*)

- The SMS data class to use for the allocation

- `--data-set-type` | `--dst` | `--dsntype` (*string*)

- The data set type (BASIC, EXTPREF, EXTREQ, HFS, LARGE, PDS, LIBRARY, PIPE)

- `--device-type` | `--dt` | `--unit` (*string*)

- The device type, also known as 'unit'

- `--directory-blocks` | `--db` | `--dirblks` (*number*)

- The number of directory blocks (for example, 25)

Default value: 25

- `--management-class` | `--mc` (*string*)

- The SMS management class to use for the allocation

- `--primary-space` | `--ps` (*number*)

- The primary space allocation (for example, 5)

Default value: 10

- `--record-format` | `--rf` | `--recfm` (*string*)

- The record format for the data set (for example, FB for "Fixed Block")

Default value: U

- `--record-length` | `--r1` | `--lrec1` (*number*)

- The logical record length. Analogous to the length of a line (for example, 80)

Default value: 27998

- `--secondary-space` | `--ss` (*number*)

- The secondary space allocation (for example, 1)

- `--size` | `--sz` (*string*)
 - The size of the data set (specified as nCYL or nTRK - where n is the number of cylinders or tracks). Sets the primary allocation (the secondary allocation becomes ~10% of the primary).
- `--storage-class` | `--sc` (*string*)
 - The SMS storage class to use for the allocation
- `--volume-serial` | `--vs` | `--volser` (*string*)
 - The volume serial (VOLSER) on which you want the data set to be placed. A VOLSER is analogous to a drive name on a PC.
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Create an empty binary partitioned data set (PDS) with default parameters:
 - `zowe zos-files create data-set-binary NEW.BINARY.DATASET`

- Create an empty binary PDSE using data set type LIBRARY:

- `zowe zos-files create data-set-binary NEW.BINARY.DATASET --data-set-type LIBRARY`

[zowe](#) › [zos-files](#) › [create](#) › [data-set-c](#)

Create data sets for C code programming

Usage

`zowe zos-files create data-set-c <dataSetName> [options]`

Positional Arguments

- `dataSetName` (*string*)
 - The name of the data set that you want to create

Options

- `--attributes` | `-a` (*boolean*)
 - Show the full allocation attributes
- `--block-size` | `--bs` | `--blksize` (*number*)
 - The block size for the data set (for example, 6160)
Default value: 32760
- `--data-class` | `--dc` (*string*)
 - The SMS data class to use for the allocation
- `--data-set-type` | `--dst` | `--dsntype` (*string*)
 - The data set type (BASIC, EXTPREF, EXTREQ, HFS, LARGE, PDS, LIBRARY, PIPE)
- `--device-type` | `--dt` | `--unit` (*string*)
 - The device type, also known as 'unit'
- `--directory-blocks` | `--db` | `--dirblks` (*number*)
 - The number of directory blocks (for example, 25)

Default value: 25

- `--management-class` | `--mc` (*string*)
 - The SMS management class to use for the allocation
- `--primary-space` | `--ps` (*number*)
 - The primary space allocation (for example, 5)

Default value: 1

- `--record-format` | `--rf` | `--recfm` (*string*)
 - The record format for the data set (for example, FB for "Fixed Block")

Default value: VB

- `--record-length` | `--rl` | `--lrecl` (*number*)
 - The logical record length. Analogous to the length of a line (for example, 80)

Default value: 260

- `--secondary-space` | `--ss` (*number*)
 - The secondary space allocation (for example, 1)
- `--size` | `--sz` (*string*)
 - The size of the data set (specified as nCYL or nTRK - where n is the number of cylinders or tracks). Sets the primary allocation (the secondary allocation becomes ~10% of the primary).
- `--storage-class` | `--sc` (*string*)
 - The SMS storage class to use for the allocation
- `--volume-serial` | `--vs` | `--volser` (*string*)
 - The volume serial (VOLSER) on which you want the data set to be placed. A VOLSER is analogous to a drive name on a PC.
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be

terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.
Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)
Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Create an empty C code PDS with default parameters:
 - `zowe zos-files create data-set-c NEW.CCODE.DATASET`
- Create an empty C code PDSE using data set type LIBRARY:
 - `zowe zos-files create data-set-c NEW.CCODE.DATASET --data-set-type LIBRARY`

[zowe](#) › [zos-files](#) › [create](#) › [data-set-classic](#)

Create classic data sets (JCL, HLASM, CBL, etc...)

Usage

```
zowe zos-files create data-set-classic <dataSetName> [options]
```

Positional Arguments

- `dataSetName` (*string*)
 - The name of the data set that you want to create

Options

- `--attributes` | `-a` (*boolean*)
 - Show the full allocation attributes
- `--block-size` | `--bs` | `--blksize` (*number*)
 - The block size for the data set (for example, 6160)
Default value: 6160
- `--data-class` | `--dc` (*string*)
 - The SMS data class to use for the allocation
- `--data-set-type` | `--dst` | `--dsntype` (*string*)
 - The data set type (BASIC, EXTPREF, EXTREQ, HFS, LARGE, PDS, LIBRARY, PIPE)
- `--device-type` | `--dt` | `--unit` (*string*)
 - The device type, also known as 'unit'
- `--directory-blocks` | `--db` | `--dirblks` (*number*)
 - The number of directory blocks (for example, 25)
Default value: 25
- `--management-class` | `--mc` (*string*)
 - The SMS management class to use for the allocation
- `--primary-space` | `--ps` (*number*)
 - The primary space allocation (for example, 5)
Default value: 1
- `--record-format` | `--rf` | `--recfm` (*string*)
 - The record format for the data set (for example, FB for "Fixed Block")
Default value: FB
- `--record-length` | `--r1` | `--lrec1` (*number*)
 - The logical record length. Analogous to the length of a line (for example, 80)

Default value: 80

- `--secondary-space` | `--ss` (*number*)
 - The secondary space allocation (for example, 1)
- `--size` | `--sz` (*string*)
 - The size of the data set (specified as nCYL or nTRK - where n is the number of cylinders or tracks). Sets the primary allocation (the secondary allocation becomes ~10% of the primary).
- `--storage-class` | `--sc` (*string*)
 - The SMS storage class to use for the allocation
- `--volume-serial` | `--vs` | `--volser` (*string*)
 - The volume serial (VOLSER) on which you want the data set to be placed. A VOLSER is analogous to a drive name on a PC.
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Create an empty z/OS 'classic' PDS with default parameters:
 - `zowe zos-files create data-set-classic NEW.CLASSIC.DATASET`
- Create an empty z/OS 'classic' PDSE using data set type LIBRARY:
 - `zowe zos-files create data-set-classic NEW.CLASSIC.DATASET --data-set-type LIBRARY`

[zowe](#) › [zos-files](#) › [create](#) › [data-set-partitioned](#)

Create partitioned data sets (PDS)

Usage

```
zowe zos-files create data-set-partitioned <dataSetName> [options]
```

Positional Arguments

- `dataSetName` (*string*)
 - The name of the data set that you want to create

Options

- `--attributes` | `-a` (*boolean*)
 - Show the full allocation attributes
- `--block-size` | `--bs` | `--blksize` (*number*)
 - The block size for the data set (for example, 6160)
Default value: 6160
- `--data-class` | `--dc` (*string*)
 - The SMS data class to use for the allocation
- `--data-set-type` | `--dst` | `--dsntype` (*string*)
 - The data set type (BASIC, EXTPREF, EXTREQ, HFS, LARGE, PDS, LIBRARY, PIPE)
- `--device-type` | `--dt` | `--unit` (*string*)

- The device type, also known as 'unit'
- `--directory-blocks` | `--db` | `--dirblks` (*number*)
 - The number of directory blocks (for example, 25)
 - Default value: 5
- `--management-class` | `--mc` (*string*)
 - The SMS management class to use for the allocation
- `--primary-space` | `--ps` (*number*)
 - The primary space allocation (for example, 5)
 - Default value: 1
- `--record-format` | `--rf` | `--recfm` (*string*)
 - The record format for the data set (for example, FB for "Fixed Block")
 - Default value: FB
- `--record-length` | `--r1` | `--lrec1` (*number*)
 - The logical record length. Analogous to the length of a line (for example, 80)
 - Default value: 80
- `--secondary-space` | `--ss` (*number*)
 - The secondary space allocation (for example, 1)
- `--size` | `--sz` (*string*)
 - The size of the data set (specified as nCYL or nTRK - where n is the number of cylinders or tracks). Sets the primary allocation (the secondary allocation becomes ~10% of the primary).
- `--storage-class` | `--sc` (*string*)
 - The SMS storage class to use for the allocation
- `--volume-serial` | `--vs` | `--volser` (*string*)
 - The volume serial (VOLSER) on which you want the data set to be placed. A VOLSER is analogous to a drive name on a PC.

- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)

- The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Create an empty PDS with default parameters:
 - `zowe zos-files create data-set-partitioned NEW.PDS.DATASET`
- Create an empty PDSE using data set type LIBRARY:
 - `zowe zos-files create data-set-partitioned NEW.PDSE.DATASET --data-set-type LIBRARY`

[zowe](#) › [zos-files](#) › [create](#) › [data-set-sequential](#)

Create physical sequential data sets (PS)

Usage

```
zowe zos-files create data-set-sequential <dataSetName> [options]
```

Positional Arguments

- `dataSetName` (*string*)
 - The name of the data set that you want to create

Options

- `--attributes` | `-a` (*boolean*)
 - Show the full allocation attributes
- `--block-size` | `--bs` | `--blksize` (*number*)
 - The block size for the data set (for example, 6160)

Default value: 6160
- `--data-class` | `--dc` (*string*)
 - The SMS data class to use for the allocation
- `--device-type` | `--dt` | `--unit` (*string*)
 - The device type, also known as 'unit'
- `--directory-blocks` | `--db` | `--dirblks` (*number*)
 - The number of directory blocks (for example, 25)
- `--management-class` | `--mc` (*string*)
 - The SMS management class to use for the allocation
- `--primary-space` | `--ps` (*number*)
 - The primary space allocation (for example, 5)

Default value: 1
- `--record-format` | `--rf` | `--recfm` (*string*)
 - The record format for the data set (for example, FB for "Fixed Block")

Default value: FB
- `--record-length` | `--r1` | `--lrec1` (*number*)
 - The logical record length. Analogous to the length of a line (for example, 80)

Default value: 80

- `--secondary-space` | `--ss` (*number*)
 - The secondary space allocation (for example, 1)
- `--size` | `--sz` (*string*)
 - The size of the data set (specified as nCYL or nTRK - where n is the number of cylinders or tracks). Sets the primary allocation (the secondary allocation becomes ~10% of the primary).
- `--storage-class` | `--sc` (*string*)
 - The SMS storage class to use for the allocation
- `--volume-serial` | `--vs` | `--volser` (*string*)
 - The volume serial (VOLSER) on which you want the data set to be placed. A VOLSER is analogous to a drive name on a PC.
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Create an empty physical sequential data set with default parameters:
 - `zowe zos-files create data-set-sequential NEW.PS.DATASET`

[zowe](#) › [zos-files](#) › [create](#) › [data-set-vsam](#)

Create a VSAM cluster

Usage

`zowe zos-files create data-set-vsam <dataSetName> [options]`

Positional Arguments

- `dataSetName` (*string*)
 - The name of the dataset in which to create a VSAM cluster

Options

- `--attributes` | `-a` (*boolean*)
 - Show the full allocation attributes
- `--data-class` | `--dc` (*string*)
 - The SMS data class to use for the allocation
- `--data-set-organization` | `--dso` | `--dsorg` (*string*)
 - The data set organization.

Default value: INDEXED
Allowed values: INDEXED, IXD, LINEAR, LIN, NONINDEXED, NIXD, NUMBERED, NUMD, ZFS
- `--management-class` | `--mc` (*string*)
 - The SMS management class to use for the allocation
- `--retain-for` | `--rf` (*number*)
 - The number of days that the VSAM cluster will be retained on the system. You can delete the cluster at any time when neither retain-for nor retain-to is specified.

- `--retain-to` | `--rt` (*string*)
 - The earliest date that a command without the PURGE parameter can delete an entry. Specify the expiration date in the form yyyyddd, where yyyy is a four-digit year (maximum value: 2155) and ddd is the three-digit day of the year from 001 through 365 (for non-leap years) or 366 (for leap years). You can delete the cluster at any time when neither retain-for nor retain-to is used. You cannot specify both the 'retain-to' and 'retain-for' options.
- `--secondary-space` | `--ss` (*number*)
 - The number of items for the secondary space allocation (for example, 840). The type of item allocated is the same as the type used for the '--size' option. If you do not specify a secondary allocation, a value of ~10% of the primary allocation is used.
- `--size` | `--sz` (*string*)
 - The primary size to allocate for the VSAM cluster. Specify size as the number of items to allocate (nitems). You specify the type of item by keyword.

Default value: 840KB
- `--storage-class` | `--sc` (*string*)
 - The SMS storage class to use for the allocation
- `--volumes` | `-v` (*string*)
 - The storage volumes on which to allocate a VSAM cluster. Specify a single volume by its volume serial (VOLSER). To specify more than one volume, enclose the option in double-quotes and separate each VOLSER with a space. You must specify the volumes option when your cluster is not SMS-managed.
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)

- The z/OSMF server port.

Default value: 443

- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https

- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Create a VSAM data set named "[SOME.DATA.SET.NAME](#)" using default values of INDEXED, 840 KB primary storage and 84 KB secondary storage:
 - `zowe zos-files create data-set-vsam SOME.DATA.SET.NAME`
- Create a 5 MB LINEAR VSAM data set named "[SOME.DATA.SET.NAME](#)" with 1 MB of secondary space. Show the properties of the data set when it is created:
 - `zowe zos-files create data-set-vsam SOME.DATA.SET.NAME --data-set-organization LINEAR --size 5MB --secondary-space 1 --attributes`
- Create a VSAM data set named "[SOME.DATA.SET.NAME](#)", which is retained for 100 days:
 - `zowe zos-files create data-set-vsam SOME.DATA.SET.NAME --retain-for 100`

[zowe](#) › [zos-files](#) › [create](#) › [uss-directory](#)

Create a UNIX directory.

Usage

```
zowe zos-files create uss-directory <ussPath> [options]
```

Positional Arguments

- `ussPath` (*string*)
 - The name of the directory that you want to create.

Options

- `--mode` | `-m` (*string*)
 - Specifies the file permission bits to use when creating the directory.

- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)

- The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Create a USS directory named "testDir" :
 - `zowe zos-files create uss-directory testDir`
- Create a USS directory named "testDir" with mode "rwxrwxrwx" :
 - `zowe zos-files create uss-directory testDir -m rwxrwxrwx`

[zowe](#) › [zos-files](#) › [create](#) › [uss-file](#)

Create a UNIX file.

Usage

```
zowe zos-files create uss-file <ussPath> [options]
```

Positional Arguments

- `ussPath` (*string*)
 - The name of the file that you want to create.

Options

- `--mode` | `-m` (*string*)
 - Specifies the file permission bits to use when creating the file.
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.
Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.

- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)
 - Default value: https
 - Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Create a USS file named "test.ext" :
 - `zowe zos-files create uss-file text.txt`
- Create a USS file named "text.txt" with mode "rwxrwxrwx" :
 - `zowe zos-files create uss-file text.txt -m rwxrwxrwx`

Create a z/OS file system.

Usage

```
zowe zos-files create zos-file-system <fileSystemName> [options]
```

Positional Arguments

- `fileSystemName` (*string*)
 - The name of the file system to create.

Options

- `--cyls-pri` | `--cp` (*number*)
 - The number of primary cylinders to allocate for the ZFS.
Default value: 10
- `--cyls-sec` | `--cs` (*number*)
 - The number of secondary cylinders to allocate for the ZFS.
Default value: 2
- `--data-class` | `--dc` (*string*)
 - The SMS data class to use for the allocation
- `--group` | `-g` (*string*)
 - The z/OS group ID or GID for the group of the ZFS root directory.
- `--management-class` | `--mc` (*string*)
 - The SMS management class to use for the allocation
- `--owner` | `-o` (*string*)
 - The z/OS user ID or UID for the owner of the ZFS root directory.
- `--perms` | `-p` (*number*)
 - The permissions code for the ZFS root directory.
Default value: 755

- `--storage-class` | `--sc` (*string*)
 - The SMS storage class to use for the allocation
- `--timeout` | `-t` (*number*)
 - The number of seconds to wait for the underlying "zfsadm format" command to complete. If this command times out, the ZFS may have been created but not formatted correctly.

Default value: 20
- `--volumes` | `-v` (*array*)
 - The storage volumes on which to allocate the z/OS file system. Specify a single volume by its volume serial (VOLSER). To specify more than one volume, separate each VOLSER with a space. You must specify the volumes option when your cluster is not SMS-managed.
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Create a ZFS named "HLQ.MYNEW.ZFS" using default values of 755 permissions, 10 primary and 2 secondary cylinders allocated, and a timeout of 20 seconds:
 - `zowe zos-files create zos-file-system HLQ.MYNEW.ZFS`
- Create a ZFS with 100 primary and 10 secondary cylinders allocated:
 - `zowe zos-files create zos-file-system HLQ.MYNEW.ZFS --cp 100 --cs 10`
- Create a ZFS specifying the volumes that should be used:
 - `zowe zos-files create zos-file-system HLQ.MYNEW.ZFS -v ZFS001 ZFS002`

[zowe](#) › [zos-files](#) › [delete](#)

Delete a data set or Unix System Services file.

[zowe](#) › [zos-files](#) › [delete](#) › [data-set](#)

Delete a data set or data set member permanently

Usage

```
zowe zos-files delete data-set <dataSetName> [options]
```

Positional Arguments

- `dataSetName` (*string*)
 - The name of the data set that you want to delete

Required Options

- `--for-sure` | `-f` (*boolean*)
 - Specify this option to confirm that you want to delete the data set permanently.

Options

- `--volume` | `--vol` (*string*)
 - The volume serial (VOLSER) where the data set resides. The option is required only when the data set is not catalogued on the system.
- `--response-timeout` | `--rto` (*number*)

- The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.
Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)
Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication

- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Delete the data set named 'ibmuser.cntl':
 - `zowe zos-files delete data-set "ibmuser.cntl" -f`
- Delete the data set member named 'ibmuser.cntl(mem)':
 - `zowe zos-files delete data-set "ibmuser.cntl(mem)" -f`

[zowe](#) › [zos-files](#) › [delete](#) › [data-set-vsam](#)

Delete a VSAM cluster permanently

Usage

```
zowe zos-files delete data-set-vsam <dataSetName> [options]
```

Positional Arguments

- `dataSetName` (*string*)

- The name of the VSAM cluster that you want to delete

Options

- `--erase` | `-e` (*boolean*)
 - Specify this option to overwrite the data component for the cluster with binary zeros. This option is ignored if the NOERASE attribute was specified when the cluster was defined or altered.

Default value: false
- `--purge` | `-p` (*boolean*)
 - Specify this option to delete the VSAM cluster regardless of its retention period or date.

Default value: false
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Required Options

- `--for-sure` | `-f` (*boolean*)
 - Specify this option to confirm that you want to delete the VSAM cluster permanently.

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)

- Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
 - Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)
 - Default value: https
 - Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)

- The value of the token to pass to the API.

Examples

- Delete the VSAM data set named 'ibmuser.cntl.vsam':
 - `zowe zos-files delete data-set-vsam "ibmuser.cntl.vsam" -f`
- Delete all expired VSAM data sets that match 'ibmuser.AAA.**.FFF':
 - `zowe zos-files delete data-set-vsam "ibmuser.AAA.**.FFF" -f`
- Delete a non-expired VSAM data set named 'ibmuser.cntl.vsam':
 - `zowe zos-files delete data-set-vsam "ibmuser.cntl.vsam" -f --purge`
- Delete an expired VSAM data set named 'ibmuser.cntl.vsam' by overwriting the components with zeros:
 - `zowe zos-files delete data-set-vsam "ibmuser.cntl.vsam" -f --erase`

[zowe](#) › [zos-files](#) › [delete](#) › [migrated-data-set](#)

Delete migrated data sets.

Usage

```
zowe zos-files delete migrated-data-set <dataSetName> [options]
```

Positional Arguments

- `dataSetName` (*string*)
 - The name of the migrated data set you want to delete.

Options

- `--wait` | `-w` (*boolean*)
 - If true then the function waits for completion of the request. If false (default) the request is queued.

Default value: false
- `--purge` | `-p` (*boolean*)

- If true then the function uses the PURGE=YES on ARCHDEL request. If false (default) the function uses the PURGE=NO on ARCHDEL request.

Default value: false

- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Delete a migrated data set using default options:
 - `zowe zos-files delete migrated-data-set "USER.DATA.SET"`

[zowe](#) › [zos-files](#) › [delete](#) › [uss-file](#)

Delete a Unix Systems Services (USS) File or directory permanently

Usage

```
zowe zos-files delete uss-file <fileName> [options]
```

Positional Arguments

- `fileName` (*string*)
 - The name of the file or directory that you want to delete

Required Options

- `--for-sure` | `-f` (*boolean*)
 - Specify this option to confirm that you want to delete the file or directory permanently.

Options

- `--recursive` | `-r` (*boolean*)
 - Delete directories recursively.
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Delete the empty directory '/u/ibmuser/testcases':
 - `zowe zos-files delete uss-file "/a/ibmuser/testcases" -f`

- Delete the file named '/a/ibmuser/my_text.txt':
 - `zowe zos-files delete uss-file "/a/ibmuser/testcases/my_text.txt" -f`
- Recursively delete the directory named '/u/ibmuser/testcases':
 - `zowe zos-files delete uss-file "/a/ibmuser/testcases" -rf`

[zowe](#) › [zos-files](#) › [delete](#) › [zos-file-system](#)

Delete a z/OS file system permanently.

Usage

```
zowe zos-files delete zos-file-system <fileSystemName> [options]
```

Positional Arguments

- `fileSystemName` (*string*)
 - The name of the z/OS file system that you want to delete.

Required Options

- `--for-sure` | `-f` (*boolean*)
 - Specify this option to confirm that you want to delete the ZFS permanently.

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.
 - Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Options

- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Delete the z/OS file system 'HLQ.MYNEW.ZFS':
 - `zowe zos-files delete zos-file-system "HLQ.MYNEW.ZFS" -f`

[zowe](#) › [zos-files](#) › [download](#)

Download content from z/OS data sets and USS files to your PC.

[zowe](#) › [zos-files](#) › [download](#) › [all-members](#)

Download all members from a partitioned data set to a local folder

Usage

```
zowe zos-files download all-members <dataSetName> [options]
```

Positional Arguments

- `dataSetName` (*string*)
 - The name of the data set from which you want to download members

Options

- `--binary` | `-b` (*boolean*)
 - Download the file content in binary mode, which means that no data conversion is performed. The data transfer process returns each line as-is, without translation. No delimiters are added between records.
- `--directory` | `-d` (*string*)
 - The directory to where you want to save the members. The command creates the directory for you when it does not already exist. By default, the command creates a folder

structure based on the data set qualifiers. For example, the data set `ibmuser.new.cntl`'s members are downloaded to `ibmuser/new/cntl`).

- `--encoding` | `--ec` (*string*)
 - Download the file content with encoding mode, which means that data conversion is performed using the file encoding specified.
- `--extension` | `-e` (*string*)
 - Save the local files with a specified file extension. For example, `.txt`. Or `""` for no extension. When no extension is specified, `.txt` is used as the default file extension.
- `--fail-fast` | `--ff` (*boolean*)
 - Set this option to false to continue downloading dataset members if one or more fail.

Default value: true
- `--max-concurrent-requests` | `--mcr` (*number*)
 - Specifies the maximum number of concurrent z/OSMF REST API requests to download members. Increasing the value results in faster downloads. However, increasing the value increases resource consumption on z/OS and can be prone to errors caused by making too many concurrent requests. If the download process encounters an error, the following message displays:
The maximum number of TSO address spaces have been created. When you specify 0, Zowe CLI attempts to download all members at once without a maximum number of concurrent requests.

Default value: 1
- `--preserve-original-letter-case` | `--po` (*boolean*)
 - Specifies if the automatically generated directories and files use the original letter case

Default value: false
- `--record` | `-r` (*boolean*)
 - Download the file content in record mode, which means that no data conversion is performed and the record length is prepended to the data. The data transfer process returns each line as-is, without translation. No delimiters are added between records. Conflicts with binary.
- `--volume-serial` | `--vs` (*string*)

- The volume serial (VOLSER) where the data set resides. You can use this option at any time. However, the VOLSER is required only when the data set is not cataloged on the system. A VOLSER is analogous to a drive name on a PC.
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Download the members of the data set "ibmuser.loadlib" in binary mode to the directory "loadlib":
 - `zowe zos-files download all-members "ibmuser.loadlib" -b -d loadlib`
- Download the members of the data set "ibmuser.cntl" in text mode to the directory "jcl":
 - `zowe zos-files download all-members "ibmuser.cntl" -d jcl`

[zowe](#) › [zos-files](#) › [download](#) › [data-set](#)

Download content from a z/OS data set to a local file

Usage

zowe zos-files download data-set <dataSetName> [options]

Positional Arguments

- `dataSetName` (*string*)
 - The name of the data set that you want to download

Options

- `--binary` | `-b` (*boolean*)
 - Download the file content in binary mode, which means that no data conversion is performed. The data transfer process returns each line as-is, without translation. No delimiters are added between records.
- `--encoding` | `--ec` (*string*)
 - Download the file content with encoding mode, which means that data conversion is performed using the file encoding specified.
- `--extension` | `-e` (*string*)
 - Save the local files with a specified file extension. For example, .txt. Or "" for no extension. When no extension is specified, .txt is used as the default file extension.
- `--file` | `-f` (*string*)
 - The path to the local file where you want to download the content. When you omit the option, the command generates a file name automatically for you.
- `--preserve-original-letter-case` | `--po` (*boolean*)
 - Specifies if the automatically generated directories and files use the original letter case

Default value: false
- `--record` | `-r` (*boolean*)
 - Download the file content in record mode, which means that no data conversion is performed and the record length is prepended to the data. The data transfer process returns each line as-is, without translation. No delimiters are added between records. Conflicts with binary.
- `--volume-serial` | `--vs` (*string*)

- The volume serial (VOLSER) where the data set resides. You can use this option at any time. However, the VOLSER is required only when the data set is not cataloged on the system. A VOLSER is analogous to a drive name on a PC.
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Download the data set "ibmuser.loadlib(main)" in binary mode to the local file "main.obj":
 - `zowe zos-files download data-set "ibmuser.loadlib(main)" -b -f main.obj`

[zowe](#) › [zos-files](#) › [download](#) › [uss-file](#)

Download content from a USS file to a local file on your PC

Usage

```
zowe zos-files download uss-file <ussFileName> [options]
```

Positional Arguments

- `ussFileName` (*string*)
 - The name of the USS file you want to download

Options

- `--binary` | `-b` (*boolean*)
 - Download the file content in binary mode, which means that no data conversion is performed. The data transfer process returns each line as-is, without translation. No delimiters are added between records.
- `--encoding` | `--ec` (*string*)
 - Download the file content with encoding mode, which means that data conversion is performed using the file encoding specified.
- `--file` | `-f` (*string*)
 - The path to the local file where you want to download the content. When you omit the option, the command generates a file name automatically for you.
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Download the file `"/a/ibmuser/my_text.txt"` to `./my_text.txt`:
 - `zowe zos-files download uss-file "/a/ibmuser/my_text.txt" -f ./my_text.txt`
- Download the file `"/a/ibmuser/MyJava.class"` to `"java/MyJava.class"` in binary mode:
 - `zowe zos-files download uss-file "/a/ibmuser/MyJava.class" -b -f "java/MyJava.class"`

[zowe](#) › [zos-files](#) › [invoke](#)

Invoke z/OS utilities such as Access Method Services (AMS).

[zowe](#) › [zos-files](#) › [invoke](#) › [ams-file](#)

Submit control statements for execution by Access Method Services (IDCAMS). You can use IDCAMS to create VSAM data sets (CSI, ZFS, etc...), delete data sets, and more. You must format the control statements exactly as the IDCAMS utility expects. For more information about control statements, see the IBM publication 'z/OS DFSMS Access Method Services Commands'.

Usage

```
zowe zos-files invoke ams-file <controlStatementsFile> [options]
```

Positional Arguments

- `controlStatementsFile` (*string*)
 - The path to a file that contains IDCAMS control statements. Ensure that your file does not contain statements that are longer than 255 characters (maximum allowed length).

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443

- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Options

- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)

- The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Reads the specified file and submits the controls statements:
 - `zowe zos-files invoke ams-file "./path/to/file/MyControlStatements.idcams"`

[zowe](#) › [zos-files](#) › [invoke](#) › [ams-statements](#)

Submit control statements for execution by Access Method Services (IDCAMS). You can use IDCAMS to create VSAM data sets (CSI, ZFS, etc...), delete data sets, and more. You must format the control statements exactly as the IDCAMS utility expects. For more information about control statements, see the IBM publication 'z/OS DFSMS Access Method Services Commands'.

Usage

```
zowe zos-files invoke ams-statements <controlStatements> [options]
```

Positional Arguments

- `controlStatements` (*string*)
 - The IDCAMS control statement that you want to submit. Zowe CLI attempts to split the inline control statement at 255 characters.

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.

- `--port` | `-P` (*number*)
 - The z/OSMF server port.
 - Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
 - Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)
 - Default value: https
 - Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Options

- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be

terminated and return an error. Allowed values: 5 - 600

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Defines a cluster named 'DUMMY.VSAM.CLUSTER':
 - `zowe zos-files invoke ams-statements "DEFINE CLUSTER (NAME (DUMMY.VSAM.CLUSTER) CYL(1 1))"`
- Deletes a cluster named 'DUMMY.VSAM.CLUSTER':
 - `zowe zos-files invoke ams-statements "DELETE DUMMY.VSAM.CLUSTER CLUSTER"`

[zowe](#) › [zos-files](#) › [list](#)

List data sets and data set members. Optionally, you can list their details and attributes.

[zowe](#) › [zos-files](#) › [list](#) › [all-members](#)

List all members of a partitioned data set. To view additional information about each member, use the `--attributes` option under the Options section of this help text.

Usage

zowe zos-files list all-members <dataSetName> [options]

Positional Arguments

- `dataSetName` (*string*)
 - The name of the data set for which you want to list the members

Options

- `--attributes` | `-a` (*boolean*)
 - Display more information about each member. Data sets with an undefined record format display information related to executable modules. Variable and fixed block data sets display information about when the members were created and modified.
- `--max-length` | `--max` (*number*)
 - The option `--max-length` specifies the maximum number of items to return. Skip this parameter to return all items. If you specify an incorrect value, the parameter returns up to 1000 items.
- `--pattern` (*string*)
 - The option `--pattern` specifies the match pattern used when listing members in a data set. The default is to match against all members, e.g. "*".
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443

- `--user` | `-u` (*string*)

- Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)

- The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Show members of the data set "ibmuser.asm":
 - `zowe zos-files list all-members "ibmuser.asm"`
- Show attributes of members of the data set "ibmuser.cntl":
 - `zowe zos-files list all-members "ibmuser.cntl" -a`
- Show the first 5 members of the data set "ibmuser.cntl":
 - `zowe zos-files list all-members "ibmuser.cntl" --max 5`
- Show the first 4 members of the data set "ibmuser.cntl" matching an input pattern":
 - `zowe zos-files list all-members "sys1.maclib" --pattern IJK* --max 4`

[zowe](#) › [zos-files](#) › [list](#) › [data-set](#)

List data sets that match a pattern in the data set name

Usage

```
zowe zos-files list data-set <dataSetName> [options]
```

Positional Arguments

- `dataSetName` (*string*)
 - The name or pattern of the data set that you want to list

Options

- `--attributes` | `-a` (*boolean*)
 - Display more information about each member. Data sets with an undefined record format display information related to executable modules. Variable and fixed block data sets display information about when the members were created and modified.

- `--max-length` | `--max` (*number*)
 - The option `--max-length` specifies the maximum number of items to return. Skip this parameter to return all items. If you specify an incorrect value, the parameter returns up to 1000 items.
- `--volume-serial` | `--vs` (*string*)
 - The volume serial (VOLSER) where the data set resides. You can use this option at any time. However, the VOLSER is required only when the data set is not cataloged on the system. A VOLSER is analogous to a drive name on a PC.
- `--start` | `-s` (*string*)
 - An optional search parameter that specifies the first data set name to return in the response document.
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Show the data set "ibmuser.asm":

- `zowe zos-files list data-set "ibmuser.asm"`
- Show attributes of the data set "ibmuser.cntl":
 - `zowe zos-files list data-set "ibmuser.cntl" -a`
- Show all data sets of the user "ibmuser":
 - `zowe zos-files list data-set "ibmuser.*"`
- Show attributes of all data sets of the user "ibmuser":
 - `zowe zos-files list data-set "ibmuser.*" -a`
- Show the first 5 data sets of the user "ibmuser":
 - `zowe zos-files list data-set "ibmuser.cntl" --max 5`

[zowe](#) › [zos-files](#) › [list](#) › [file-system](#)

List all mounted filesystems, or the specific filesystem mounted at a given path, or the filesystem with a given filesystem name.

Usage

```
zowe zos-files list file-system [options]
```

Options

- `--max-length` | `--max` (*number*)
 - The option `--max-length` specifies the maximum number of items to return. Skip this parameter to return all items. If you specify an incorrect value, the parameter returns up to 1000 items.
- `--fsname` | `-f` (*string*)
 - Specifies the name of the mounted file system. This option and `--path` are mutually exclusive.
- `--path` | `-p` (*string*)
 - Specifies the path where the file system is mounted. This option and `--fsname` are mutually exclusive.
- `--response-timeout` | `--rto` (*number*)

- The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.
Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)
Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication

- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Response Format Options

- `--response-format-filter` | `--rff` (*array*)
 - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '--response-format-type' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
 - The command response output format type. Must be one of the following:
 - table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.
 - list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.

object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string

- `--response-format-header` | `--rfh` (*boolean*)
 - If "`--response-format-type table`" is specified, include the column headers in the output.

Examples

- To list all mounted filesystems:
 - `zowe zos-files list file-system`
- To list filesystems mounted to a specific path:
 - `zowe zos-files list file-system -p /a/ibmuser`
- To list filesystems mounted with a specific name:
 - `zowe zos-files list file-system -f MY.ZFS`

[zowe](#) › [zos-files](#) › [list](#) › [uss-files](#)

List USS files and directories in a UNIX file path

Usage

```
zowe zos-files list uss-files <path> [options]
```

Positional Arguments

- `path` (*string*)
 - The directory containing the files and directories to be listed

Options

- `--max-length` | `--max` (*number*)
 - The option `--max-length` specifies the maximum number of items to return. Skip this parameter to return all items. If you specify an incorrect value, the parameter returns up to 1000 items.

- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)

- The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Response Format Options

- `--response-format-filter` | `--rff` (*array*)
 - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '--response-format-type' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
 - The command response output format type. Must be one of the following:
 - table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.
 - list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.

object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string

- `--response-format-header` | `--rfh` (*boolean*)
 - If "`--response-format-type table`" is specified, include the column headers in the output.

Examples

- Show the files and directories in path '/u/ibmuser':
 - `zowe zos-files list uss-files "/u/ibmuser"`
- Show the files and directories in path '/u/ibmuser' displaying only the file or directory name:
 - `zowe zos-files list uss-files "/u/ibmuser" --rff name`
- Show the files and directories in path '/u/ibmuser' displaying the headers associated with the file detail:
 - `zowe zos-files list uss-files "/u/ibmuser" --rfh`

zowe › zos-files › migrate

Migrate data sets.

zowe › zos-files › migrate › data-set

Migrate a data set.

Usage

```
zowe zos-files migrate data-set <dataSetName> [options]
```

Positional Arguments

- `dataSetName` (*string*)
 - The name of the data set you want to migrate.

Options

- `--wait` | `-w` (*boolean*)
 - If true then the function waits for completion of the request. If false (default) the request is queued.

Default value: false
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)

- The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Migrate a data set using default options:
 - `zowe zos-files migrate data-set "USER.DATA.SET"`

[zowe](#) › [zos-files](#) › [mount](#)

Mount z/OS UNIX file systems, such as HFS, ZFS, and more. This connects you to USS file systems.

[zowe](#) › [zos-files](#) › [mount](#) › [file-system](#)

Mount a UNIX file system on a specified directory.

Usage

```
zowe zos-files mount file-system <fileSystemName> <mountPoint> [options]
```

Positional Arguments

- `fileSystemName` (*string*)
 - The name of the file system to mount.
- `mountPoint` (*string*)
 - The directory to use as a mount point.

Options

- `--fs-type` | `--ft` (*string*)
 - Specify the file system type that you are going to mount. The name must match the TYPE operand on a FILESYSTYPE statement in the BPXPRMxx parmlib member for the file system.

Default value: ZFS
- `--mode` | `-m` (*string*)
 - Specify the mode for mounting the file system (rdonly - read-only, rdwr - read/write).

Default value: rdonly
Allowed values: rdonly, rdwr
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)

- The z/OSMF server port.

Default value: 443

- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https

- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Mount a z/OS file system using default options:
 - `zowe zos-files mount file-system MY.ZFS /a/ibmuser/mountdir`
- Mount a hierarchical file system with write access:
 - `zowe zos-files mount file-system MY.HFS /a/ibmuser/mountdir --ft HFS -m rdwr`

[zowe](#) › [zos-files](#) › [recall](#)

Recall migrated data sets.

[zowe](#) › [zos-files](#) › [recall](#) › [data-set](#)

Recall a migrated data set.

Usage

```
zowe zos-files recall data-set <dataSetName> [options]
```

Positional Arguments

- `dataSetName` (*string*)
 - The name of the data set you want to recall.

Options

- `--wait` | `-w` (*boolean*)
 - If true then the function waits for completion of the request. If false (default) the request is queued.

Default value: false

- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.

- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443

- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.

- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.

- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Recall a data set using default options:
 - `zowe zos-files recall data-set "USER.DATA.SET"`

[zowe](#) › [zos-files](#) › [rename](#)

Rename a data set or member.

[zowe](#) › [zos-files](#) › [rename](#) › [data-set](#)

Rename a data set.

Usage

`zowe zos-files rename data-set <beforeDataSetName> <afterDataSetName> [options]`

Positional Arguments

- `beforeDataSetName` (*string*)
 - The name of the data set that you want to rename.
- `afterDataSetName` (*string*)
 - The name you want to rename the data set to.

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.
Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.
Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)
Default value: https
Allowed values: http, https

- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Options

- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Rename the data set named 'USER.BEFORE.SET' to 'USER.AFTER.SET':
 - `zowe zos-files rename data-set "USER.BEFORE.SET" "USER.AFTER.SET"`

[zowe](#) › [zos-files](#) › [rename](#) › [data-set-member](#)

Rename a data set member.

Usage

```
zowe zos-files rename data-set-member <dataSetName> <beforeMemberName>  
<afterMemberName> [options]
```

Positional Arguments

- `dataSetName` (*string*)
 - The name of the data set the member belongs to.
- `beforeMemberName` (*string*)
 - The name of the data set member that you want to rename.
- `afterMemberName` (*string*)
 - The name you want to rename the data set member to.

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)

- The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Options

- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- In the data set 'USER.DATA.SET', rename the member named 'MEM1' to 'MEM2':
 - `zowe zos-files rename data-set-member "USER.DATA.SET" "MEM1" "MEM2"`

zowe › zos-files › unmount

Unmount file systems, such as HFS, ZFS, and more. This disconnects you from USS file systems.

zowe › zos-files › unmount › file-system

Unmount a UNIX file system.

Usage

```
zowe zos-files unmount file-system <fileSystemName> [options]
```

Positional Arguments

- `fileSystemName` (*string*)
 - The name of the file system to unmount.

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.
Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)

- Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Options

- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)

- The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Unmount a mounted file system:
 - `zowe zos-files unmount file-system MY.FS`

zowe › zos-files › upload

Upload the contents of a file to data sets.

zowe › zos-files › upload › dir-to-pds

Upload files from a local directory to a partitioned data set (PDS)

Usage

```
zowe zos-files upload dir-to-pds <inputdir> <dataSetName> [options]
```

Positional Arguments

- `inputdir` (*string*)
 - The path for a local directory that you want to upload to a PDS
- `dataSetName` (*string*)
 - The name of the partitioned data set to which you want to upload the files

Options

- `--binary` | `-b` (*boolean*)
 - Data content in binary mode, which means that no data conversion is performed. The data transfer process returns each record as-is, without translation. No delimiters are added between records.
- `--encoding` | `--ec` (*string*)

- Data content in encoding mode, which means that data conversion is performed according to the encoding specified.
- `--migrated-recall` | `--mr` (*string*)
 - The method by which migrated data set is handled. By default, a migrated data set is recalled synchronously. You can specify the following values: wait, nowait, error
 - Default value: nowait
- `--record` | `-r` (*boolean*)
 - Data content in record mode, which means that no data conversion is performed and the record length is prepended to the data. The data transfer process returns each line as-is, without translation. No delimiters are added between records. Conflicts with binary.
- `--volume-serial` | `--vs` (*string*)
 - The volume serial (VOLSER) where the data set resides. You can use this option at any time. However, the VOLSER is required only when the data set is not cataloged on the system. A VOLSER is analogous to a drive name on a PC.
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.
 - Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Upload a directory named "src" to a PDS named "ibmuser.src":
 - `zowe zos-files upload dir-to-pds "src" "ibmuser.src"`
- Upload a directory named "src" to a migrated PDS named "ibmuser.src" and wait for it to be recalled:
 - `zowe zos-files upload dir-to-pds "src" "ibmuser.src" --mr wait`

zowe › zos-files › upload › dir-to-uss

Upload a local directory to a USS directory.

An optional `.zosattributes` file in the source directory can be used to control file conversion and tagging.

An example `.zosattributes` file:

```
# pattern local-encoding remote-encoding
# Don't upload the node_modules directory
.* -
*.jpg binary binary
# Convert CICS Node.js profiles to EBCDIC
*.profile ISO8859-1 EBCDIC
```

Lines starting with the '#' character are comments. Each line can specify up to three positional attributes:

- A pattern to match a set of files. Pattern-matching syntax follows the same rules as those that apply in `.gitignore` files (note that negated patterns that begin with '!' are not supported). See https://git-scm.com/docs/gitignore#_pattern_format.
- A local-encoding to identify a file's encoding on the local workstation. If '-' is specified for local-encoding, files that match the pattern are not transferred.
- A remote-encoding to specify the file's desired character set on USS. This attribute must either match the local encoding or be set to EBCDIC. If set to EBCDIC, files are transferred in text mode and converted, otherwise they are transferred in binary mode. Remote files are tagged either with the remote encoding or as binary.

Due to a z/OSMF limitation, files that are transferred in text mode are converted to the default EBCDIC code page on the z/OS system. Therefore the only EBCDIC code page to specify as the remote encoding is the default code page for your system.

A .zosattributes file can either be placed in the top-level directory you want to upload, or its location can be specified by using the --attributes parameter. .zosattributes files that are placed in nested directories are ignored.

Usage

```
zowe zos-files upload dir-to-uss <inputDir> <USSDir> [options]
```

Positional Arguments

- `inputDir` (*string*)
 - The local directory path that you want to upload to a USS directory
- `USSDir` (*string*)
 - The name of the USS directory to which you want to upload the local directory

Options

- `--binary` | `-b` (*boolean*)
 - Data content in binary mode, which means that no data conversion is performed. The data transfer process returns each record as-is, without translation. No delimiters are added between records.
- `--recursive` | `-r` (*boolean*)
 - Upload all directories recursively.
- `--binary-files` | `--bf` (*string*)
 - Comma separated list of file names to be uploaded in binary mode. Use this option when you upload a directory in default ASCII mode, but you want to specify certain files to be uploaded in binary mode. All files matching specified file names will be uploaded in binary mode. If a .zosattributes file (or equivalent file specified via --attributes) is present, --binary-files will be ignored.
- `--ascii-files` | `--af` (*string*)
 - Comma separated list of file names to be uploaded in ASCII mode. Use this option when you upload a directory with --binary/-b flag, but you want to specify certain files to be uploaded in ASCII mode. All files matching specified file names will be uploaded in ASCII mode. If a .zosattributes file (or equivalent file specified via --attributes) is present, --ascii-files will be ignored.

- `--attributes` | `--attrs` (*string*)
 - Path of an attributes file to control how files are uploaded
- `--max-concurrent-requests` | `--mcr` (*number*)
 - Specifies the maximum number of concurrent z/OSMF REST API requests to upload files. Increasing the value results in faster uploads. However, increasing the value increases resource consumption on z/OS and can be prone to errors caused by making too many concurrent requests. If the upload process encounters an error, the following message displays:
The maximum number of TSO address spaces have been created. When you specify 0, Zowe CLI attempts to upload all members at once without a maximum number of concurrent requests.

Default value: 1
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Upload all files from the "local_dir" directory to the "/a/ibmuser/my_dir" USS directory:"

- `zowe zos-files upload dir-to-uss "local_dir" "/a/ibmuser/my_dir"`
- Upload all files from the "local_dir" directory and all its sub-directories, to the "/a/ibmuser/my_dir" USS directory::
 - `zowe zos-files upload dir-to-uss "local_dir" "/a/ibmuser/my_dir" --recursive`
- Upload all files from the "local_dir" directory to the "/a/ibmuser/my_dir" USS directory in default ASCII mode, while specifying a list of file names (without path) to be uploaded in binary mode::
 - `zowe zos-files upload dir-to-uss "local_dir" "/a/ibmuser/my_dir" --binary-files "myFile1.exe,myFile2.exe,myFile3.exe"`
- Upload all files from the "local_dir" directory to the "/a/ibmuser/my_dir" USS directory in binary mode, while specifying a list of file names (without path) to be uploaded in ASCII mode::
 - `zowe zos-files upload dir-to-uss "local_dir" "/a/ibmuser/my_dir" --binary --ascii-files "myFile1.txt,myFile2.txt,myFile3.txt"`
- Recursively upload all files from the "local_dir" directory to the "/a/ibmuser/my_dir" USS directory, specifying files to ignore and file encodings in the local file my_global_attributes::
 - `zowe zos-files upload dir-to-uss "local_dir" "/a/ibmuser/my_dir" --recursive --attributes my_global_attributes`

[zowe](#) › [zos-files](#) › [upload](#) › [file-to-data-set](#)

Upload the contents of a file to a z/OS data set

Usage

```
zowe zos-files upload file-to-data-set <inputfile> <dataSetName> [options]
```

Positional Arguments

- `inputfile` (*string*)
 - The local file that you want to upload to a data set
- `dataSetName` (*string*)
 - The name of the data set to which you want to upload the file

Options

- `--binary` | `-b` (*boolean*)
 - Data content in binary mode, which means that no data conversion is performed. The data transfer process returns each record as-is, without translation. No delimiters are added between records.
- `--encoding` | `--ec` (*string*)
 - Data content in encoding mode, which means that data conversion is performed according to the encoding specified.
- `--migrated-recall` | `--mr` (*string*)
 - The method by which migrated data set is handled. By default, a migrated data set is recalled synchronously. You can specify the following values: wait, nowait, error

Default value: nowait
- `--record` | `-r` (*boolean*)
 - Data content in record mode, which means that no data conversion is performed and the record length is prepended to the data. The data transfer process returns each line as-is, without translation. No delimiters are added between records. Conflicts with binary.
- `--volume-serial` | `--vs` (*string*)
 - The volume serial (VOLSER) where the data set resides. You can use this option at any time. However, the VOLSER is required only when the data set is not cataloged on the system. A VOLSER is analogous to a drive name on a PC.
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443

- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Upload file contents to a sequential data set named "ibmuser.ps":
 - `zowe zos-files upload file-to-data-set "file.txt" "ibmuser.ps"`
- Upload file contents to a PDS member named "ibmuser.pds(mem)":
 - `zowe zos-files upload file-to-data-set "file.txt" "ibmuser.pds(mem)"`
- Upload file contents to a migrated data set and wait for it to be recalled:
 - `zowe zos-files upload file-to-data-set "file.txt" "ibmuser.ps" --mr wait`

[zowe](#) › [zos-files](#) › [upload](#) › [file-to-uss](#)

Upload content to a USS file from local file

Usage

```
zowe zos-files upload file-to-uss <inputfile> <USSFileName> [options]
```

Positional Arguments

- `inputfile` (*string*)
 - The local file that you want to upload to a USS file
- `USSFileName` (*string*)
 - The name of the USS file to which you want to upload the file

Options

- `--binary` | `-b` (*boolean*)

- Data content in binary mode, which means that no data conversion is performed. The data transfer process returns each record as-is, without translation. No delimiters are added between records.
- `--encoding` | `--ec` (*string*)
 - Data content in encoding mode, which means that data conversion is performed according to the encoding specified.
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.
- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.

- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Upload to the USS file `/a/ibmuser/my_text.txt` from the file `file.txt`:
 - `zowe zos-files upload file-to-uss "file.txt" "/a/ibmuser/my_text.txt"`

[zowe](#) › [zos-files](#) › [upload](#) › [stdin-to-data-set](#)

Upload the content of a stdin to a z/OS data set

Usage

zowe zos-files upload stdin-to-data-set <dataSetName> [options]

Positional Arguments

- `dataSetName` (*string*)
 - The name of the data set to which you want to upload data

Options

- `--binary` | `-b` (*boolean*)
 - Data content in binary mode, which means that no data conversion is performed. The data transfer process returns each record as-is, without translation. No delimiters are added between records.
- `--migrated-recall` | `--mr` (*string*)
 - The method by which migrated data set is handled. By default, a migrated data set is recalled synchronously. You can specify the following values: wait, nowait, error

Default value: nowait
- `--record` | `-r` (*boolean*)
 - Data content in record mode, which means that no data conversion is performed and the record length is prepended to the data. The data transfer process returns each line as-is, without translation. No delimiters are added between records. Conflicts with binary.
- `--volume-serial` | `--vs` (*string*)
 - The volume serial (VOLSER) where the data set resides. You can use this option at any time. However, the VOLSER is required only when the data set is not cataloged on the system. A VOLSER is analogous to a drive name on a PC.
- `--response-timeout` | `--rto` (*number*)
 - The maximum amount of time in seconds the z/OSMF Files TSO servlet should run before returning a response. Any request exceeding this amount of time will be terminated and return an error. Allowed values: 5 - 600

Zosmf Connection Options

- `--host` | `-H` (*string*)
 - The z/OSMF server host name.

- `--port` | `-P` (*number*)
 - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
 - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
 - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
 - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
 - The protocol used (HTTP or HTTPS)

Default value: https
Allowed values: http, https
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
 - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)

- The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

Examples

- Stream content from stdin to a sequential data set named "ibmuser.ps" from a Windows console:
 - `echo "hello world" | zowe zos-files upload stdin-to-data-set "ibmuser.ps"`
- Stream content from stdin to a partition data set member named "ibmuser.pds(mem)" from a Windows console:
 - `echo "hello world" | zowe zos-files upload stdin-to-data-set "ibmuser.pds(mem)"`
- Stream content from stdin to a migrated data set and wait for it to be recalled from a Windows console:
 - `echo "hello world" | zowe zos-files upload stdin-to-data-set "ibmuser.ps" --mr wait`

zowe › zos-ftp

Data set and job functionality via FTP. This functionality uses the open source zos-node-accessor package from IBM. Commands under this group require you to create a zftp profile before using them.

If you find this functionality useful, please consider setting up z/OSMF on your system to get improved stability and speed and more features (for example, issuing TSO and console commands) by using core Zowe CLI.

zowe › zos-ftp › allocate

Allocate a sequential or partitioned dataset

zowe › zos-ftp › allocate › data-set

Allocate a sequential or partitioned dataset

Usage

```
zowe zos-ftp allocate data-set <datasetName> [options]
```

Positional Arguments

- `datasetName` (*string*)
 - The dataset name you'd like to allocate.

Options

- `--dcb` (*string*)
 - DCB parameters for dataset allocation. It's space separated like RECFM=FB LRECL=326 BLKSIZE=23472

FTP Connection options

- `--host` | `-H` (*string*)
 - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
 - The port of the z/OS FTP server.

Default value: 21

- `--user` | `-u` (*string*)
 - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
 - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
 - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true

- `--connection-timeout` | `--ct` (*number*)
 - How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
 - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
 - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Allocate a dataset "IBMUSER.DATASET":
 - `zowe zos-ftp allocate data-set "IBMUSER.DATASET"`

[zowe](#) › [zos-ftp](#) › [delete](#)

Delete data sets, jobs, and USS files

[zowe](#) › [zos-ftp](#) › [delete](#) › [data-set](#)

Delete a data set

Usage

```
zowe zos-ftp delete data-set <dataSet> [options]
```

Positional Arguments

- `dataSet` (*string*)
 - The data set (PDS member or physical sequential data set) which you would like to delete.

Required Options

- `--for-sure` | `-f` (*boolean*)
 - Specify this option to confirm that you want to delete the data set permanently.

FTP Connection options

- `--host` | `-H` (*string*)
 - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
 - The port of the z/OS FTP server.

Default value: 21
- `--user` | `-u` (*string*)
 - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
 - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
 - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true
- `--connection-timeout` | `--ct` (*number*)
 - How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)

- Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
 - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Delete the data set "ibmuser.cntl":
 - `zowe zos-ftp delete data-set "ibmuser.cntl" -f`

[zowe](#) › [zos-ftp](#) › [delete](#) › [job](#)

Cancel a job and purge its output. Note: this command will not work to delete TSU or STC type jobs.

Usage

`zowe zos-ftp delete job <jobid> [options]`

Positional Arguments

- `jobid` (*string*)
 - The ID of the job that you would like to delete

FTP Connection options

- `--host` | `-H` (*string*)
 - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
 - The port of the z/OS FTP server.

Default value: 21

- `--user` | `-u` (*string*)
 - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
 - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
 - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true

- `--connection-timeout` | `--ct` (*number*)
 - How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.

- `--server-name` | `--sn` (*string*)
 - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
 - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Cancel the job "JOB00123" and purge its output, optionally abbreviating the job ID:
 - `zowe zos-ftp delete job j123`

[zowe](#) › [zos-ftp](#) › [delete](#) › [uss-file](#)

Delete a USS file

Usage

`zowe zos-ftp delete uss-file <ussFile> [options]`

Positional Arguments

- `ussFile` (*string*)
 - The absolute path to a USS file you would like to delete.

Required Options

- `--for-sure` | `-f` (*boolean*)
 - Specify this option to confirm that you want to delete the data set permanently.

Options

- `--recursive` (*boolean*)
 - Delete the directory and all files/directories under it.

FTP Connection options

- `--host` | `-H` (*string*)
 - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
 - The port of the z/OS FTP server.

Default value: 21

- `--user` | `-u` (*string*)
 - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
 - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
 - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true

- `--connection-timeout` | `--ct` (*number*)
 - How long (in milliseconds) to wait for the control connection to be established.
Default value: 10000

TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
 - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
 - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Delete the USS file "/u/ibmuser/myfile.txt":
 - `zowe zos-ftp delete uss-file "/u/ibmuser/myfile.txt" -f`

[zowe](#) › [zos-ftp](#) › [download](#)

Download data set, job spool, and USS file content

[zowe](#) › [zos-ftp](#) › [download](#) › [all-spool-by-jobid](#)

Download all spool content for a job to files in a local directory by providing the job id

Usage

```
zowe zos-ftp download all-spool-by-jobid <jobid> [options]
```

Positional Arguments

- `jobid` (*string*)
 - The ID of the job for which you would like to list spool files

Options

- `--directory` | `-d` (*string*)
 - The local directory to save the spool content to. By default, it will be saved to `./output`.
- `--omit-jobid-directory` | `--ojd` (*boolean*)
 - If you specify this, the job output will be saved directly to the specified (or default) directory. For example, if you omit this, the output would be saved to `./output/JOB00123`. If you specify `--ojd`, the `JOB00123` directory would not be included in the output path and the content would be saved to `./output`.

FTP Connection options

- `--host` | `-H` (*string*)
 - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
 - The port of the z/OS FTP server.

Default value: 21

- `--user` | `-u` (*string*)
 - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
 - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
 - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true

- `--connection-timeout` | `--ct` (*number*)
 - How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
 - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
 - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Download all spool for the job with the ID JOB00123 to the default subdirectory in the current directory:
 - `zowe zos-ftp download all-spool-by-jobid j123`
- Download all spool for the job with the ID JOB00123 to the directory build/job_output:
 - `zowe zos-ftp download all-spool-by-jobid j123 -d build/job_output/`

[zowe](#) › [zos-ftp](#) › [download](#) › [data-set](#)

Download the contents of a z/OS data set to a local file

Usage

```
zowe zos-ftp download data-set <dataSet> [options]
```

Positional Arguments

- `dataSet` (*string*)
 - The data set (PDS member or physical sequential data set) which you would like to download to a local file.

Options

- `--binary` | `-b` (*boolean*)
 - Download the file content in binary mode, which means that no data conversion is performed. The data transfer process returns each line as-is, without translation. No delimiters are added between records.
- `--file` | `-f` (*string*)
 - The path to the local file where you want to download the content. When you omit the option, the command generates a file name automatically for you.
- `--record` | `-r` | `--rdw` (*boolean*)
 - Download the variable-length data set with RECFM of V, VB, VBS, etc in rdw mode, in which the 4-byte RDW (Record Descriptor Word) is inserted at the beginning of each record.

FTP Connection options

- `--host` | `-H` (*string*)
 - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
 - The port of the z/OS FTP server.
Default value: 21
- `--user` | `-u` (*string*)
 - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
 - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
 - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.
Default value: true
- `--connection-timeout` | `--ct` (*number*)

- How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
 - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
 - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Download the data set "ibmuser.loadlib(main)" in binary mode to the local file "main.obj":
 - `zowe zos-ftp download data-set "ibmuser.loadlib(main)" -b -f main.obj`

[zowe](#) › [zos-ftp](#) › [download](#) › [uss-file](#)

Download the contents of a USS file to a local file

Usage

```
zowe zos-ftp download uss-file <ussFile> [options]
```

Positional Arguments

- `ussFile` (*string*)
 - The path to the USS file you would like to download.

Options

- `--binary` | `-b` (*boolean*)
 - Download the file content in binary mode, which means that no data conversion is performed. The data transfer process returns each line as-is, without translation. No delimiters are added between records.
- `--file` | `-f` (*string*)
 - The path to the local file where you want to download the content. When you omit the option, the command generates a file name automatically for you.

FTP Connection options

- `--host` | `-H` (*string*)
 - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
 - The port of the z/OS FTP server.
Default value: 21
- `--user` | `-u` (*string*)
 - Username for authentication on z/OS

- `--password` | `-p` | `--pass` | `--pw` (*string*)
 - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
 - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true
- `--connection-timeout` | `--ct` (*number*)
 - How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
 - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
 - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.

- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Download the USS file `"/u/users/ibmuser/main.obj"` in binary mode to the local file `"main.obj"`:
 - `zowe zos-ftp download uss-file "/u/users/ibmuser/main.obj" -b -f main.obj`

zowe › zos-ftp › list

List data sets, data set members, uss files, jobs, spool files

zowe › zos-ftp › list › data-set

List all data sets that match a DSLEVEL pattern (see help below).

The following values can be used with the `--response-format-filter` (`--rff`) argument to display more data from the data sets: `volume`, `unit`, `referred`, `ext`, `used`, `recfm`, `lrecl`, `blkz`, `dsorg`, and `dsname`.

Usage

```
zowe zos-ftp list data-set <pattern> [options]
```

Positional Arguments

- `pattern` (*string*)
 - The pattern or patterns to match data sets against. Also known as 'DSLEVEL', it is somewhat similar to the concept of a 'glob' (but not identical). The following special sequences can be used in the pattern:
 - `%`: Matches any single character
 - `*`: Matches any number of characters within a data set name qualifier (e.g. `"ibmuser.j*.old"` matches `"ibmuser.jcl.old"` but not `"ibmuser.jcl.very.old"`)
 - `**`: Matches any number of characters within any number of data set name qualifiers (e.g.

"ibmuser.**.old" matches both "ibmuser.jcl.old" and "ibmuser.jcl.very.old")
However, the pattern cannot begin with any of these sequences.

FTP Connection options

- `--host` | `-H` (*string*)
 - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
 - The port of the z/OS FTP server.

Default value: 21
- `--user` | `-u` (*string*)
 - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
 - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
 - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true
- `--connection-timeout` | `--ct` (*number*)
 - How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)

- Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
 - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Response Format Options

- `--response-format-filter` | `--rff` (*array*)
 - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '--response-format-type' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
 - The command response output format type. Must be one of the following:

table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the

table.

list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.

object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string

- `--response-format-header` | `--rfh` (*boolean*)
 - If "`--response-format-type table`" is specified, include the column headers in the output.

Examples

- List all data sets beginning with "ibmuser" and ending in "cntl":
 - `zowe zos-ftp list data-set "ibmuser.**.cntl"`

[zowe](#) › [zos-ftp](#) › [list](#) › [data-set-members](#)

List all members of the specified PDS or PDSE data set.

Usage

```
zowe zos-ftp list data-set-members <dsname> [options]
```

Positional Arguments

- `dsname` (*string*)
 - The PDS or PDSE data set name.

FTP Connection options

- `--host` | `-H` (*string*)
 - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
 - The port of the z/OS FTP server.

Default value: 21

- `--user` | `-u` (*string*)
 - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
 - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
 - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true

- `--connection-timeout` | `--ct` (*number*)
 - How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
 - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
 - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Response Format Options

- `--response-format-filter` | `--rff` (*array*)
 - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '`--response-format-type`' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
 - The command response output format type. Must be one of the following:

table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.

list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.

object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
 - If "`--response-format-type table`" is specified, include the column headers in the output.

Examples

- List all members in data set "ibmuser.test.cntl":
 - `zowe zos-ftp list data-set-members "ibmuser.test.cntl"`

zowe › zos-ftp › list › jobs

List all data sets that match a DSLEVEL pattern (see help below).

Usage

`zowe zos-ftp list jobs [options]`

Options

- `--prefix` (*string*)
 - Specify the job name prefix of the jobs you own and want to list. You can specify a wildcard, which is usually in the form "JOB*".
If you don't specify this option all jobs under this owner will be listed by default.
- `--owner` | `-o` (*string*)
 - Specify the owner user ID of the jobs you want to list. The owner is the individual/user who submitted the job OR the user ID assigned to the job.

FTP Connection options

- `--host` | `-H` (*string*)
 - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
 - The port of the z/OS FTP server.

Default value: 21
- `--user` | `-u` (*string*)
 - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
 - Password to authenticate to FTP.

- `--secure-ftp` (*boolean*)
 - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true

- `--connection-timeout` | `--ct` (*number*)
 - How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
 - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
 - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Response Format Options

- `--response-format-filter` | `--rff` (*array*)
 - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '`--response-format-type`' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
 - The command response output format type. Must be one of the following:

table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.

list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.

object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
 - If "`--response-format-type table`" is specified, include the column headers in the output.

Examples

- List all jobs with names beginning beginning with "ibmu":
 - `zowe zos-ftp list jobs --prefix "ibmu*"`
- List Alice's jobs with names beginning beginning with "ibmu":

- `zowe zos-ftp list jobs --prefix "ibmu*" --owner "alice"`

zowe › **zos-ftp** › **list** › **spool-files-by-jobid**

Given a z/OS job JOBID, list the spool files (DDs) for a z/OS job on the JES/spool queues. The command does not pre-validate the JOBID.

Usage

```
zowe zos-ftp list spool-files-by-jobid <jobid> [options]
```

Positional Arguments

- `jobid` (*string*)
 - The z/OS JOBID of the job with the spool files you want to list. No pre-validation of the JOBID is performed.

FTP Connection options

- `--host` | `-H` (*string*)
 - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
 - The port of the z/OS FTP server.

Default value: 21
- `--user` | `-u` (*string*)
 - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
 - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
 - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true

- `--connection-timeout` | `--ct` (*number*)
 - How long (in milliseconds) to wait for the control connection to be established.
Default value: 10000

TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
 - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
 - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Response Format Options

- `--response-format-filter` | `--rff` (*array*)
 - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '`--response-format-type`' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
 - The command response output format type. Must be one of the following:
 - table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.
 - list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.
 - object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.
 - string: Formats output data as a string. JSON objects/arrays are stringified.
 - Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
 - If "`--response-format-type table`" is specified, include the column headers in the output.

Examples

- List the spool files of the job with JOBID JOB00123:
 - `zowe zos-ftp list spool-files-by-jobid job00123`

[zowe](#) › [zos-ftp](#) › [list](#) › [uss-files](#)

List USS files and subdirectories in a directory. Optional file name pattern like "prefix*", "*suffix", or "prefix*suffix" can be specified at the end of directory. See EXAMPLES section.

The following values can be used with the `--response-format-filter` (`--rff`) argument to display more data from the data sets: name, size, owner, group, and permissions.

Usage

zowe zos-ftp list uss-files <directory> [options]

Positional Arguments

- `directory` (*string*)
 - The USS directory to list files in, or the directory with file name pattern

FTP Connection options

- `--host` | `-H` (*string*)
 - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
 - The port of the z/OS FTP server.

Default value: 21

- `--user` | `-u` (*string*)
 - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
 - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
 - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true

- `--connection-timeout` | `--ct` (*number*)
 - How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)

- Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
 - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
 - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Response Format Options

- `--response-format-filter` | `--rff` (*array*)
 - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '--response-format-type' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)

- The command response output format type. Must be one of the following:

table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.

list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.

object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string

- `--response-format-header` | `--rfh` (*boolean*)
 - If "`--response-format-type table`" is specified, include the column headers in the output.

Examples

- List USS files in the directory `"/u/users/ibmuser/"`:
 - `zowe zos-ftp list uss-files "/u/users/ibmuser"`
- List USS files with suffix of `".txt"` in the directory `"/u/users/ibmuser/"`:
 - `zowe zos-ftp list uss-files "/u/users/ibmuser/*.txt"`
- List USS files in the directory `"/u/users/ibmuser/"` and show only the file name:
 - `zowe zos-ftp list uss-files "/u/users/ibmuser/" --rff name`

[zowe](#) › [zos-ftp](#) › [make](#)

Make a USS directory

[zowe](#) › [zos-ftp](#) › [make](#) › [uss-directory](#)

Make a Unix System Services Directory

Usage

`zowe zos-ftp make uss-directory <ussDirectory> [options]`

Positional Arguments

- `ussDirectory` (*string*)
 - The USS directory you'd like to make.

FTP Connection options

- `--host` | `-H` (*string*)
 - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
 - The port of the z/OS FTP server.

Default value: 21

- `--user` | `-u` (*string*)
 - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
 - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
 - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true

- `--connection-timeout` | `--ct` (*number*)
 - How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.

- `--server-name` | `--sn` (*string*)
 - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
 - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Make a USS directory `"/u/users/ibmuser/mydir"`:
 - `zowe zos-ftp make uss-directory "/u/users/ibmuser/mydir"`

[zowe](#) › [zos-ftp](#) › [rename](#)

Rename data sets and USS files or directories

[zowe](#) › [zos-ftp](#) › [rename](#) › [data-set](#)

Rename a cataloged data set

Usage

```
zowe zos-ftp rename data-set <oldDataSet> <newDataSet> [options]
```

Positional Arguments

- `oldDataSet` (*string*)
 - The current name of the data set you want to rename.
- `newDataSet` (*string*)
 - The new name for the data set.

FTP Connection options

- `--host` | `-H` (*string*)
 - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
 - The port of the z/OS FTP server.
Default value: 21
- `--user` | `-u` (*string*)
 - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
 - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
 - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.
Default value: true
- `--connection-timeout` | `--ct` (*number*)

- How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
 - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
 - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Rename the data set `ibmuser.jcl` to `ibmuser.cntl`:
 - `zowe zos-ftp rename data-set ibmuser.jcl ibmuser.cntl`
- Rename the data set member `"ibmuser.cntl(alloc)"` to `"ibmuser.cntl(alloc2)"`. Note: you can only rename members within the same partitioned data set. You cannot move a member to another data set with this command.:
 - `zowe zos-ftp rename data-set "ibmuser.cntl(alloc)" "ibmuser.cntl(alloc2)"`

[zowe](#) › [zos-ftp](#) › [rename](#) › [uss-file](#)

Rename a USS file or directory

Usage

```
zowe zos-ftp rename uss-file <olduss> <newuss> [options]
```

Positional Arguments

- `olduss` (*string*)
 - The current name of the USS file you want to rename.
- `newuss` (*string*)
 - The new name for the USS file.

FTP Connection options

- `--host` | `-H` (*string*)
 - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
 - The port of the z/OS FTP server.

Default value: 21
- `--user` | `-u` (*string*)
 - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
 - Password to authenticate to FTP.

- `--secure-ftp` (*boolean*)
 - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true

- `--connection-timeout` | `--ct` (*number*)
 - How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
 - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
 - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
 - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
 - The name of a (base) profile to load for this command execution.

Base Connection Options

- `--token-type` | `--tt` (*string*)
 - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
 - The value of the token to pass to the API.

- `--cert-file` (*local file path*)
 - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
 - The file path to a certificate key file to use for authentication

Examples

- Rename the file `/u/users/ibmuser/hello.txt` to `/u/users/ibmuser/hello2.txt`:
 - ```
zowe zos-ftp rename uss-file "/u/users/ibmuser/hello.txt"
"/u/users/ibmuser/hello2.txt"
```

## zowe › zos-ftp › submit

---

Submit jobs from local files and data sets

### zowe › zos-ftp › submit › data-set

Submit a job from a cataloged data set containing JCL. The JCL will be downloaded via FTP and then submitted.

## Usage

```
zowe zos-ftp submit data-set <dataSet> [options]
```

## Positional Arguments

- `dataSet` (*string*)
  - The data set containing JCL that you would like to submit

## Options

- `--wait` | `-w` (*string*)
  - Specify job query interval and max times of querying job status. The format of this option is comma-separated numeric values. For example, '5,12' means queries job status every 5 seconds for 12 times at most.
- `--wait-for-output` | `--wfo` (*boolean*)
  - Wait for the job to enter OUTPUT status before completing the command.

- `--wait-for-active` | `--wfa` (*boolean*)
  - Wait for the job to enter ACTIVE status before completing the command.

## FTP Connection options

- `--host` | `-H` (*string*)
  - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
  - The port of the z/OS FTP server.  
Default value: 21
- `--user` | `-u` (*string*)
  - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
  - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
  - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.  
Default value: true
- `--connection-timeout` | `--ct` (*number*)
  - How long (in milliseconds) to wait for the control connection to be established.  
Default value: 10000

## TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)

- Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

## Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
  - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Response Format Options

- `--response-format-filter` | `--rff` (*array*)
  - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '--response-format-type' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
  - The command response output format type. Must be one of the following:  
  
table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the



table.

list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.

object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string

- `--response-format-header` | `--rfh` (*boolean*)
  - If "`--response-format-type table`" is specified, include the column headers in the output.

## Examples

- Submit a job residing in the data set "ibmuser.cntl(iefbr14)":
  - `zowe zos-ftp submit data-set "ibmuser.cntl(iefbr14)"`
- Submit a job from the data set "ibmuser.cntl(iefbr14)" and print only the job ID:
  - `zowe zos-ftp submit data-set "ibmuser.cntl(iefbr14)" --rff jobid --rft string`
- Submit a job from the data set "ibmuser.cntl(iefbr14)" and wait for job complete.:
  - `zowe zos-ftp submit data-set "ibmuser.cntl(iefbr14)" --wait 5,12`

## [zowe](#) › [zos-ftp](#) › [submit](#) › [local-file](#)

Submit a job from a local file containing JCL

### Usage

```
zowe zos-ftp submit local-file <file> [options]
```

### Positional Arguments

- `file` (*local file path*)
  - The file you would like to submit as jcl

### Options

- `--wait` | `-w` (*string*)
  - Specify job query interval and max times of querying job status. The format of this option is comma-separated numeric values. For example, '5,12' means queries job status every 5 seconds for 12 times at most.
- `--wait-for-output` | `--wfo` (*boolean*)
  - Wait for the job to enter OUTPUT status before completing the command.
- `--wait-for-active` | `--wfa` (*boolean*)
  - Wait for the job to enter ACTIVE status before completing the command.

## FTP Connection options

- `--host` | `-H` (*string*)
  - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
  - The port of the z/OS FTP server.

Default value: 21
- `--user` | `-u` (*string*)
  - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
  - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
  - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true
- `--connection-timeout` | `--ct` (*number*)
  - How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

## TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
  - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

## Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
  - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Response Format Options

- `--response-format-filter` | `--rff` (*array*)

- Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '--response-format-type' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
  - The command response output format type. Must be one of the following:
 

table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.

list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.

object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
  - If "--response-format-type table" is specified, include the column headers in the output.

## Examples

- Submit a job from the local file "my\_build\_jcl.txt":
  - `zowe zos-ftp submit local-file "my_build_jcl.txt"`
- Submit a job from the local file "my\_build\_jcl.txt" and print only the job ID:
  - `zowe zos-ftp submit local-file "my_build_jcl.txt" --rff jobid --rft string`
- Submit a job from the local file "my\_build\_jcl.txt" and wait for job complete.:
  - `zowe zos-ftp submit local-file "my_build_jcl.txt" --wait 5,12`

## [zowe](#) › [zos-ftp](#) › [submit](#) › [stdin](#)

Submit a job from JCL written to the standard input (stdin) of this process.

## Usage

zowe zos-ftp submit stdin [options]

## Options

- `--wait` | `-w` (*string*)
  - Specify job query interval and max times of querying job status. The format of this option is comma-separated numeric values. For example, '5,12' means queries job status every 5 seconds for 12 times at most.
- `--wait-for-output` | `--wfo` (*boolean*)
  - Wait for the job to enter OUTPUT status before completing the command.
- `--wait-for-active` | `--wfa` (*boolean*)
  - Wait for the job to enter ACTIVE status before completing the command.

## FTP Connection options

- `--host` | `-H` (*string*)
  - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
  - The port of the z/OS FTP server.  
  
Default value: 21
- `--user` | `-u` (*string*)
  - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
  - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
  - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true

- `--connection-timeout` | `--ct` (*number*)
  - How long (in milliseconds) to wait for the control connection to be established.  
Default value: 10000

## TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
  - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

## Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
  - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Response Format Options

- `--response-format-filter` | `--rff` (*array*)
  - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '`--response-format-type`' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
  - The command response output format type. Must be one of the following:
    - table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.
    - list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.
    - object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.
    - string: Formats output data as a string. JSON objects/arrays are stringified.
  - Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
  - If "`--response-format-type table`" is specified, include the column headers in the output.

## Examples

- Submit a job from stdin, redirecting the contents of my\_jcl.txt in.:
  - `zowe zos-ftp submit stdin < my_jcl.txt`
- Submit a job from the local file "my\_build\_jcl.txt" and wait for job complete.:
  - `zowe zos-ftp submit stdin "my_build_jcl.txt" --wait 5,12`

## [zowe](#) › [zos-ftp](#) › [upload](#)

---

Upload data set and USS content

## [zowe](#) › [zos-ftp](#) › [upload](#) › [file-to-data-set](#)

Upload contents of a local file to a z/OS data set

### Usage

```
zowe zos-ftp upload file-to-data-set <file> <dataSet> [options]
```

### Positional Arguments

- `file` (*local file path*)
  - Upload the contents of this file to the data set
- `dataSet` (*string*)
  - The data set (PDS member or physical sequential data set) to which you would like to upload content.

### Options

- `--binary` | `-b` (*boolean*)
  - Upload content in binary mode.
- `--dcb` (*string*)
  - DCB parameters for sequential dataset (PS dataset) allocation if not existing. It is space separated like RECFM=FB LRECL=326 BLKSIZE=23472

### FTP Connection options

- `--host` | `-H` (*string*)
  - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
  - The port of the z/OS FTP server.  
Default value: 21
- `--user` | `-u` (*string*)
  - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)



- Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
  - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true

- `--connection-timeout` | `--ct` (*number*)
  - How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

## TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
  - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

## Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
  - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)

- The value of the token to pass to the API.
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Examples

- Upload to "ibmuser.cntl(iefbr14)" from the file iefbr14.txt:
  - `zowe zos-ftp upload file-to-data-set iefbr14.txt "ibmuser.cntl(iefbr14)"`
- Upload to "ibmuser.cntl(iefbr14)" from the file iefbr14.txt with the DCB parameters:
  - `zowe zos-ftp upload file-to-data-set iefbr14.txt "ibmuser.cntl(iefbr14)" --dcb "RECFM=FB LRECL=326 BLKSIZE=23472"`

## [zowe](#) › [zos-ftp](#) › [upload](#) › [file-to-uss-file](#)

Upload contents of a local to a Unix System Services file.

### Usage

```
zowe zos-ftp upload file-to-uss-file <file> <ussFile> [options]
```

### Positional Arguments

- `file` (*local file path*)
  - Upload the contents of this local file to a data set.
- `ussFile` (*string*)
  - The USS file to which you would like to upload content.

### Options

- `--binary` | `-b` (*boolean*)
  - Upload content in binary mode.

### FTP Connection options

- `--host` | `-H` (*string*)
  - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
  - The port of the z/OS FTP server.

Default value: 21
- `--user` | `-u` (*string*)
  - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
  - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
  - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true
- `--connection-timeout` | `--ct` (*number*)
  - How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

## TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
  - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

## Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
  - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Examples

- Upload to `"/u/users/ibmuser/iefbr14.txt"` from the file `iefbr14.txt`:
  - `zowe zos-ftp upload file-to-uss-file iefbr14.txt "/u/users/ibmuser/iefbr14.txt"`

## [zowe](#) › [zos-ftp](#) › [upload](#) › [stdin-to-data-set](#)

Upload contents piped to stdin to a z/OS data set

### Usage

```
zowe zos-ftp upload stdin-to-data-set <dataSet> [options]
```

### Positional Arguments

- `dataSet` (*string*)

- The data set (PDS member or physical sequential data set) to which you would like to upload content.

## Options

- `--binary` | `-b` (*boolean*)
  - Upload content in binary mode.

## FTP Connection options

- `--host` | `-H` (*string*)
  - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
  - The port of the z/OS FTP server.  
Default value: 21
- `--user` | `-u` (*string*)
  - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
  - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
  - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.  
Default value: true
- `--connection-timeout` | `--ct` (*number*)
  - How long (in milliseconds) to wait for the control connection to be established.  
Default value: 10000

## TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)

- Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
  - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

## Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
  - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Examples

- Upload to "ibmuser.cntl(iefbr14)" from standard input (you can pipe into this command):
  - `zowe zos-ftp upload stdin-to-data-set "ibmuser.cntl(iefbr14)"`

## [zowe](#) › [zos-ftp](#) › [upload](#) › [stdin-to-uss-file](#)

Upload from stdin to a Unix System Services File

## Usage

zowe zos-ftp upload stdin-to-uss-file <ussFile> [options]

## Positional Arguments

- `ussFile` (*string*)
  - The USS file to which you would like to upload content.

## Options

- `--binary` | `-b` (*boolean*)
  - Upload content in binary mode.

## FTP Connection options

- `--host` | `-H` (*string*)
  - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
  - The port of the z/OS FTP server.

Default value: 21

- `--user` | `-u` (*string*)
  - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
  - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
  - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true

- `--connection-timeout` | `--ct` (*number*)

- How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

## TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
  - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

## Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
  - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Examples



- Upload to "/u/users/ibmuser/iefbr14.txt" from standard input (you can pipe into this command):

- `zowe zos-ftp upload stdin-to-uss-file "/u/users/ibmuser/iefbr14.txt"`

## [zowe](#) › [zos-ftp](#) › [view](#)

---

View data sets, job output, and USS content

### [zowe](#) › [zos-ftp](#) › [view](#) › [all-spool-by-jobid](#)

View all spool content for a job by providing the job id

#### Usage

```
zowe zos-ftp view all-spool-by-jobid <jobid> [options]
```

#### Positional Arguments

- `jobid` (*string*)
  - The ID of the job for which you would like to list spool files

#### FTP Connection options

- `--host` | `-H` (*string*)
  - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
  - The port of the z/OS FTP server.

Default value: 21

- `--user` | `-u` (*string*)
  - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
  - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)

- Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true

- `--connection-timeout` | `--ct` (*number*)

- How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

## TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)

- Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.

- `--server-name` | `--sn` (*string*)

- Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

## Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)

- The name of a (zftp) profile to load for this command execution.

- `--base-profile` | `--base-p` (*string*)

- The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)

- The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.

- `--token-value` | `--tv` (*string*)

- The value of the token to pass to the API.

- `--cert-file` (*local file path*)

- The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Examples

- View all spool content for the job with ID JOB00123 (optionally abbreviating the job ID):
  - `zowe zos-ftp view all-spool-by-jobid j123`

## [zowe](#) › [zos-ftp](#) › [view](#) › [data-set](#)

View the contents of a z/OS data set

## Usage

```
zowe zos-ftp view data-set <dataSet> [options]
```

## Positional Arguments

- `dataSet` (*string*)
  - The data set (PDS member or physical sequential data set) which you would like to view the contents of.

## Options

- `--binary` | `-b` (*boolean*)
  - View content in binary form without converting to ASCII text

## FTP Connection options

- `--host` | `-H` (*string*)
  - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
  - The port of the z/OS FTP server.

Default value: 21

- `--user` | `-u` (*string*)

- Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
  - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
  - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true

- `--connection-timeout` | `--ct` (*number*)
  - How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

## TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
  - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

## Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
  - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)

- The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Examples

- View the content of the data set "ibmuser.cntl(iefbr14)":
  - `zowe zos-ftp view data-set "ibmuser.cntl(iefbr14)"`
- View the content of the data set "ibmuser.loadlib(main)" and pipe it into the hex viewer program xxd:
  - `zowe zos-ftp view data-set "ibmuser.loadlib(main)" -b | xxd`

## [zowe](#) › [zos-ftp](#) › [view](#) › [job-status-by-jobid](#)

View status details of a single z/OS job on spool/JES queues. The command does not prevalidate the JOBID.

### Usage

```
zowe zos-ftp view job-status-by-jobid <jobid> [options]
```

### Positional Arguments

- `jobid` (*string*)
  - The ID of the jobfor which you would like to list spool files

### FTP Connection options

- `--host` | `-H` (*string*)
  - The hostname or IP address of the z/OS server to connect to.

- `--port` | `-P` (*number*)
  - The port of the z/OS FTP server.

Default value: 21
- `--user` | `-u` (*string*)
  - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
  - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
  - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true
- `--connection-timeout` | `--ct` (*number*)
  - How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

## TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
  - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

## Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
  - The name of a (zftp) profile to load for this command execution.

- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Response Format Options

- `--response-format-filter` | `--rff` (*array*)
  - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '`--response-format-type`' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
  - The command response output format type. Must be one of the following:
    - table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.
    - list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.
    - object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string

- `--response-format-header` | `--rfh` (*boolean*)
  - If "`--response-format-type table`" is specified, include the column headers in the output.

## Examples

- View the status for the job with ID "JOB00123" (optionally abbreviating the ID):
  - `zowe zos-ftp view job-status-by-jobid j123`

## [zowe](#) › [zos-ftp](#) › [view](#) › [spool-file-by-id](#)

View the contents of a spool file from a z/OS job on spool/JES queues. The command does not pre-validate the JOBID or spool ID.

## Usage

```
zowe zos-ftp view spool-file-by-id <jobid> <spoolfileid> [options]
```

## Positional Arguments

- `jobid` (*string*)
  - The z/OS JOBID of the job containing the spool file you want to view. No pre-validation of the JOBID is performed.
- `spoolfileid` (*number*)
  - The spool file ID number for the spool file to view. No pre-validation of the ID is performed.

## FTP Connection options

- `--host` | `-H` (*string*)
  - The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
  - The port of the z/OS FTP server.

Default value: 21



- `--user` | `-u` (*string*)
  - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
  - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
  - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.

Default value: true

- `--connection-timeout` | `--ct` (*number*)
  - How long (in milliseconds) to wait for the control connection to be established.

Default value: 10000

## TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
  - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

## Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)
  - The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Examples

- View the spool file with ID 4 for the job with job ID JOB00123:
  - `zowe zos-ftp view spool-file-by-id JOB00123 4`

## [zowe](#) › [zos-ftp](#) › [view](#) › [uss-file](#)

View the contents of a Unix System Services File

### Usage

```
zowe zos-ftp view uss-file <ussFile> [options]
```

### Positional Arguments

- `ussFile` (*string*)
  - The USS file you'd like to view the contents of.

### Options

- `--binary` | `-b` (*boolean*)
  - View content in binary form without converting to ASCII text

### FTP Connection options

- `--host` | `-H` (*string*)

- The hostname or IP address of the z/OS server to connect to.
- `--port` | `-P` (*number*)
  - The port of the z/OS FTP server.
  - Default value: 21
- `--user` | `-u` (*string*)
  - Username for authentication on z/OS
- `--password` | `-p` | `--pass` | `--pw` (*string*)
  - Password to authenticate to FTP.
- `--secure-ftp` (*boolean*)
  - Set to true for both control and data connection encryption, 'control' for control connection encryption only, or 'implicit' for implicitly encrypted control connection (this mode is deprecated in modern times, but usually uses port 990). Note: Unfortunately, this plugin's functionality only works with FTP and FTPS, not 'SFTP' which is FTP over SSH.
  - Default value: true
- `--connection-timeout` | `--ct` (*number*)
  - How long (in milliseconds) to wait for the control connection to be established.
  - Default value: 10000

## TLS / Secure Connection options

- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates. Only specify this if you are connecting to a secure FTP instance.
- `--server-name` | `--sn` (*string*)
  - Server name for the SNI (Server Name Indication) TLS extension. Only specify if you are connecting securely

## Profile Options

- `--zftp-profile` | `--zftp-p` (*string*)

- The name of a (zftp) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Examples

- View the content of the USS file `"/u/users/ibmuser/myfile.txt"`:
  - `zowe zos-ftp view uss-file "/u/users/ibmuser/myfile.txt"`
- View the content of the USS file `"/u/users/ibmuser/myjava.jar"` in binary mode and pipe it into the hex viewer command `xxd`:
  - `zowe zos-ftp view uss-file "/u/users/ibmuser/myjava.jar" -b | xxd`

## zowe › zos-jobs

---

Manage z/OS jobs.

## zowe › zos-jobs › cancel

---

Cancel a single job by job ID. This cancels the job if it is running or on input.

## zowe › zos-jobs › cancel › job

Cancel a single job by job ID

### Usage

```
zowe zos-jobs cancel job <jobid> [options]
```

### Positional Arguments

- `jobid` (*string*)
  - The job ID (e.g. JOB00123) of the job. Job ID is a unique identifier for z/OS batch jobs -- no two jobs on one system can have the same ID. Note: z/OS allows you to abbreviate the job ID if desired. You can use, for example "J123".

### Options

- `--modify-version` (*string*)
  - Using this option to set X-IBM-Job-Modify-Version to "2.0" will make the cancel job API synchronous. Otherwise, it will be asynchronous by default.

Default value: 1.0

### Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.

Default value: 443

- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Examples

- Cancel job with job ID JOB03456:
  - `zowe zos-jobs cancel job JOB03456`
- Cancel job with job ID JOB03456 synchronously:
  - `zowe zos-jobs cancel job JOB03456 --modify-version "2.0"`

## [zowe](#) › [zos-jobs](#) › [delete](#)

---

Delete a single job by job ID in OUTPUT status. This cancels the job if it is running and purges its output from the system.

## [zowe](#) › [zos-jobs](#) › [delete](#) › [job](#)

Delete a single job by job ID

### Usage

```
zowe zos-jobs delete job <jobid> [options]
```

### Positional Arguments

- `jobid` (*string*)
  - The job ID (e.g. JOB00123) of the job. Job ID is a unique identifier for z/OS batch jobs -- no two jobs on one system can have the same ID. Note: z/OS allows you to abbreviate the job ID if desired. You can use, for example "J123".

### Options

- `--modify-version` (*string*)

- Using this option to set X-IBM-Job-Modify-Version to "2.0" will make the delete job API synchronous. Otherwise, it will be asynchronous by default.

Default value: 1.0

## Zosmf Connection Options

- `--host` | `-H` (*string*)

- The z/OSMF server host name.

- `--port` | `-P` (*number*)

- The z/OSMF server port.

Default value: 443

- `--user` | `-u` (*string*)

- Mainframe (z/OSMF) user name, which can be the same as your TSO login.

- `--password` | `--pass` | `--pw` (*string*)

- Mainframe (z/OSMF) password, which can be the same as your TSO password.

- `--reject-unauthorized` | `--ru` (*boolean*)

- Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)

- The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.

- `--protocol` (*string*)

- The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)

- The file path to a certificate file to use for authentication



- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Examples

- Delete job with job ID JOB03456:
  - `zowe zos-jobs delete job JOB03456`
- Delete job with job ID JOB03456 synchronously:
  - `zowe zos-jobs delete job JOB03456 --modify-version "2.0"`

## [zowe](#) › [zos-jobs](#) › [download](#)

---

Download the output of a job as separate files.

## [zowe](#) › [zos-jobs](#) › [download](#) › [output](#)

Download all job output to a local directory. Each spool DD will be downloaded to its own file in the directory.

## Usage

zowe zos-jobs download output <jobid> [options]

## Positional Arguments

- `jobid` (*string*)
  - The z/OS JOBID of the job containing the spool files you want to view. No pre-validation of the JOBID is performed.

## Options

- `--directory` | `-d` | `--dir` (*string*)
  - The local directory you would like to download the output for the job to.
- `--extension` | `-e` (*string*)
  - A file extension to save the job output with. Defaults to '.txt'.
- `--omit-jobid-directory` | `--ojd` (*boolean*)
  - If specified, job output will be saved directly to the specified directory rather than creating a subdirectory named after the ID of the job.

## Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.  
  
Default value: 443
- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Examples

- Download all the output of the job with job ID JOB00234 to an automatically generated directory.:
  - `zowe zos-jobs download output JOB00234`

## [zowe](#) › [zos-jobs](#) › [list](#)

---

List z/OS jobs and list the spool files (DDs) for a z/OS job on the JES/spool queues.

### [zowe](#) › [zos-jobs](#) › [list](#) › [jobs](#)

List jobs on JES spool/queues. By default, the command lists jobs owned (owner) by the user specified in your z/OSMF profile. The default for prefix is "\*". The command does not prevalidate your user ID. The command surfaces errors verbatim from the z/OSMF Jobs REST endpoints.

#### Usage

```
zowe zos-jobs list jobs [options]
```

#### Options

- `--owner` | `-o` (*string*)
  - Specify the owner of the jobs you want to list. The owner is the individual/user who submitted the job OR the user ID assigned to the job. The command does not prevalidate the owner. You can specify a wildcard according to the z/OSMF Jobs REST endpoint documentation, which is usually in the form "USER\*".
- `--prefix` | `-p` (*string*)
  - Specify the job name prefix of the jobs you want to list. The command does not prevalidate the owner. You can specify a wildcard according to the z/OSMF Jobs REST endpoint documentation, which is usually in the form "JOB\*".
- `--exec-data` | `--ed` (*boolean*)
  - Use this option to retrieve execution data for jobs via the z/OSMF REST API.

#### Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)

- The z/OSMF server port.

Default value: 443

- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)

Default value: https  
Allowed values: http, https

- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Response Format Options

- `--response-format-filter` | `--rff` (*array*)
  - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '`--response-format-type`' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
  - The command response output format type. Must be one of the following:
    - table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.
    - list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.
    - object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.
    - string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
  - If "`--response-format-type table`" is specified, include the column headers in the output.

## Examples

- List all jobs with default settings. The command returns jobs owned by your user ID with any job name:

- `zowe zos-jobs list jobs`
- List all jobs owned by user IDs starting with 'ibmu' and job names starting with 'myjo':
  - `zowe zos-jobs list jobs -o "ibmu*" -p "myjo*"`
- List all jobs with default owner and prefix settings, displaying only the job ID of each job:
  - `zowe zos-jobs list jobs --rff jobid --rft table`
- List all jobs and return job execution data along with the default information:
  - `zowe zos-jobs list jobs --exec-data`
- List all jobs owned by user IDs starting with 'ibmu' and return job execution data along with the default information:
  - `zowe zos-jobs list jobs -o "ibmu*" --exec-data`
- List all jobs owned by user IDs starting with 'ibmu' and job names starting with 'myjo' and return job execution data along with the default information:
  - `zowe zos-jobs list jobs -o "ibmu*" -p "myjo*" --exec-data`

## [zowe](#) › [zos-jobs](#) › [list](#) › [spool-files-by-jobid](#)

Given a z/OS job JOBID, list the spool files (DDs) for a z/OS job on the JES/spool queues. The command does not pre-validate the JOBID. The command presents errors verbatim from the z/OSMF Jobs REST endpoints.

### Usage

```
zowe zos-jobs list spool-files-by-jobid <jobid> [options]
```

### Positional Arguments

- `jobid` (*string*)
  - The z/OS JOBID of the job with the spool files you want to list. No pre-validation of the JOBID is performed.

### Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.

- `--port` | `-P` (*number*)
  - The z/OSMF server port.
  - Default value: 443
- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.
  - Default value: true
- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)
  - Default value: https
  - Allowed values: http, https
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)



- The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Response Format Options

- `--response-format-filter` | `--rff` (*array*)
  - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '--response-format-type' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
  - The command response output format type. Must be one of the following:
    - table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.
    - list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.
    - object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.
    - string: Formats output data as a string. JSON objects/arrays are stringified.
  - Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
  - If "--response-format-type table" is specified, include the column headers in the output.

## Examples

- List the spool files of the job with JOBID JOB00123:

- `zowe zos-jobs list spool-files-by-jobid job00123`

## [zowe](#) › [zos-jobs](#) › [submit](#)

---

Submit a job (JCL).

## [zowe](#) › [zos-jobs](#) › [submit](#) › [data-set](#)

Submit a job (JCL) contained in a data set. The data set may be of type physical sequential or a PDS member. The command does not pre-validate the data set name. The command presents errors verbatim from the z/OSMF Jobs REST endpoints. For more information about z/OSMF Jobs API errors, see the z/OSMF Jobs API REST documentation.

### Usage

```
zowe zos-jobs submit data-set <dataset> [options]
```

### Positional Arguments

- `dataset` (*string*)
  - The z/OS data set containing the JCL to submit. You can specify a physical sequential data set (for example, "DATA.SET") or a partitioned data set qualified by a member (for example, "DATA.SET(MEMBER)").

### Options

- `--volume` | `--vol` (*string*)
  - The volume serial (VOLSER) where the data set resides. The option is required only when the data set is not catalogued on the system.
- `--wait-for-active` | `--wfa` (*boolean*)
  - Wait for the job to enter ACTIVE status before completing the command.
- `--wait-for-output` | `--wfo` (*boolean*)
  - Wait for the job to enter OUTPUT status before completing the command.
- `--view-all-spool-content` | `--vasc` (*boolean*)
  - Print all spool output. If you use this option you will wait for the job to complete.

- `--directory` | `-d` (*string*)
  - The local directory you would like to download the output of the job. Creates a subdirectory using the jobID as the name and files are titled based on DD names. If you use this option you will wait for the job to complete.
- `--extension` | `-e` (*string*)
  - A file extension to save the job output with. Default is '.txt'.
- `--jcl-symbols` | `--js` (*string*)
  - A string of JCL symbols to use for substitution. For symbol values with no spaces: "symbol1=value1 symbol2=value2 ...". When a value contains spaces, enclose the value in single quotes: "symbol1='value 1 with spaces' symbol2='value 2 with spaces' ...". To embed a single quote in a value, use two single quotes: "NAME=O"Brian".

## Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.  
  
Default value: 443
- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.  
  
Default value: true
- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this

option if you are not using an API mediation layer.

- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)

Default value: https  
Allowed values: http, https
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Response Format Options

- `--response-format-filter` | `--rff` (*array*)
  - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '--response-format-type' to reduce the output of a command to a single field/property or a list of a single field/property.

- `--response-format-type` | `--rft` (*string*)
  - The command response output format type. Must be one of the following:
 

table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.

list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.

object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
  - If "`--response-format-type table`" is specified, include the column headers in the output.

## Examples

- Submit the JCL in the data set "ibmuser.cntl(deploy)":
  - `zowe zos-jobs submit data-set "ibmuser.cntl(deploy)"`
- Submit the JCL in the data set "ibmuser.cntl(deploy)", wait for the job to complete and print all output from the job:
  - `zowe zos-jobs submit data-set "ibmuser.cntl(deploy)" --vasc`

## [zowe](#) › [zos-jobs](#) › [submit](#) › [local-file](#)

Submit a job (JCL) contained in a local file. The command presents errors verbatim from the z/OSMF Jobs REST endpoints. For more information about z/OSMF Jobs API errors, see the z/OSMF Jobs API REST documentation.

### Usage

```
zowe zos-jobs submit local-file <localFile> [options]
```

### Positional Arguments

- `localFile` (*string*)

- The local file containing the JCL to submit.

## Options

- `--wait-for-active` | `--wfa` (*boolean*)
  - Wait for the job to enter ACTIVE status before completing the command.
- `--wait-for-output` | `--wfo` (*boolean*)
  - Wait for the job to enter OUTPUT status before completing the command.
- `--view-all-spool-content` | `--vasc` (*boolean*)
  - Print all spool output. If you use this option you will wait for the job to complete.
- `--directory` | `-d` (*string*)
  - The local directory you would like to download the output of the job. Creates a subdirectory using the jobID as the name and files are titled based on DD names. If you use this option you will wait for the job to complete.
- `--extension` | `-e` (*string*)
  - A file extension to save the job output with. Default is '.txt'.
- `--jcl-symbols` | `--js` (*string*)
  - A string of JCL symbols to use for substitution. For symbol values with no spaces: "symbol1=value1 symbol2=value2 ...". When a value contains spaces, enclose the value in single quotes: "symbol1='value 1 with spaces' symbol2='value 2 with spaces' ...". To embed a single quote in a value, use two single quotes: "NAME=O'Brian".

## Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.

Default value: 443

- `--user` | `-u` (*string*)

- Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)

Default value: https  
Allowed values: http, https
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)

- The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Response Format Options

- `--response-format-filter` | `--rff` (*array*)
  - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '--response-format-type' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
  - The command response output format type. Must be one of the following:
    - table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.
    - list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.
    - object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.
    - string: Formats output data as a string. JSON objects/arrays are stringified.
  - Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
  - If "--response-format-type table" is specified, include the column headers in the output.

## Examples

- Submit the JCL in the file "iefbr14.txt":
  - `zowe zos-jobs submit local-file "iefbr14.txt"`



Submit a job (JCL) passed to the command via the stdin stream. The command presents errors verbatim from the z/OSMF Jobs REST endpoints. For more information about z/OSMF Jobs API errors, see the z/OSMF Jobs API REST documentation.

## Usage

```
zowe zos-jobs submit stdin [options]
```

## Options

- `--wait-for-active` | `--wfa` (*boolean*)
  - Wait for the job to enter ACTIVE status before completing the command.
- `--wait-for-output` | `--wfo` (*boolean*)
  - Wait for the job to enter OUTPUT status before completing the command.
- `--view-all-spool-content` | `--vasc` (*boolean*)
  - Print all spool output. If you use this option you will wait for the job to complete.
- `--directory` | `-d` (*string*)
  - The local directory you would like to download the output of the job. Creates a subdirectory using the jobID as the name and files are titled based on DD names. If you use this option you will wait for the job to complete.
- `--extension` | `-e` (*string*)
  - A file extension to save the job output with. Default is '.txt'.
- `--jcl-symbols` | `--js` (*string*)
  - A string of JCL symbols to use for substitution. For symbol values with no spaces: "symbol1=value1 symbol2=value2 ...". When a value contains spaces, enclose the value in single quotes: "symbol1='value 1 with spaces' symbol2='value 2 with spaces' ...". To embed a single quote in a value, use two single quotes: "NAME=O"Brian".

## Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)

- The z/OSMF server port.

Default value: 443

- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)

- Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Response Format Options

- `--response-format-filter` | `--rff` (*array*)
  - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '`--response-format-type`' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
  - The command response output format type. Must be one of the following:
    - table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.
    - list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.
    - object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.
    - string: Formats output data as a string. JSON objects/arrays are stringified.
  - Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
  - If "`--response-format-type table`" is specified, include the column headers in the output.

## Examples

- Submit the JCL in the file "iefbr14.txt" via standard in:
  - `zowe zos-jobs submit stdin < iefbr14.txt`

- Submit the JCL in the file "iefbr14.txt" via standard in from the output of another command:

- `cat iefbr14.txt | zowe zos-jobs submit stdin`

## [zowe](#) › [zos-jobs](#) › [view](#)

---

View details of z/OS jobs on spool/JES queues.

### [zowe](#) › [zos-jobs](#) › [view](#) › [job-status-by-jobid](#)

View status details of a single z/OS job on spool/JES queues. The command does not prevalidate the JOBID. The command presents errors verbatim from the z/OSMF Jobs REST endpoints (expect for "no jobs found").

#### Usage

`zowe zos-jobs view job-status-by-jobid <jobid> [options]`

#### Positional Arguments

- `jobid` (*string*)
  - The z/OS JOBID of the job you want to view. No prevalidation of the JOBID is performed.

#### Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.  
  
Default value: 443
- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)

- Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.

- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Response Format Options

- `--response-format-filter` | `--rff` (*array*)
  - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '`--response-format-type`' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
  - The command response output format type. Must be one of the following:
 

table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.

list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.

object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
  - If "`--response-format-type table`" is specified, include the column headers in the output.

## Examples

- View status and other details of the job with the job ID JOB00123:
  - `zowe zos-jobs view job-status-by-jobid j123`
- Print only the status (for example, "OUTPUT" or "ACTIVE") of the job with the job ID JOB00123:
  - `zowe zos-jobs view job-status-by-jobid j123 --rff status --rft string`

## [zowe](#) › [zos-jobs](#) › [view](#) › [spool-file-by-id](#)

View the contents of a spool file from a z/OS job on spool/JES queues. The command does not pre-validate the JOBID or spool ID. The command presents errors verbatim from the z/OSMF Jobs REST endpoints.

## Usage

zowe zos-jobs view spool-file-by-id <jobid> <spoolfileid> [options]

## Positional Arguments

- `jobid` (*string*)
  - The z/OS JOBID of the job containing the spool file you want to view. No pre-validation of the JOBID is performed.
- `spoolfileid` (*number*)
  - The spool file ID number for the spool file to view. Use the "zowe zos-jobs list spool-files-by-jobid" command to obtain spool ID [numbers](#). No pre-validation of the ID is performed.

## Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.  
  
Default value: 443
- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.  
  
Default value: true
- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.

- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)
  - Default value: https
  - Allowed values: http, https
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Examples

- View the spool file with ID 4 for the job with job ID JOB00123:
  - `zowe zos-jobs view spool-file-by-id JOB00123 4`



## zowe › zos-logs

---

Interact with z/OS logs.

## zowe › zos-logs › list

---

List z/OS logs by invoking z/OSMF REST API.

## zowe › zos-logs › list › logs

List z/OS operlog within a time range.

Use this operation to get the z/OS operations logs. It invokes z/OSMF REST API to retrieve logs.

Executing 'zowe zos-logs list logs' will by default return logs from current time and backwards to 10 minutes before.

Note: OPERLOG needs to be configured on z/OS server.

### Usage

```
zowe zos-logs list logs [options]
```

### Options

- `--start-time` | `--st` (*string*)
  - Specify the time in ISO-8601 time format from when z/OSMF will start to retrieve the logs. For example, '2021-01-26T03:33:18.065Z', '2021-01-26T11:33:18.065+08:00'. Default is the current time.
- `--direction` | `-d` (*string*)
  - Specify the direction when retrieving the message log. Either 'forward' or 'backward' is valid, case insensitive.  
  
Default value: backward  
Allowed values: forward, backward
- `--range` | `-r` (*string*)
  - Specify a time range in which the logs will be retrieved. The format is like nnnu, nnn is 1-999, u is one of 's', 'm', 'h', for example, '999s', '20m', '3h'.

Default value: 10m

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--host` | `-H` (*string*)
  - Host name of service on the mainframe.
- `--port` | `-P` (*number*)
  - Port number of service on the mainframe.
- `--user` | `-u` (*string*)
  - User name to authenticate to service on the mainframe.
- `--password` | `--pass` | `--pw` (*string*)
  - Password to authenticate to service on the mainframe.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.

Default value: true

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication

- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Examples

- List logs starting from '2021-07-26T03:38:37.098Z' and forwards to 5 minutes later:
  - `zowe zos-logs list logs --start-time 2021-07-26T03:38:37.098Z --range 5m --direction forward`
- List logs starting from '2021-07-26T03:38:37.098Z' and forwards to 5 minutes later. Alias version of the above command:
  - `zowe zos-logs list logs --st 2021-07-26T03:38:37.098Z -r 5m -d forward`
- List logs starting from '2021-07-26T03:38:37.098Z' and backwards to 5 minutes before:
  - `zowe zos-logs list logs --start-time 2021-07-26T03:38:37.098Z --range 5m`

## zowe › zos-ssh

---

Issue z/OS USS commands remotely using an SSH session. Output from the commands is displayed on the local terminal.

## zowe › zos-ssh › issue

---

Issue a z/OS USS command.

## zowe › zos-ssh › issue › command

Issue a z/OS USS command

### Usage

```
zowe zos-ssh issue command <command> [options]
```

### Positional Arguments

- `command` (*string*)
  - z/OS USS command to issue

### Options

- `--cwd` (*string*)
  - Working directory in which to execute the command

### z/OS Ssh Connection Options

- `--host` | `-H` (*string*)
  - The z/OS SSH server host name.
- `--port` | `-P` (*number*)
  - The z/OS SSH server port.

Default value: 22

- `--user` | `-u` (*string*)
  - Mainframe user name, which can be the same as your TSO login.

- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe password, which can be the same as your TSO password.
- `--privateKey` | `--key` | `--pk` (*string*)
  - Path to a file containing your private key, that must match a public key stored in the server for authentication
- `--keyPassphrase` | `--passphrase` | `--kp` (*string*)
  - Private key passphrase, which unlocks the private key.
- `--handshakeTimeout` | `--timeout` | `--to` (*number*)
  - How long in milliseconds to wait for the SSH handshake to complete.

## Profile Options

- `--ssh-profile` | `--ssh-p` (*string*)
  - The name of a (ssh) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.
  - Default value: true
- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication

- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Examples

- Issue a simple command, giving the working directory:
  - `zowe zos-ssh issue command "npm install express" --cwd /u/cicprov/mnt/CICPY01I/bundles/myapp`

## zowe › zos-tso

---

Issue TSO commands and interact with TSO address spaces.

## zowe › zos-tso › issue

---

Issue TSO commands.

## zowe › zos-tso › issue › command

Creates a TSO address space, issues a TSO command through the newly created address space, waits for the READY prompt to print the response, and terminates the TSO address space. All response data are returned to the user up to (but not including) the TSO 'READY' prompt.

### Usage

```
zowe zos-tso issue command <commandText> [options]
```

### Positional Arguments

- `commandText` (*string*)
  - The TSO command to issue.

### Options

- `--suppress-startup-messages` | `--ssm` (*boolean*)
  - Suppress console messages from start of address space.

### TSO ADDRESS SPACE OPTIONS

- `--account` | `-a` (*string*)
  - Your z/OS TSO/E accounting information.
- `--character-set` | `--cs` (*string*)
  - Character set for address space to convert messages and responses from UTF-8 to EBCDIC.

Default value: 697

- `--code-page` | `--cp` (*string*)
  - Codepage value for TSO/E address space to convert messages and responses from UTF-8 to EBCDIC.

Default value: 1047
- `--columns` | `--cols` (*number*)
  - The number of columns on a screen.

Default value: 80
- `--logon-procedure` | `-l` (*string*)
  - The logon procedure to use when creating TSO procedures on your behalf.

Default value: IZUFPROC
- `--region-size` | `--rs` (*number*)
  - Region size for the TSO/E address space.

Default value: 4096
- `--rows` (*number*)
  - The number of rows on a screen.

Default value: 24

## Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.

Default value: 443
- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)



- Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.  
  
Default value: true
- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)  
  
Default value: https  
Allowed values: http, https
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--tso-profile` | `--tso-p` (*string*)
  - The name of a (tso) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)

- The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Examples

- Issue the TSO command "status" to display information about jobs for your user ID:
  - `zowe zos-tso issue command "status"`

## [zowe](#) › [zos-tso](#) › [ping](#)

---

Ping a TSO address space, from which you previously started and received a token (a.k.a 'servlet-key').

### [zowe](#) › [zos-tso](#) › [ping](#) › [address-space](#)

Ping a TSO address space, from which you previously started and received a token (a.k.a 'servlet-key').

## Usage

```
zowe zos-tso ping address-space <servletKey> [options]
```

## Positional Arguments

- `servletKey` (*string*)
  - The servlet key from a previously started TSO address space.

## Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.

Default value: 443

- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)

Default value: https  
Allowed values: http, https
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Examples

- Ping the TSO address space identified by IBMUSER-329-aafkaaoc:
  - `zowe zos-tso ping address-space IBMUSER-329-aafkaaoc`

## zowe › zos-tso › send

---

Send data to TSO and collect responses until the prompt is reached.

### zowe › zos-tso › send › address-space

Send data to the TSO address space, from which you previously started and received a token (a.k.a 'servlet-key').

## Usage

```
zowe zos-tso send address-space <servletKey> [options]
```

## Positional Arguments

- `servletKey` (*string*)
  - The servlet key from a previously started TSO address space.

## Required Options

- `--data` (*string*)
  - The data to which we want to send to the TSO address space represented by the servlet key.

## Zosmf Connection Options

- `--host` | `-H` (*string*)

- The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.
  - Default value: 443
- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.
  - Default value: true
- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)
  - Default value: https
  - Allowed values: http, https
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.

- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Examples

- "Send the TIME TSO command to the TSO address space identified by IBMUSER-329-aafkaaoc":
  - `zowe zos-tso send address-space IBMUSER-329-aafkaaoc --data "TIME"`

## [zowe](#) › [zos-tso](#) › [start](#)

---

Start TSO/E address space.

## [zowe](#) › [zos-tso](#) › [start](#) › [address-space](#)

Start a TSO address space, from which you will receive a token (a.k.a 'servlet-key') for further address space interaction (e.g. termination).

## Usage

```
zowe zos-tso start address-space [options]
```

## TSO ADDRESS SPACE OPTIONS

- `--account` | `-a` (*string*)
  - Your z/OS TSO/E accounting information.
- `--character-set` | `--cs` (*string*)
  - Character set for address space to convert messages and responses from UTF-8 to EBCDIC.

Default value: 697

- `--code-page` | `--cp` (*string*)
  - Codepage value for TSO/E address space to convert messages and responses from UTF-8 to EBCDIC.

Default value: 1047

- `--columns` | `--cols` (*number*)
  - The number of columns on a screen.

Default value: 80

- `--logon-procedure` | `-l` (*string*)
  - The logon procedure to use when creating TSO procedures on your behalf.

Default value: IZUFPROC

- `--region-size` | `--rs` (*number*)
  - Region size for the TSO/E address space.

Default value: 4096

- `--rows` (*number*)
  - The number of rows on a screen.

Default value: 24

## Options

- `--servlet-key-only` | `--sko` (*boolean*)
  - Specify this option to print only the servlet key

## Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.

Default value: 443

- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--tso-profile` | `--tso-p` (*string*)
  - The name of a (tso) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)



- The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Examples

- Start TSO/E address space:
  - `zowe zos-tso start address-space`
- Start TSO/E address space, and receive response in JSON format:
  - `zowe zos-tso start address-space --rfj`
- Start TSO/E address space, and print only the servlet key:
  - `zowe zos-tso start address-space --sko`

## [zowe](#) › [zos-tso](#) › [stop](#)

---

Stop TSO/E address space.

## [zowe](#) › [zos-tso](#) › [stop](#) › [address-space](#)

Stop a TSO address space, from which you previously started and received a token (a.k.a 'servlet-key').

### Usage

```
zowe zos-tso stop address-space <servletkey> [options]
```

### Positional Arguments

- `servletkey` (*string*)
  - The servlet key from a previously started TSO address space.

## Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.
  - Default value: 443
- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.
  - Default value: true
- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)
  - Default value: https
  - Allowed values: http, https
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

### Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

### Examples

- Stop the TSO address space identified by IBMUSER-329-aafkaaoc:
  - `zowe zos-tso stop address-space IBMUSER-329-aafkaaoc`

## zowe › zos-workflows

---

Create and manage z/OSMF workflows on a z/OS system.

## zowe › zos-workflows › archive

---

Archive workflow instance in z/OSMF.

## zowe › zos-workflows › archive › active-workflow

Archive an active workflow instance in z/OSMF.

### Usage

```
zowe zos-workflows archive active-workflow [options]
```

### Options

- `--workflow-name` | `--wn` (*string*)
  - The name of the workflow to be archived.
- `--workflow-key` | `--wk` (*string*)
  - The workflow key of the workflow to be archived.

### Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.  
  
Default value: 443
- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)

- Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)

Default value: https  
Allowed values: http, https
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)

- The value of the token to pass to the API.

## Response Format Options

- `--response-format-filter` | `--rff` (*array*)
  - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '`--response-format-type`' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
  - The command response output format type. Must be one of the following:
    - table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.
    - list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.
    - object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.
    - string: Formats output data as a string. JSON objects/arrays are stringified.
  - Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
  - If "`--response-format-type table`" is specified, include the column headers in the output.

## Examples

- Archive a workflow with workflow name "testworkflow":
  - `zowe zos-workflows archive active-workflow --wn "testworkflow"`
- Archive multiple workflows with workflow names starting with "test":
  - `zowe zos-workflows archive active-workflow --wn "test.*"`
- Archive a workflow with workflow key "123-456-abv-xyz":
  - `zowe zos-workflows archive active-workflow --wk "123-456-abv-xyz"`

## zowe › zos-workflows › create

---

Create a z/OSMF workflow on a z/OS system.

### zowe › zos-workflows › create › workflow-from-data-set

Create a z/OSMF workflow on a z/OS system using a Data set

#### Usage

```
zowe zos-workflows create workflow-from-data-set <workflowName> [options]
```

#### Positional Arguments

- `workflowName` (*string*)
  - Name of the workflow

#### Required Options

- `--data-set` | `--ds` (*string*)
  - Data set that contains a workflow definition.
- `--system-name` | `--sn` (*string*)
  - z/OS system to execute the workflow.
- `--owner` | `--ow` (*string*)
  - User ID of the workflow owner. This user can perform the workflow steps or delegate the steps to other users.

#### Options

- `--variables-input-file` | `--vif` (*string*)
  - Specifies an optional properties file that you can use to pre-specify values for one or more of the variables that are defined in the workflow definition file.
- `--variables` | `--vs` (*string*)
  - Includes a list of variables for the workflow. The variables that you specify here take precedence over the variables that are specified in the workflow variable input file. Make

sure the value meets all regular expression requirements set for the corresponding variable.

- `--assign-to-owner` | `--ato` (*boolean*)
  - Indicates whether the workflow steps are assigned to the workflow owner.
- `--access-type` | `--at` (*string*)
  - Specifies the access type for the workflow. Public, Restricted or Private.  
Allowed values: Public, Restricted, Private
- `--delete-completed` | `--dc` (*boolean*)
  - Whether the successfully completed jobs to be deleted from the JES spool.
- `--overwrite` | `--ov` (*boolean*)
  - Replaces an existing workflow with a new workflow.

## Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.  
Default value: 443
- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.  
Default value: true
- `--base-path` | `--bp` (*string*)



- The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)

Default value: https  
Allowed values: http, https
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Response Format Options

- `--response-format-filter` | `--rff` (*array*)
  - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields.

In addition, you can use this option in conjunction with '--response-format-type' to reduce the output of a command to a single field/property or a list of a single field/property.

- `--response-format-type` | `--rft` (*string*)

- The command response output format type. Must be one of the following:

`table`: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.

`list`: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.

`object`: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

`string`: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string

- `--response-format-header` | `--rfh` (*boolean*)

- If "--response-format-type table" is specified, include the column headers in the output.

## Examples

- Create a workflow with name "testworkflow" using the data set "TESTID.WKFLOW" that contains the workflow definition xml on the system "TESTM1" with owner "OTHERID" and delete workflow with the same name if it already exist in z/OSMF:
  - ```
zowe zos-workflows create workflow-from-data-set "testworkflow" --data-set "TESTID.WKFLOW" --system-name "TESTM1" --owner "OTHERID" --overwrite
```
- Create a workflow with name "testworkflow" using data set "TESTID.WKFLOW" containing workflow definition xml, on system "TESTM1" with owner "MYSYSID" and delete succesfully completed jobs:
 - ```
zowe zos-workflows create workflow-from-data-set "testworkflow" --data-set "TESTID.WKFLOW" --system-name "TESTM1" --owner "MYSYSID" --delete-completed
```
- Create a workflow with name "testworkflow" using data set "TESTID.WKFLOW" containing workflow definition xml, on system "TESTM1" with owner "MYSYSID" and with variable values in the member PROPERTIES of data set TESTID.DATA:

- `zowe zos-workflows create workflow-from-data-set "testworkflow" --data-set "TESTID.WKFLOW" --system-name "TESTM1" --owner "MYSYSID" --variables-input-file TESTID.DATA(PROPERTIES)`
- Create a workflow with name "testworkflow" using the data set "TESTID.WKFLOW" that contains a workflow definition xml, on a system "TESTM1" with owner "MYSYSID" and with the variable name DUMMYVAR and the value DUMMYVAL. Assign it to the owner:
  - `zowe zos-workflows create workflow-from-data-set "testworkflow" --data-set "TESTID.WKFLOW" --system-name "TESTM1" --owner "MYSYSID" --variables DUMMYVAR=DUMMYVAL --assign-to-owner`

## [zowe](#) › [zos-workflows](#) › [create](#) › [workflow-from-local-file](#)

Create a z/OSMF workflow on a z/OS system using a Local file

### Usage

```
zowe zos-workflows create workflow-from-local-file <workflowName> [options]
```

### Positional Arguments

- `workflowName` (*string*)
  - Name of the workflow

### Required Options

- `--local-file` | `--lf` (*string*)
  - Local file that contains workflow definiton.
- `--system-name` | `--sn` (*string*)
  - z/OS system to execute the workflow.
- `--owner` | `--ow` (*string*)
  - User ID of the workflow owner. This user can perform the workflow steps or delegate the steps to other users.

### Options

- `--variables-input-file` | `--vif` (*string*)

- Specifies an optional properties file that you can use to pre-specify values for one or more of the variables that are defined in the workflow definition file.
- `--variables` | `--vs` (*string*)
  - Includes a list of variables for the workflow. The variables that you specify here take precedence over the variables that are specified in the workflow variable input file. Make sure the value meets all regular expression requirements set for the corresponding variable.
- `--assign-to-owner` | `--ato` (*boolean*)
  - Indicates whether the workflow steps are assigned to the workflow owner.
- `--access-type` | `--at` (*string*)
  - Specifies the access type for the workflow. Public, Restricted or Private.  
Allowed values: Public, Restricted, Private
- `--delete-completed` | `--dc` (*boolean*)
  - Whether the successfully completed jobs to be deleted from the JES spool.
- `--overwrite` | `--ov` (*boolean*)
  - Replaces an existing workflow with a new workflow.
- `--remote-directory` | `--rd` (*string*)
  - The remote uss directory where the files are to be uploaded. The directory has to exist
- `--keep-files` | `--kf` (*boolean*)
  - Avoid deletion the uploaded files in /tmp or another specified directory after successful execution.  
Default value: false

## Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)

- The z/OSMF server port.

Default value: 443

- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)

- Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Response Format Options

- `--response-format-filter` | `--rff` (*array*)
  - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '`--response-format-type`' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
  - The command response output format type. Must be one of the following:
    - table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.
    - list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.
    - object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.
    - string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
  - If "`--response-format-type table`" is specified, include the column headers in the output.

## Examples

- Create a workflow with name "testworkflow" using the local file "TESTID\_WKFLOW.xml" that contains the workflow definition xml on the system "TESTM1" with owner "OTHERID" and

delete workflow with the same name if it already exist in z/OSMF:

- `zowe zos-workflows create workflow-from-local-file "testworkflow" --local-file "TESTID_WKFLOW.xml" --system-name "TESTM1" --owner "OTHERID" --overwrite`

## [zowe](#) › [zos-workflows](#) › [create](#) › [workflow-from-uss-file](#)

Create a workflow instance in z/OSMF using a USS file

### Usage

```
zowe zos-workflows create workflow-from-uss-file <workflowName> [options]
```

### Positional Arguments

- `workflowName` (*string*)
  - Name of the workflow instance to create

### Required Options

- `--uss-file` | `--uf` (*string*)
  - Uss file that contains workflow definiton.
- `--system-name` | `--sn` (*string*)
  - z/OS system to execute the workflow.
- `--owner` | `--ow` (*string*)
  - User ID of the workflow owner. This user can perform the workflow steps or delegate the steps to other users.

### Options

- `--variables-input-file` | `--vif` (*string*)
  - Specifies an optional properties file that you can use to pre-specify values for one or more of the variables that are defined in the workflow definition file.
- `--variables` | `--vs` (*string*)
  - Includes a list of variables for the workflow. The variables that you specify here take precedence over the variables that are specified in the workflow variable input file. Make

sure the value meets all regular expression requirements set for the corresponding variable.

- `--assign-to-owner` | `--ato` (*boolean*)
  - Indicates whether the workflow steps are assigned to the workflow owner.
- `--access-type` | `--at` (*string*)
  - Specifies the access type for the workflow. Public, Restricted or Private.  
Allowed values: Public, Restricted, Private
- `--delete-completed` | `--dc` (*boolean*)
  - Whether the successfully completed jobs to be deleted from the JES spool.
- `--overwrite` | `--ov` (*boolean*)
  - Replaces an existing workflow with a new workflow.

## Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.  
Default value: 443
- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.  
Default value: true
- `--base-path` | `--bp` (*string*)



- The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)

Default value: https  
Allowed values: http, https
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Response Format Options

- `--response-format-filter` | `--rff` (*array*)
  - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields.

In addition, you can use this option in conjunction with '--response-format-type' to reduce the output of a command to a single field/property or a list of a single field/property.

- `--response-format-type` | `--rft` (*string*)

- The command response output format type. Must be one of the following:

`table`: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.

`list`: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.

`object`: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

`string`: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string

- `--response-format-header` | `--rfh` (*boolean*)

- If "--response-format-type table" is specified, include the column headers in the output.

## Examples

- Create a workflow with name "testworkflow" using uss file "/path/workflow.xml" containing workflow definition, on system "TESTM1" with owner "OTHERID" and delete workflow with the same name if it already exist in z/OSMF:

- ```
zowe zos-workflows create workflow-from-uss-file "testworkflow" --uss-file "/path/workflow.xml" --system-name "TESTM1" --owner "OTHERID" --overwrite
```

- Create a workflow with name "testworkflow" using uss file "/path/workflow.xml" containing workflow definition, on system "TESTM1" with owner "MYSYSID" and delete successfully completed jobs:

- ```
zowe zos-workflows create workflow-from-uss-file "testworkflow" --uss-file "/path/workflow.xml" --system-name "TESTM1" --owner "MYSYSID" --delete-completed
```

- Create a workflow with name "testworkflow" using uss file "/path/workflow.xml" containing workflow definition, on system "TESTM1" with owner "MYSYSID" and with variable values in the member PROPERTIES of data set TESTID.DATA:

- `zowe zos-workflows create workflow-from-uss-file "testworkflow" --uss-file "/path/workflow.xml" --system-name "TESTM1" --owner "MYSYSID" --variables-input-file TESTID.DATA(PROPERTIES)`
- Create a workflow with name "testworkflow" using uss file "/path/workflow.xml" containing workflow definition, on system "TESTM1" with owner "MYSYSID" and with variables VAR1 and VAR2 with values DUMMYVAL1 and DUMMYVAL2, and assign it to the owner:
  - `zowe zos-workflows create workflow-from-uss-file "testworkflow" --uss-file "/path/workflow.xml" --system-name "TESTM1"--variables VAR1=DUMMYVAL1,VAR2=DUMMYVAL2 --owner "MYSYSID" --assign-to-owner`

## [zowe](#) › [zos-workflows](#) › [delete](#)

---

Delete an active workflow or an archived workflow from z/OSMF.

### [zowe](#) › [zos-workflows](#) › [delete](#) › [active-workflow](#)

Delete an active workflow instance in z/OSMF

#### Usage

```
zowe zos-workflows delete active-workflow [options]
```

#### Options

- `--workflow-key` | `--wk` (*string*)
  - Delete active workflow by specified workflow key
- `--workflow-name` | `--wn` (*string*)
  - Delete active workflow by specified workflow name

#### Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.

Default value: 443

- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)

Default value: https  
Allowed values: http, https
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Examples

- To delete a workflow instance in z/OSMF with workflow key "d043b5f1-adab-48e7-b7c3-d41cd95fa4b0":
  - `zowe zos-workflows delete active-workflow --workflow-key "d043b5f1-adab-48e7-b7c3-d41cd95fa4b0"`
- To delete a workflow instance in z/OSMF with workflow name "testWorkflow":
  - `zowe zos-workflows delete active-workflow --workflow-name "testWorkflow"`
- To delete multiple workflow instances in z/OSMF with names starting with "test":
  - `zowe zos-workflows delete active-workflow --workflow-name "test.*"`

## [zowe](#) › [zos-workflows](#) › [delete](#) › [archived-workflow](#)

Delete an archived workflow from z/OSMF

### Usage

`zowe zos-workflows delete archived-workflow [options]`

### Options

- `--workflow-key` | `--wk` (*string*)
  - Delete an archived workflow by specified workflow key
- `--workflow-name` | `--wn` (*string*)
  - Delete an archived workflow by specified workflow name

### Zosmf Connection Options

- `--host` | `-H` (*string*)

- The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.
  - Default value: 443
- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.
  - Default value: true
- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)
  - Default value: https
  - Allowed values: http, https
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.

- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Examples

- To delete an archived workflow from z/OSMF with workflow key "d043b5f1-adab-48e7-b7c3-d41cd95fa4b0":
  - `zowe zos-workflows delete archived-workflow --workflow-key "d043b5f1-adab-48e7-b7c3-d41cd95fa4b0"`
- To delete an archived workflow from z/OSMF with workflow name "testWorkflow":
  - `zowe zos-workflows delete archived-workflow --workflow-name "testWorkflow"`
- To delete multiple archived workflows from z/OSMF with names beginning with "test":
  - `zowe zos-workflows delete archived-workflow --workflow-name "test.*"`

## [zowe](#) › [zos-workflows](#) › [list](#)

---

List the z/OSMF workflows for a system or a sysplex with filter options.

### [zowe](#) › [zos-workflows](#) › [list](#) › [active-workflow-details](#)

Get the details of an active z/OSMF workflow

## Usage

```
zowe zos-workflows list active-workflow-details [options]
```

## Options

- `--workflow-name` | `--wn` (*string*)
  - List active workflow details by specified workflow name.
- `--workflow-key` | `--wk` (*string*)
  - List active workflow details by specified workflow key.
- `--list-steps` | `--ls` (*boolean*)
  - Optional parameter for listing steps and their properties.
- `--steps-summary-only` | `--sso` (*boolean*)
  - Optional parameter that lists steps summary only.
- `--list-variables` | `--lv` (*boolean*)
  - Optional parameter for listing variables and their properties.
- `--skip-workflow-summary` | `--sws` (*boolean*)
  - Optional parameter that skips the default workflow summary.

## Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.
  - Default value: 443
- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.



Default value: true

- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Examples

- To list the details of an active workflow with key "7c62c790-0340-86b2-61ce618d8f8c" including its steps and variables:
  - `zowe zos-workflows list active-workflow-details --workflow-key "7c62c790-0340-86b2-61ce618d8f8c" --list-steps --list-variables`
- To list the details of an active workflow with name "testWorkflow" including its steps and variables:
  - `zowe zos-workflows list active-workflow-details --workflow-name "testWorkflow" --list-steps --list-variables`

## [zowe](#) › [zos-workflows](#) › [list](#) › [active-workflows](#)

List active workflow instance(s) in z/OSMF.

Multiple filters can be used together.

Omitting all options will list all workflows on the sysplex

### Usage

```
zowe zos-workflows list active-workflows [options]
```

### Options

- `--workflow-name` | `--wn` (*string*)
  - Filter by workflow name. For wildcard use `.*`
- `--category` | `--cat` (*string*)
  - Filter by the category of the workflows, which is either general or configuration.
- `--system` | `--sys` (*string*)
  - Filter by the nickname of the system on which the workflows is/are active.
- `--owner` | `--ow` (*string*)
  - Filter by owner of the workflow(s) (a valid z/OS user ID).
- `--vendor` | `--vd` (*string*)
  - Filter by the name of the vendor that provided the workflow(s) definition file.
- `--status-name` | `--sn` (*string*)

- Filter by the status of the workflow(s).

Allowed values: in-progress, complete, automation-in-progress, canceled

## Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.
  - Default value: 443
- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.
  - Default value: true
- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)
  - Default value: https
  - Allowed values: http, https
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)

- The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Response Format Options

- `--response-format-filter` | `--rff` (*array*)
  - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '--response-format-type' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
  - The command response output format type. Must be one of the following:
    - table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.
    - list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.
    - object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.

string: Formats output data as a string. JSON objects/arrays are stringified.

Allowed values: table, list, object, string

- `--response-format-header` | `--rfh` (*boolean*)
  - If "`--response-format-type table`" is specified, include the column headers in the output.

## Examples

- List the workflow with name "testworkflow":
  - `zowe zos-workflows list active-workflows --wn "testworkflow"`
- List multiple active workflows on the entire sysplex with names containing "workflow":
  - `zowe zos-workflows list active-workflows --wn ".*workflow.*"`
- List multiple active workflows on system "IBMSYS" with names beginning with "testW" that are in status "complete":
  - `zowe zos-workflows list active-workflows --wn "test.*" --sys "IBMSYS" --sn "complete"`

## [zowe](#) › [zos-workflows](#) › [list](#) › [archived-workflows](#)

List the archived z/OSMF workflows for a system or sysplex.

### Usage

```
zowe zos-workflows list archived-workflows [options]
```

### Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.  
  
Default value: 443
- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.

- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.  
  
Default value: true
- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)  
  
Default value: https  
Allowed values: http, https
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.

- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Response Format Options

- `--response-format-filter` | `--rff` (*array*)
  - Filter (include) fields in the response. Accepts an array of field/property names to include in the output response. You can filter JSON objects properties OR table columns/fields. In addition, you can use this option in conjunction with '`--response-format-type`' to reduce the output of a command to a single field/property or a list of a single field/property.
- `--response-format-type` | `--rft` (*string*)
  - The command response output format type. Must be one of the following:
    - table: Formats output data as a table. Use this option when the output data is an array of homogeneous JSON objects. Each property of the object will become a column in the table.
    - list: Formats output data as a list of strings. Can be used on any data type (JSON objects/arrays) are stringified and a new line is added after each entry in an array.
    - object: Formats output data as a list of prettified objects (or single object). Can be used in place of "table" to change from tabular output to a list of prettified objects.
    - string: Formats output data as a string. JSON objects/arrays are stringified.
  - Allowed values: table, list, object, string
- `--response-format-header` | `--rfh` (*boolean*)
  - If "`--response-format-type table`" is specified, include the column headers in the output.

## [zowe](#) › [zos-workflows](#) › [list](#) › [definition-file-details](#)

Retrieve the contents of a z/OSMF workflow definition from a z/OS system.

### Usage

```
zowe zos-workflows list definition-file-details <definitionFilePath> [options]
```

### Positional Arguments

- `definitionFilePath` (*string*)

- Specifies the location of the workflow definition file, which is either a UNIX path name or a fully qualified z/OS data set name.

## Options

- `--list-steps` | `--ls` (*boolean*)
  - Optional parameter for listing steps and their properties.
- `--list-variables` | `--lv` (*boolean*)
  - Optional parameter for listing variables and their properties.

## Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.  
  
Default value: 443
- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.  
  
Default value: true
- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)



- The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Examples

- To list the contents of a workflow definition stored in the UNIX file `"/user/dir/workflow.xml"` including its steps and variables:
  - `zowe zos-workflows list definition-file-details "/user/dir/workflow.xml" --list-steps --list-variables`
- To list the contents of a workflow definition stored in the z/OS data set `"USER.DATA.SET.XML"` including its steps and variables:
  - `zowe zos-workflows list definition-file-details "USER.DATA.SET.XML" --list-steps --list-variables`

## zowe › zos-workflows › start

---

Start a z/OSMF workflow on a z/OS system.

### zowe › zos-workflows › start › workflow-full

Will run workflow from the beginning to the end or to the first manual step.

#### Usage

```
zowe zos-workflows start workflow-full [options]
```

#### Options

- `--workflow-key` | `--wk` (*string*)
  - Workflow key of workflow instance to be started
- `--workflow-name` | `--wn` (*string*)
  - Workflow name of workflow instance to be started
- `--resolve-conflict-by` | `--rcb` (*string*)
  - How variable conflicts should be handled.  
Options:  
outputFileValue: Allow the output file values to override the existing values.  
existingValue: Use the existing variables values instead of the output file values.  
leaveConflict: Automation is stopped. The user must resolve the conflict manually.  
  
Default value: outputFileValue  
Allowed values: outputFileValue, existingValue, leaveConflict
- `--wait` | `-w` (*boolean*)
  - Identifies whether to wait for workflow instance to finish.

#### Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.

Default value: 443

- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.

Default value: true

- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)

Default value: https

Allowed values: http, https

- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Examples

- To start a workflow instance in z/OSMF with workflow key "d043b5f1-adab-48e7-b7c3-d41cd95fa4b0":
  - `zowe zos-workflows start workflow-full --workflow-key "d043b5f1-adab-48e7-b7c3-d41cd95fa4b0"`
- To start a workflow instance in z/OSMF with workflow key "d043b5f1-adab-48e7-b7c3-d41cd95fa4b0" and wait for it to be finished:
  - `zowe zos-workflows start workflow-full --workflow-key "d043b5f1-adab-48e7-b7c3-d41cd95fa4b0" --wait`
- To start a workflow instance in z/OSMF with workflow key "d043b5f1-adab-48e7-b7c3-d41cd95fa4b0" and if there is a conflict in variable's value use the value that is in output file:
  - `zowe zos-workflows start workflow-full --workflow-key "d043b5f1-adab-48e7-b7c3-d41cd95fa4b0" --resolve-conflict-by "outputFileValue"`
- To start a workflow instance in z/OSMF with workflow name "testWorkflow":
  - `zowe zos-workflows start workflow-full --workflow-name "testWorkflow"`

## [zowe](#) › [zos-workflows](#) › [start](#) › [workflow-step](#)

Will run given step of workflow instance plus following steps if specified by `--perform-following-steps` option.

### Usage

```
zowe zos-workflows start workflow-step <stepName> [options]
```

### Positional Arguments

- `stepName` (*string*)
  - Specifies the step name that will be run.

## Options

- `--workflow-key` | `--wk` (*string*)
  - Workflow key of workflow instance to be started
- `--workflow-name` | `--wn` (*string*)
  - Workflow name of workflow instance to be started
- `--resolve-conflict-by` | `--rcb` (*string*)
  - How variable conflicts should be handled.  
Options:  
outputFileValue: Allow the output file values to override the existing values.  
existingValue: Use the existing variables values instead of the output file values.  
leaveConflict: Automation is stopped. The user must resolve the conflict manually.  
  
Default value: outputFileValue  
Allowed values: outputFileValue, existingValue, leaveConflict
- `--perform-following-steps` | `--pfs` (*boolean*)
  - Identifies whether to perform also following steps in the workflow instance.  
  
Default value: false

## Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.  
  
Default value: 443
- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.

- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.

Default value: true
- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)

Default value: https  
Allowed values: http, https
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.

- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Examples

- To start step "Step1" only in a workflow instance in z/OSMF with workflow key "d043b5f1-adab-48e7-b7c3-d41cd95fa4b0":
  - `zowe zos-workflows start workflow-step "Step1" --workflow-key "d043b5f1-adab-48e7-b7c3-d41cd95fa4b0"`
- To start a workflow instance in z/OSMF from step "Step1" with workflow key "d043b5f1-adab-48e7-b7c3-d41cd95fa4b0":
  - `zowe zos-workflows start workflow-step "Step1" --workflow-key "d043b5f1-adab-48e7-b7c3-d41cd95fa4b0" --perform-following-steps`
- To start step "Step1" only in a workflow instance in z/OSMF with workflow key "d043b5f1-adab-48e7-b7c3-d41cd95fa4b0" and if there is a conflict in variable's value use the value that is in output file:
  - `zowe zos-workflows start workflow-step "Step1" --workflow-key "d043b5f1-adab-48e7-b7c3-d41cd95fa4b0" --resolve-conflict-by "outputFileValue"`
- To start step "Step1" only in a workflow instance in z/OSMF with workflow name "testWorkflow":
  - `zowe zos-workflows start workflow-step "Step1" --workflow-name "testWorkflow"`

## zowe › zosmf

---

Retrieve and show the properties of a z/OSMF web server.

## zowe › zosmf › check

---

Confirm that z/OSMF is running on a specified system and gather information about the z/OSMF server for diagnostic purposes.

## zowe › zosmf › check › status

Confirm that z/OSMF is running on a system specified in your profile and gather information about the z/OSMF server for diagnostic purposes. The command outputs properties of the z/OSMF server such as version, hostname, and installed plug-ins.

### Usage

```
zowe zosmf check status [options]
```

### Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.  
Default value: 443
- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.  
Default value: true



- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)
 

Default value: https  
Allowed values: http, https
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Examples

- Report the status of the z/OSMF server that you specified in your default z/OSMF profile:
  - `zowe zosmf check status`

- Report the status of the z/OSMF server that you specified in a supplied z/OSMF profile:
  - `zowe zosmf check status --zosmf-profile SomeZosmfProfileName`
- Report the status of the z/OSMF server that you specified manually via command line:
  - `zowe zosmf check status --host myhost --port 443 --user myuser --password mypass`

## [zowe](#) › [zosmf](#) › [list](#)

---

Obtain a list of systems that are defined to a z/OSMF instance.

### [zowe](#) › [zosmf](#) › [list](#) › [systems](#)

Obtain a list of systems that are defined to a z/OSMF instance.

#### Usage

```
zowe zosmf list systems [options]
```

#### Zosmf Connection Options

- `--host` | `-H` (*string*)
  - The z/OSMF server host name.
- `--port` | `-P` (*number*)
  - The z/OSMF server port.  
Default value: 443
- `--user` | `-u` (*string*)
  - Mainframe (z/OSMF) user name, which can be the same as your TSO login.
- `--password` | `--pass` | `--pw` (*string*)
  - Mainframe (z/OSMF) password, which can be the same as your TSO password.
- `--reject-unauthorized` | `--ru` (*boolean*)
  - Reject self-signed certificates.  
Default value: true

- `--base-path` | `--bp` (*string*)
  - The base path for your API mediation layer instance. Specify this option to prepend the base path to all z/OSMF resources when making REST requests. Do not specify this option if you are not using an API mediation layer.
- `--protocol` (*string*)
  - The protocol used (HTTP or HTTPS)
 

Default value: https  
Allowed values: http, https
- `--cert-file` (*local file path*)
  - The file path to a certificate file to use for authentication
- `--cert-key-file` (*local file path*)
  - The file path to a certificate key file to use for authentication

## Profile Options

- `--zosmf-profile` | `--zosmf-p` (*string*)
  - The name of a (zosmf) profile to load for this command execution.
- `--base-profile` | `--base-p` (*string*)
  - The name of a (base) profile to load for this command execution.

## Base Connection Options

- `--token-type` | `--tt` (*string*)
  - The type of token to get and use for the API. Omit this option to use the default token type, which is provided by 'zowe auth login'.
- `--token-value` | `--tv` (*string*)
  - The value of the token to pass to the API.

## Examples

- Obtain a list of systems defined to a z/OSMF instance with your default z/OSMF profile:
  - `zowe zosmf list systems`

- Obtain a list of systems defined to a z/OSMF instance for the specified z/OSMF profile:
  - `zowe zosmf list systems --zosmf-profile SomeZosmfProfileName`
- Obtain a list of the systems defined to a z/OSMF instance that you specified in the command line:
  - `zowe zosmf list systems --host myhost --port 443 --user myuser --password mypass`